

RYAN® MATAWAY® VERTICAL SLICER/DETHATCHER

QUICK SPECS

ENGINE: 11-hp OHV

Kohler® Command Pro

OPTIONAL REELS:

Flail Type

Fixed Type

DIMENSIONS:

Weight: 304 lbs. (138 kg)

Length: 54 in. (1.4 m)

Height: 43 in. (1.1 m)

Width: 35.5 in. (0.9 m)



Heavy-duty dethatcher.

IMPROVE GRASS CONDITION BY DETHATCHING

Remove layers of dead grass, roots and debris matted between the soil and the growing grass.

Help keep grass greener and healthier while minimizing the chance of disease.

RELIABLE CONSTRUCTION

All-welded frame and high-quality components to ensure long lasting product with commercial durability.

OPTIONAL REELS

Flail or fixed blade type vertical slicer/dethatcher reels; Match the cutting blade, spacing and dethatcher reels with the job and desired results.

HEAVY-DUTY

Heavy-duty, front-wheel drive, self-propelled dethatcher with ground-engaging vertical slicing capabilities.

DEALER INFO:



WHEN PERFORMANCE MATTERS™

©2005 Jacobsen, A Textron Company.
1-888-922-TURF or www.ryanturf.com



MODELS

MATAWAY® VERTICAL SLICER/DETHATCHER	
Engine	4-cycle OHV Kohler® Command Pro; cast-iron bore; recoil starter; dual-element air cleaner
Horsepower (@ 3,600 rpm)	11 (8 kW)
Displacement	24.3 cu. in. (398 cc)
Oil Capacity	2 qt. (1.9 L)

SPECIFICATIONS

UNIT	
Clutch	Spring-loaded belt tightener
Primary Drive	4L-section V-belt to front wheels by gear box and sealed roller chain; triple 3V-section V-belts from engine to reel
Lubrication	Oil splash in gear case; pressure grease fitting elsewhere
Cutting Depth	Adjustable to any desired depth up to 1.5 in. (38 mm)
Slicing Width	19 in. (483 mm)
Front Tires	Two 10.4 x 4.10-4, 2-ply, pneumatic; knob tread
Rear Tires	Two 10.25 x 4.10-4, 2-ply, pneumatic; sawtooth tread
DIMENSIONS	
Weight	304 lbs. (1.38 kg) with reels
Width	35.5 in. (0.9 m)
Length	54 in. (1.4 m)
Height	43 in. (1.1 m)

REELS

OPTIONAL VERTICAL SLICER/DETHATCHER	
Flail Blade Type	1/8 in. (3 mm) at 1 in. (25 mm) spacing
Fixed Blade Type	1/32 in. (1 mm) at 1/2 in. (13 mm) spacing; 1/32 in. (1 mm) at 1 in. (25 mm) spacing; 1/16 in. (2 mm) at 1 in. (25 mm) spacing; 1/16 in. (2 mm) at 1 1/2 in. (38 mm) spacing

NOTE: Specifications, while correct at time of printing, may change without notice.