

RYAN®

By Jacobsen

TOW-BEHIND LAWNAIRE® AERATOR



The aerator for smaller fields delivers big results.

Specifications, while correct at time of printing, may change without notice.

Ryan® is a registered trademark of Jacobsen, A Textron Company
© 2003, Jacobsen, A Textron Company
Charlotte, North Carolina
www.jacobsen.com

TOW-BEHIND LAWNLAIRE® AERATOR

(Fits all Cushman® Turf-Truckster® models.)

UNIT

Frame	1.5 in. (38 mm) sq. x 0.1875 in. (5 mm) wall tube
Hitch	Clevis™ and pin type
Axles	
Aerating Wheel	1.25 in. (32 mm) diameter
Transport Wheel	0.75 in. (19 mm) diameter
Aerating Wheels	Cast iron with sintered bushing; pressure lubrication fitting; grooved for mounting aerating tines on both sides; each wheel weighs 75 lbs. (34 kg)
Tines	Eight per wheel (48 total); one set of 0.75 in. (19 mm) diameter coring tines standard; optional 0.5 in. (13 mm) diameter coring, 7.5 in. (191 mm) slicing or 6 in. (152 mm) open-spoon; tines are formed from austemper-hardened alloy steel; wheels can be mounted with double tines; 16 per wheel (96 total)
Aerating Width	36 in. (914 mm)
Coring Depth	Up to 4 in. (102 mm)
Aeration Pattern	6 in. x 6 in. (152 mm x 152 mm) with single tines; 3 in. x 3 in. (76 mm x 76 mm) with double tines
Holes per Square Foot	Up to nine with single tines; up to 18 with double tines
Productivity	1.5 acres/hr. (0.6 ha/h) at 4 mph (6 km/h)
Towing Speed	10 mph (16 km/h) maximum
Transport Lift	Wheels are pivotable about extended axle shaft using removable lever or 700 psi hydraulic lift
Transport Tires	4.10/3.50-4, 2-ply, pneumatic tires with ball bearings
Options	Hydraulic or manual lift

DIMENSIONS

Weight	500 lbs. (227 kg)
Width	46 in. (1.2 m)
Length	68.5 in. (1.7 m)
Height	31 in. (787 mm)

Specifications, while correct at time of printing, may change without notice.