

[Click here to print this page](#)[Close Window](#)

Specimen Label

SHAKE DOWN

LIQUID ANTIFOAM

Ingredients:

Polydimethylsiloxane

Inorganic/Organic Carrier

NET CONTENTS: 16 oz (0.47 liters)

SHAKE DOWN Antifoam eliminates unwanted foaming in spray applications involving recirculating sprayers and other high agitation equipment.

For best results, add SHAKE DOWN to solution prior to foaming. If foam already exists, add SHAKE DOWN until foam is eliminated.

SHAKE DOWN is a Polydimethylsiloxane approved for use as a spray adjuvant under 40 CFR 180.1001 (c) at labeled rates.

RATE: 1/2 - 1 oz. SHAKE DOWN per 100 gallons (15-30 ml per 378 liters) of solution.

CAUTION: Keep out of reach of children. In case of eye contact, flush with large amounts of clean, flowing water for at least 15 minutes. In case of ingestion, dilute by drinking water or milk, induce vomiting, and seek medical attention. Refer to Material Safety Data Sheet (MSDS) for further details. Dispose of in accordance with all applicable federal, state, and local regulations.

NOTICE: There are no warranties which extend beyond the description on the label hereof. The manufacturer, Becker Underwood, Inc., warrants this product to be as described on the label. The manufacturer's liability on this warranty is limited to return of the purchase price of this product. The buyer assumes all risks and liability resulting from the use of this product, whether used singly or in combination with other goods. The manufacturer neither assumes nor authorizes any person to assume for it any other liability in connection with the sale or use of this product.

Manufactured by:

Becker Underwood, Inc.

801 Dayton Avenue
Ames, IA 50010
515-232-5907
Fax 515-232-5961
www.bucolor.com

[Click here to print this page](#)[Close Window](#)

