

Applications

- Fits Techline® CV, Techline® and Techlite® Dripperlines

Features/Benefits

- Barbed fittings for secure fit and easy installation without glue or tools
- Maximum recommended system pressure: 50 psi; 8mm fittings: 25 psi
- UV resistant
- Durable one-piece construction
- Allows for easy on-site inspection of proper fitting installation



TLTEE
Insert Tee



TLCOUP
Insert Coupling



TL2W075MA
3/4" MPT
"V" 2-Way Insert



TLELL
Insert Elbow



TLCROS
Insert Cross



TL075MA
3/4" Male Adapter



TL075FTEE
Combination Tee
Ins x Ins x 3/4" FPT



TLFIG8
Figure 8 Line End



TLDPLUG
Dripper Plug Ring



TLMTUBEADP
Dripper Micro-Tubing
Adapter



TLSOV
Shut-Off Valve
Ins x Ins



TLS6
6" Soil Staple
(Place approximately every
3' of tubing, plus two on
each tee, elbow or cross.)

Ordering Information

Model #	Product Description	Ctn. Qty.
TLCOUP	Techline Insert Coupling	25
TLELL	Techline Insert Elbow	25
TLTEE	Techline Insert Tee	25
TL075MA	Techline Male Adapter 3/4"	25
TL075FTEE	Techline Combination Tee (Ins x Ins x 3/4" FPT)	10
TL2W075MA	Techline "V" 2 Way Insert x 3/4" MPT	10
TLCROS	Techline Insert Cross	25
TLFIG8	1/2" Figure Eight Line End	25
TLDPLUG	Techline Dripper Plug	25
TLMTUBEADP	Techline Micro Tubing Adapter	25
TLS6	6" Soil Staple	25
TLSOV	Techline Shut-Off Valve (IXI)	10