

Inline Pressure Regulators

Features

- Can be installed above or below grade.
- Preset outlet pressures: 30 psi (2,0 bars) and 40 psi (2,8 bars).
- 3/4" or 1" NPT female-threaded inlet and outlet.

Operating Range

- Flow
 - PSI-L30X-075: 0.10 to 5.0 GPM; 6 to 300 GPH (0,4 to 18,9 l/m)
 - PSI-M30X-075, PSI-M40X-075: 2.0 to 10.0 GPM; 120 to 600 GPH (7,8 to 37,9 l/m)
 - PSI-M40X-100: 2.0 to 15.0 GPM; 120 to 900 GPH (7,8 to 56,8 l/m)
- Inlet Pressure:
 - 10-150 psi (0,7 to 10,3 bars)



Models

- PSI-L30X-075: 3/4" 30 psi (2,1 bars) regulator for low flow (red label)
- PSI-M30X-075: 3/4" 30 psi (2,1 bars) regulator for medium flow (yellow label)
- PSI-M40X-075: 3/4" 40 psi (2,8 bars) regulator for medium flow (yellow label)
- PSI-M40X-100: 1" 40 psi (2,8 bars) regulator for medium flow

Ordering Information		
Model #	Product Description	Ctn. Qty.
PSIL30X075	Pressure Regulator, 30 PSI, 3/4" Low Flow 0.1-5.0 GPM	1
PSIM30X075	Pressure Regulator, 30 PSI, 3/4" Med Flow 2.0-10.0 GPM	1
PSIM40X075	Pressure Regulator, 40 PSI, 3/4" Med Flow 2.0-15.0 GPM	1
PSIM40X100	Pressure Regulator, 40 PSI, 1" Med Flow 2.0-15.0 GPM	1