

1/4" Barb Transfer Fittings

Features

- Used to connect 1/4" distribution tubing (DT-025 or PT-025) in different configurations or attach 1/4" tubing to 1/2" or 3/4" tubing.
- Newly designed connectors have self-piercing barbs that easily puncture 1/2" or 3/4" tubing.
- Stem on fittings allows simple, quick installation using Xeriman™ Tool (XM-TOOL).
- Rugged plastic construction.

Operating Range

- Pressure: 0 to 50 psi (0 to 3,5 bars)




1/4" Self-Piercing Barb Connector

Features

- Used to connect 1/4" distribution tubing into 1/2" or 3/4" distribution tubing.
- Self-piercing barb inlet is easily inserted into 1/2" or 3/4" distribution tubing using a Xeriman™ Tool (XM-Tool).
- Outlet barb accepts 1/4" distribution tubing (DT-025 or PT-025). Gray outlet barb indicates unit has unrestricted flow.

Operating Range

- Pressure: 0 to 50 psi (0 to 3,5 bars)



Tubing Goof Plug

Features

- Used to plug unwanted holes in tubing.
- New design works with Xeriman™ Tool (XM-TOOL) for a quick, easy installation.



1/4" Mounting Clip

Features

- Used to attach 1/4" distribution tubing (DT-025 or PT-025) to wood without pinching the tube.
- Nail is retained in the clip for easy installation.
- Durable plastic construction.




Xeri Micro Valves

Features

- Micro-sized multi-purpose flow control valves.
- Easily adjust or turn off flow by rotating the ball valve.

Operating Range

- Pressure: 0 to 50 psi (0 to 3,5 bars)



Ordering Information		
Model #	Product Description	Ctn. Qty.
XBF1CONN	1/4" Barb Connector	50
XBF2EL	1/4" Barb x Barb ELL	50
XBF3TEE	1/4" Barb x Barb x Barb Tee	50
SPB025	Self-Piercing Barb Connector	25
EMAGPX	Tubing Goof Plug	80
MC025	1/4" Mounting Clip	25
XMV025	Xeri-Micro Valve 1/4" Barb x Barb	10