

Xeri-Bubblers™

Ideal for shrub plantings, trees, containers, and flower beds.

Features

- Adjust flow and radius by turning outer cap.
- Clean by completely unscrewing cap from base unit.
- Three convenient installation connections available for design flexibility: 10-32 self-tapping thread, 1/4" barb, and 5" spike.

Operating Range

- SXB Series Flow: 0 to 13 GPH (0 to 49,21 l/h)
- UXB Series Flow: 0 to 35 GPH (0 to 132,48 l/h)
- Pressure: 15 to 30 psi (1,0 to 2,1 bars)

Models

- SXB-180-1032: Half-circle, 5 streams, 10-32 thread
- SXB-180-025: Half-circle, 5 streams, 1/4" barb
- SXB-180-SPYK: Half-circle, 5 streams, 5" spike; includes barb x barb coupler
- SXB-360-1032: Full-circle, 8 streams, 10-32 thread
- SXB-360-025: Full-circle, 8 streams, 1/4" barb
- SXB-360-SPYK: Full-circle, 8 streams, 5" spike includes barb x barb coupler

Xeri-Bubbler Performance						
<i>Fully open (approximately 22 clicks)</i>						
Pressure psi	SXB-180 Flow GPH	Radius of Throw ft.	SXB-360 Flow GPH	Radius of Throw ft.	UXB-360 Flow GPH	Radius of Throw ft.
15	8.7	1.2	8.7	0.6	28.5	0.7
20	10.3	1.5	10.3	1.0	31.0	1.1
30	13.0	2.0	13.0	1.5	35.0	1.9



**SXB180025, SXB360025, UXB360025
BARB**



**SXB1801032, SXB3601032, UXB3601032
10-32 THREADS**



**SXB180SPYK, SXB360SPYK, UXB360SPYK
"SPIKE"**

Ordering Information		
Model #	Product Description	Ctn. Qty.
SXB1801032	Xeri-Bubbler 180 Degree, 5 Streams, 10-32 Threads	20
SXB180025	Xeri-Bubbler 180 Degree, 5 Streams, 1/4" Barb	20
SXB180SPYK	Xeri-Bubbler 180 Degree, 5 Streams, 5" Spike w/ B x B	10
SXB3601032	Xeri-Bubbler 360 Degree, 8 Streams, 10-32 Threads	20
SXB360025	Xeri-Bubbler 360 Degree, 8 Streams, 1/4" Barb	20
SXB360SPYK	Xeri-Bubbler 360 Degree, 8 Streams, 5" Spike w/ B x B	10