

# BOSHART INDUSTRIES

2-14  
May 16/14

Telephone: 1-519-595-4444 - Toll Free: 1-800-561-3164  
Fax: 1-519-595-4380 - [www.boshart.com](http://www.boshart.com)

## "BII" PVC MOLDED-IN-PLACE BALL VALVES



- Working Temperature Range 32°F to 122°F (0°C to 50°C)
- Suitable for both Schedule 40 and 80 PVC Pipe
- Variety of water supply, waste water, swimming pool, chemical feed and irrigation applications for residential, commercial, industrial, marine and agriculture use
- NSF/ANSI Standard 372 Certified
- 150 PSI Working Pressure at 73°F (22°C)

### PVC BALL VALVE - EPDM SEAT - EPDM STEM "O" RING

PART NO.	SHIPPING WGT-lbs	LIST PRICE-F	PART NO.	SHIPPING WGT-lbs	LIST PRICE-F	SIZE	PORT DIA.INS.	QUANTITY CTN	CASE
0929-05	0.18	1.29	0929S-05	0.16	1.47	1/2"	0.59	1	200
0929-07	0.26	1.92	0929S-07	0.26	2.15	3/4"	0.79	1	160
0929-10	0.44	2.99	0929S-10	0.43	3.53	1"	0.98	1	96
0929-12	0.57	4.12	0929S-12	0.58	4.65	1 1/4"	1.26	1	72
0929-15	0.94	6.84	0929S-15	0.92	6.74	1 1/2"	1.42	1	45
0929-20	1.44	10.89	0929S-20	1.55	10.44	2"	1.81	1	36
0929-25	2.47	26.02	0929S-25	2.20	24.83	2 1/2"	2.48	1	12
0929-30	4.72	40.94	0929S-30	4.67	38.84	3"	3.15	1	8
0929-40	6.68	77.34	0929S-40	6.26	73.48	4"	3.81	1	6

NOTE: Red handles may be available. Please contact your Sales Rep.

## HERSHEY PVC MOLDED-IN-PLACE BALL VALVES



Series 0921  
White PVC  
Body  
with Black  
Handle

- Working Temperature Range: 41°F to 122°F (5°C to 50°C)
- 150 PSI Working Pressure at 73°F (22°C)
- Suitable for both Schedule 40 and 80 PVC Pipe
- Shock-resistant PVC body, ball and handle. (2-1/2" - 4" have polypropylene ball)
- Variety of water supply, waste water, chemical feed and irrigation applications, for residential, commercial, industrial, marine and agricultural use
- NSF/ANSI Standard 61 & 372 Certified (0921/0921S series only)

### DELUXE PVC VALVE EPDM SEAT - EPDM STEM "O" RING - NSF approved 1/2" to 2" only

PART NO.	SIZE	PORT DIA.INS.	SHIPPING WGT-lbs	QUANTITY CTN	LIST PRICE-F
0921-05	1/2"	0.55	0.18	100	2.74
0921-07	3/4"	0.79	0.31	100	3.66
0921-10	1"	0.98	0.49	100	4.88
0921-12	1 1/4"	1.18	0.57	100	6.14
0921-15	1 1/2"	1.42	0.97	48	10.50
0921-20	2"	1.83	1.50	24	13.93
0921-25	2 1/2"	2.36	2.87	12	32.76
0921-30	3"	3.03	3.97	12	56.46
0921-40	4"	3.93	8.09	6	106.04

### DELUXE PVC VALVE PTFE SEAT - VITON STEM "O" RING - Not NSF approved

PART NO.	SIZE	PORT DIA.INS.	SHIPPING WGT-lbs	QUANTITY CTN	LIST PRICE-F
0923-05	1/2"	0.55	0.18	100	6.09
0923-07	3/4"	0.79	0.31	100	7.22
0923-10	1"	0.98	0.49	100	10.66
0923-12	1 1/4"	1.18	0.57	100	12.18
0923-15	1 1/2"	1.42	0.97	48	21.40
0923-20	2"	1.83	1.50	24	26.80

NOTE: EPDM seats are recommended for most cold water system applications. PTFE seats are chlorine and chemical resistant and are recommended for most pool/spa applications.



Series 0923  
White PVC  
Body  
with Red  
Handle

## HERSHEY CPVC HOT WATER SYSTEM BALL VALVES



Beige CPVC Body  
with Red Handle

- High heat resistance - Max. Service Temperature
  - Continuous 32°F - 194°F (0°C - 90°C)
  - Short hours 212°F (100°C)
- PTFE (polytetrafluoroethylene) Seat
- CTS (Copper Tube size) Socket for CPVC pipe
- NSF/ANSI Standard 61 & 372 Certified
- Test Pressure: 225 PSI
- Working Pressure: 150 PSI
- EPDM O-Ring

PART NO.	DESCRIPTION	PORT DIA.INS.	QUANTITY CTN	CASE	LIST PRICE-F
0922CTS-05	1/2" CTS Socket	0.47	10	100	7.70
0922CTS-07	3/4" CTS Socket	0.56	5	100	9.65
0922CTS-10	1" CTS Socket	0.78	1	100	13.55
0922CTS-12	1-1/4" CTS Socket	0.99	1	100	20.29
0922CTS-15	1-1/2" CTS Socket	1.18	1	48	25.91
0922CTS-20	2" CTS Socket	1.42	1	24	42.44