



SPECIFICATIONS

Effective Dec., 2014
 Supersedes Oct. 19, 2009
 1830 Centennial Ave.
 Hastings, NE 68901
 Ph: 402-462-2227
 Fax: 402-462-5529
 Toll Free: 866-851-2227
 centennialplastics.com

CenFlo HDPE

HDPE 3608 — ASTM D2239 and ASTM D2737 CTS

- Flexible polyethylene pipe and tubing
- Produced from only the finest virgin material
- Backed by a **30-YEAR WARRANTY**
- Virgin Black material

ASTM D2239			1/2"	3/4"	1"	1-1/4"	1-1/2"	2"
80 PSI	SIDR 19	O.D.	N/A	N/A	1.169"	1.526"	1.810"	2.285"
		I.D.	N/A	N/A	1.049"	1.380"	1.610"	2.067"
		Wall	N/A	N/A	.060"	.073"	.100"	.109"
		Wt/ft	N/A	N/A	.093#	.148#	.231#	.324#
		Coil Lengths	N/A	N/A	100-300 ft.	100-300 ft.	100-250 ft.	100-200 ft.

100 PSI	SIDR 15	O.D.	N/A	.944"	1.189"	1.564"	1.824"	2.343"
		I.D.	N/A	.824"	1.049"	1.380"	1.610"	2.067"
		Wall	N/A	.060"	.070"	.092"	.107"	.138"
		Wt/Ft	N/A	.074#	.109#	.187#	.251#	.416#
		Coil Lengths	N/A	100-400 ft.	100-300 ft.	100-300 ft.	100-250 ft.	100-200 ft.

125 PSI*	SIDR 11.5	O.D.	.742"	.968"	1.231"	1.620"	1.890"	2.427"
		I.D.	.622"	.824"	1.049"	1.380"	1.610"	2.067"
		Wall	.060"	.072"	.091"	.120"	.140"	.180"
		Wt/Ft	.057#	.090#	.143#	.246#	.330#	.544#
		Coil Lengths	100-400 ft.	100-400 ft.	100-300 ft.	100-300 ft.	100-250 ft.	100-200 ft.

160 PSI*	SIDR 9	O.D.	N/A	1.008"	1.283"	1.686"	1.968"	2.527"
		I.D.	N/A	.824"	1.049"	1.380"	1.610"	2.067"
		Wall	N/A	.092"	.117"	.153"	.179"	.230"
		Wt/Ft	N/A	.116#	.186#	.320#	.430#	.710#
		Coil Lengths	N/A	100-400 ft.	100-300 ft.	100-300 ft.	100-250 ft.	100-200 ft.

200 PSI*	SIDR 7	O.D.	N/A	1.060"	1.349"	1.774"	2.070"	2.657"
		I.D.	N/A	.824"	1.049"	1.380"	1.610"	2.067"
		Wall	N/A	.118"	.150"	.197"	.230"	.295"
		Wt/Ft	N/A	.152#	.246#	.424#	.578#	.952#
		Coil Lengths	N/A	100-400 ft.	100-300 ft.	100-300 ft.	100-250 ft.	100-200 ft.

ASTM D2737 CTS			1/2"	3/4"	1"	1-1/4"	1-1/2"	2"
200 PSI*	SDR 9	O.D.	N/A	.875"	1.125"	1.375"	1.625"	2.125"
		I.D.	N/A	.681"	.875"	1.069"	1.263"	1.653"
		Wall	N/A	.097"	.125"	.153"	.181"	.236"
		Wt/Ft	N/A	.103#	.170#	.254#	.353#	.602#
		Coil Lengths	N/A	100-400 ft.	100-300 ft.	100-300 ft.	100-250 ft.	100-200 ft.

*CenFlo 3408 SIDR 7, 9 & 11.5 pipe meets the requirements of AWWA C901.

*CenFlo 3408 CTS SDR9 pipe meets the requirements of AWWA C901.

*CenFlo HDPE SIDR 19, SIDR 15, SIDR 11.5, SIDR 9 and SIDR 7 are suitable for connections with insert fittings and clamps.

*CenFlo HDPE SDR 9 is suitable for connections with CTS compression fittings.

Centennial Plastics is an ISO 9001 Certified Company.



CenFlo HDPE is tested and certified to NSF Standard 14

\$ CenFlo HDPE is certified to the Uniform Plumbing Code™

Product also Certified to NSF/ANSI Standard 61, Annex G (weighted average lead content of <=0.25%) and is in compliance with California's Health & Safety Code Section 116875 (commonly known as AB153).



SPECIFICATIONS

Effective Dec., 2014
 Supercedes Oct., 2009
 1830 Centennial Ave.
 Hastings, NE 68901
 Ph: 402-462-2227
 Fax: 402-462-5529
 Toll Free: 866-851-2227
 centennialplastics.com

CenFlo MDPE

MDPE 2708—ASTM D2239

- Flexible polyethylene pipe
- Produced from only the finest virgin material
- Backed by a **30-YEAR WARRANTY**
- Virgin Black material

ASTM D2239			3/4"	1"	1-1/4"	1-1/2"	2"
80 PSI*	SIDR15	O.D.	.944"	1.189"	1.564"	1.824"	2.343"
		I.D.	.824"	1.049"	1.380"	1.610"	2.067"
		Wall	.060"	.070"	.092"	.107"	.138"
		Wt/Ft	.071#	.105#	.183#	.245#	.408#
		Coil Lengths	100-400 ft.	100-300 ft.	100-300 ft.	100-250 ft.	100-200 ft.

ASTM D2239			3/4"	1"	1-1/4"	1-1/2"	2"
100 PSI *	SIDR11.5	O.D.	.968"	1.231"	1.620"	1.890"	2.427"
		I.D.	.824"	1.049"	1.380"	1.610"	2.067"
		Wall	.072"	.091"	.120"	.140"	.180"
		Wt/Ft	.087#	.140#	.241#	.329#	.543#
		Coil Lengths	100-400 ft.	100-300 ft.	100-300 ft.	100-250 ft.	100-200 ft.

ASTM D2239			3/4"	1"	1-1/4"	1-1/2"	2"
160 PSI*	SIDR7	O.D.	1.060"	1.349"	1.774"	N/A	N/A
		I.D.	.824"	1.049"	1.380"	N/A	N/A
		Wall	.118"	.150"	.197"	N/A	N/A
		Wt/Ft	.149#	.241#	.417#	N/A	N/A
		Coil Lengths	100-400 ft.	100-300 ft.	100-300 ft.	N/A	N/A

*CenFlo SIDR 7 pipe meets the requirements of AWWA C901.

*CenFlo MDPE SIDR 15, SIDR 11.5 and SIDR 7 are suitable for connections with insert fittings and clamps.

Centennial Plastics is an ISO 9001 Certified Company.



CenFlo MDPE is tested and certified to NSF/ANSI Standard 14
 § CenFlo MDPE is certified to the Uniform Plumbing Code™

Product also Certified to NSF/ANSI Standard 61, Annex G (weighted average lead content of <=0.25%) and is in compliance with California's Health & Safety Code Section 116875 (commonly known as AB153).