

FORM NO. 161-HD SPECIFICATIONS
PRICES ARE LISTED ON FORM MLP-1.
PLEASE ORDER BY PART NUMBER.



DECEMBER, 2014

HD 200 SIDR-7 AWWA C-901  YELLOW LABEL/BLACK PRINT	SIZE	I.D.	MIN. WALL	WEIGHT PER 100'	COIL LENGTHS	PART NO.
	HD 160 SIDR-9  RED LABEL/WHITE PRINT	3/4"	.824	.118	15.42	100
1		1.049	.150	24.92	400	18010
					100	18015
1 1/4		1.380	.197	43.13	300	18020
					100	18025
1 1/2		1.610	.230	58.86	300	18030
					100	18045
2		2.067	.295	96.78	250	18050
	100				18060	
				200	18065	
HD 125 SIDR-11.5  GREEN LABEL/WHITE PRINT	3/4"	.824	.092	11.67	100	18105
	1	1.049	.117	18.87	400	18110
					100	18115
	1 1/4	1.380	.153	32.44	300	18120
					100	18125
	1 1/2	1.610	.179	44.24	300	18130
					100	18135
	2	2.067	.230	73.39	250	18140
100					18145	
				200	18150	
HD 100 SIDR-15  BLUE LABEL/WHITE PRINT	1/2"	.622	.060	5.72	100	18201
	3/4	.824	.072	8.95	400	18202
					100	18205
	1	1.049	.091	14.34	400	18210
					100	18215
	1 1/4	1.380	.120	24.85	300	18220
					100	18225
	2	2.067	.138	42.20	100	18230
300					18230	
HD 80 SIDR-19  WHITE LABEL/BLACK PRINT	3/4"	.824	.060	7.38	100	18315
	1	1.049	.070	10.78	400	18320
					100	18335
	1 1/4	1.380	.092	18.71	100	18340
					300	18355
	1 1/2	1.610	.107	25.45	300	18360
					100	18375
	2	2.067	.138	42.20	250	18380
100					18390	
				200	18395	
HD 80 SIDR-19  WHITE LABEL/BLACK PRINT	1"	1.049	.060	9.25	100	18420
	1 1/4	1.380	.073	14.67	300	18425
					100	18435
	1 1/2	1.610	.085	19.91	300	18440
					100	18450
	2	2.067	.109	32.81	250	18455
					100	18460
					200	18465

ALL CRESLINE HD PIPE IS PRODUCED FROM PE 3608 MATERIAL AND CONFORMS TO ASTM D 2239.

**PRESSURE RATING
FOR CRESLINE FLEXIBLE PIPES
AT VARIOUS TEMPERATURES
ALL SIZES**

DEGREE °F	73.4° F AND BELOW	100° F	120° F	140° F
HD 200	200	155	125	100
HD 160	160	125	100	80
HD 125	125	100	80	60
HD 100	100	80	60	50
HD 80	80	60	50	40

PRESSURE RATING IS THE ESTIMATED MAXIMUM PRESSURE THAT WATER AS THE MEDIUM IN THE PIPE CAN EXERT CONTINUOUSLY FOR A LONG TIME WITH A HIGH DEGREE OF CERTAINTY THAT FAILURE OF THE PIPE WILL NOT OCCUR.

CRESLINE HD FLEXIBLE PLASTIC PIPE MAY BE USED ON SUBMERSIBLE PUMPS OF 1.5 HP OR LESS.

MAXIMUM DEPTH SETTINGS TO WATER LEVEL IN FT. @ 60°F			
CRESLINE PE FLEXIBLE PIPE	MAX. TANK SHUT-OFF PRESSURE		
	40 PSI	50 PSI	60 PSI
HD 200	420'	400'	370'
HD 160	310'	290'	270'
HD 125	220'	200'	180'
HD 100	160'	140'	120'
HD 80	110'	90'	60'



CRESLINE PLASTIC PIPE CO., INC.

600 Cross Pointe Blvd.
264 Silver Spring Rd.
2100 South 35th St.
3801 East Hwy. 31

Evansville, IN 47715
Mechanicsburg, PA 17050
Council Bluffs, IA 51501
Corsicana, TX 75109

812-428-9350
717-766-2566
712-322-2294
903-872-8475

www.cresline.com

Fax 812-428-9353
Fax 717-697-2371
Fax 712-322-6673
Fax 903-872-7732