







**CE BLUE<sup>®</sup>  
FLEXIBLE PIPE**

FORM NO. 161-CE SPECIFICATIONS  
PRICES ARE LISTED ON FORM MLP-1.  
PLEASE ORDER BY PART NUMBER.



DECEMBER, 2014

CE BLUE <sup>®</sup>	SIZE	I.D.	O.D.	MIN. WALL	WEIGHT PER 100'	COIL LENGTHS	PART NO.
200 PSI - IPS SIDR - 7 AWWA C-901  ASTM D-2239	¾"	.824	1.060	.118	15.38	100	19315
						400	19320
	1	1.049	1.349	.150	24.87	100	19330
						300	19335
	1¼	1.380	1.774	.197	43.04	100	19350
						300	19355
200 PSI - CTS SDR - 9 AWWA C-901  ASTM D-2737	¾"	.681	.875	.097	10.25	100	19715
						500	19720
	1	.875	1.125	.125	16.93	100	19730
						300	19735
	500	1.069	1.375	.153	25.34	100	19738
						300	19755
	1¼	1.263	1.625	.181	35.45	100	19750
						300	19755
	2	1.653	2.125	.236	60.52	100	19770
						300	19775
100	1.653	2.125	.236	60.52	100	19785	
					200	19790	
160 PSI - IPS SIDR - 9  ASTM D-2239	¾"	.824	1.008	.092	11.65	100	19415
						400	19420
	1	1.049	1.283	.117	18.83	100	19430
						300	19435
	1¼	1.380	1.686	.153	32.37	100	19450
						300	19455
100 PSI - IPS SIDR - 15  ASTM D-2239	¾"	.824	.944	.060	7.31	100	19515
						400	19520
	1	1.049	1.189	.070	10.93	100	19530
						300	19535
	1¼	1.380	1.564	.092	18.67	100	19550
						300	19555

CRESLINE CE BLUE<sup>®</sup> POLYETHYLENE FLEXIBLE PIPE IS PRODUCED FROM HD PE 3608 MATERIAL.

**CRESLINE PLASTIC PIPE CO., INC.**

600 Cross Pointe Blvd.  
264 Silver Spring Rd.  
2100 South 35th St.  
3801 East Hwy. 31

Evansville, IN 47715  
Mechanicsburg, PA 17050  
Council Bluffs, IA 51501  
Corsicana, TX 75109

812-428-9350  
717-766-2566  
712-322-2294  
903-872-8475

[www.cresline.com](http://www.cresline.com)

Fax 812-428-9353  
Fax 717-697-2371  
Fax 712-322-6673  
Fax 903-872-7732

**PRESSURE RATING  
FOR CRESLINE FLEXIBLE PIPES  
AT VARIOUS TEMPERATURES  
ALL SIZES**

DEGREE °F	73.4° F AND BELOW	100° F	120° F	140° F
<b>CE BLUE® 200</b>	200	155	125	100
<b>CE BLUE® 160</b>	160	125	100	80
<b>CE BLUE® 100</b>	100	80	60	50

PRESSURE RATING IS THE ESTIMATED MAXIMUM PRESSURE THAT WATER AS THE MEDIUM IN THE PIPE CAN EXERT CONTINUOUSLY FOR A LONG TIME WITH A HIGH DEGREE OF CERTAINTY THAT FAILURE OF THE PIPE WILL NOT OCCUR.

CRESLINE CE FLEXIBLE PLASTIC PIPE MAY BE USED ON SUBMERSIBLE PUMPS OF 1.5 HP OR LESS.

MAXIMUM DEPTH SETTINGS TO WATER LEVEL IN FT @ 60° F			
CRESLINE PE FLEXIBLE PIPE	MAX. TANK SHUT-OFF PRESSURE		
	40 PSI	50 PSI	60 PSI
CE BLUE® 200	400'	400'	400'
CE BLUE® 160	300'	280'	260'
CE BLUE® 100	180'	155'	135'



**CRESLINE PLASTIC PIPE CO., INC.**

600 Cross Pointe Blvd.  
264 Silver Spring Rd.  
2100 South 35th St.  
3801 East Hwy. 31

Evansville, IN 47715  
Mechanicsburg, PA 17050  
Council Bluffs, IA 51501  
Corsicana, TX 75109

812-428-9350  
717-766-2566  
712-322-2294  
903-872-8475

[www.cresline.com](http://www.cresline.com)

Fax 812-428-9353  
Fax 717-697-2371  
Fax 712-322-6673  
Fax 903-872-7732