

AquascapePRO® Solids Handling Skimmer and Pondless® Waterfall Vault Pump

Available in flow rates from 3,000 to 10,000 gallons per hour (11,350 to 37,800 liters per hour)

AquascapePRO® pumps are ideal for use in Aquascape and other skimmer and falls filters systems as well as Pondless® Waterfall filter vaults.

Aquascape's horizontal pond pumps, from the AquascapePRO® line, are energy efficient and low maintenance. Quiet and efficient, these pumps have stainless steel construction, along with rubber feet to reduce vibration. With high head heights and a wide variety of flow rates to choose from there is sure to be an AquascapePRO® pump that fits your water gardens requirements.

AquascapePRO® 3000 Pump (Unit Weight: 16 lbs.)

#20002 MSRP \$569.99

AquascapePRO® 4500 Pump (Unit Weight: 17 lbs.)

#20003 MSRP \$759.99

AquascapePRO® 7500 Pump (Unit Weight: 22 lbs.)

#20004 MSRP \$929.99

AquascapePRO® 10,000 Pump (Unit Weight: 39 lbs.)

#20006 MSRP \$1,049.99

2-Year Limited Warranty



AquascapePRO® 3000 Pump



AquascapePRO® 10000 Pump



AquascapePRO® Pump Specs

Model	3,000	4,500	7,500	10,000
Maximum Flow Rate (GPH)	2,900	4,500	6,700	10,600
Maximum Head Height	20'	33'	42'	28'
Motor Type	Direct Drive	Direct Drive	Direct Drive	Direct Drive
Wattage	280	625	1200	1240
Amperage	2.6	5.4	10	11
Power Cord Length	20'	20'	20'	20'
Pump Discharge Diameter	2"	2"	2"	3"
Dimensions Pump	12" L x 6" W x 7" H	13" L x 6.5" W x 7" H	13" L x 6.5" W x 7" H	12.5" L x 9" W x 17" H
Warranty	2-Year Limited	2-Year Limited	2-Year Limited	2-Year Limited

AquascapePRO® Pump Flow Chart (GPH)

Model	Max Head Ft.	0' (0 psi)	5' (2.16 psi)	10' (4.33 psi)	15' (6.49 psi)	20' (8.66 psi)	25' (10.82 psi)	30' (12.99 psi)	35' (15.15 psi)	40' (17.32 psi)
3000	20	2900	2900	2000	1200	0				
4500	33	4500	4500	4000	3300	2700	2000	1000	0	
7500	42	6700	6700	6100	5300	4900	4000	3200	2200	1100 0
10000	28	10600	10600	8100	6900	4900	2300	0		

BEST Operating Zone

MAXIMUM Operating Zone

DO NOT Operate Zone