

SDS

GHS Safety Data Sheet PROFILE Products, LLC

Terra-Blend™ with UltraGro™

MSDS Number: CON054 Revision Date: 1/1/14

Page 1 **of** 5

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

PROFILE Products, LLC 750 LAKE COOK ROAD SUITE 440 BUFFALO GROVE, IL 60089

Phone: (847) 215-1144
Fax: (847) 215-0577
Email: profileproducts.com
Web: www.profileproducts.com

Product Name: Terra-Blend™ with UltraGro™

Revision Date: 1/1/14
MSDS Number: CON054
CAS Number: Not applicable

Product Use: Erosion control mulch for revegetation and hydraulic seeding

Product Description: Green dyed wood and cellulose fibers and a proprietary binder mixture of natural clays and seaweed

extract.

2 HAZARDS IDENTIFICATION

Route of Entry: Inhalation, skin contact, eye contact

Inhalation: Wood may cause sneezing, irritation, and dryness of the nose and throat. Dust may aggravate pre-existing respiratory

conditions.

Skin Contact: Wood & paper dust can cause irritation. Skin absorption is not known to occur.

Eye Contact: Wood & paper dust can irritate the eyes.

Ingestion: No reports of human ingestion.

NFPA: Health = 1, Fire = 1, Reactivity = 0



OSHA Classification: Wood dust is a hazardous substance as defined by the Hazard Communication Standard 29CFR 1910.1200



SDS

GHS Safety Data Sheet PROFILE Products, LLC

Terra-Blend™ with UltraGro™

MSDS Number: CON054 Revision Date: 1/1/14

Page 2 of 5

3

COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas # Perc. Chemical Name

FIRST AID MEASURES

Inhalation: Usually not a problem. Remove to fresh air if respiratory irritation develops, and get medical aid promptly if irritation

persists.

Skin Contact: Usually not a problem. Wash off with running water if irritation is experienced.

Eye Contact: Open eyelids and flush with water.

Ingestion: Get medical attention.

5 FIRE FIGHTING MEASURES

Flash Point:
Combustible product
Not applicable
Flash Point Method:
Not applicable

Autoignition Temp: 200-260°C (400-500°F) Conditions to avoid: In contact with flames or hot surfaces

Flammable- Extinguish with water; same as a wood fire

6 ACCIDENTAL RELEASE MEASURES

Scoop up product. Wear goggles and respirator if dust is produced in unventilated areas. Wet product will be slippery.

HANDLING AND STORAGE

Handling Precautions: Clean up areas where dust settles. Minimize blowdown or other practices that generate high airborne

dust concentrations.

Storage Requirements: Store in a cool, dry place. Keep away from sources of ignition.





GHS Safety Data Sheet PROFILE Products, LLC

Terra-Blend™ with UltraGro™

MSDS Number: CON054 Revision Date: 1/1/14

Page 3 of 5

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: None required for outdoor mixing and application. Use dust collection system for indoor handling

operations.

Personal Protective Equip: Eye Protection: Wear goggles when emptying bags and during other operations where there is a risk of

dust entering the eyes.

Gloves: Leather, plastic or rubber gloves could be worn to minimize skin irritation.

Respirators: When handling methods generate dust at concentrations that exceed occupational exposure limits, wear a NIOSH approved respirator. A fabric respirator or a facepiece respirator with

dust cartridges will generally provide adequate protection.

Footwear: The product is slippery when wet. Wear appropriate footwear.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Dyed, green wood & paper fibers - Pine, mixed hardwoods & shredded paper

Physical State: Wood/Paper Fibers Odor: Mild wood odor

Spec Grav./Density: Lighter than water

Vapor Pressure: N/A

10 STABILITY AND REACTIVITY

Stability: Stable product

Conditions to Avoid: Contact with strong acids and oxidizers may generate heat. Product may ignite at temperatures in

excess of 200°C (400°F).

Materials to Avoid: Strong acids and oxidizers

Hazardous Polymerization: Will not occur.

11 TOXICOLOGICAL INFORMATION

EFFECTS OF CHRONIC EXPOSURE:

Inhalation: Frequent and repeated exposure to wood dust is associated with an increased risk of developing nasal cancer.

Skin Contact: Although rare, wood dust may cause dermatitis in sensitized people.

Occupational Exposure Limits:

Wood dusts- All other species: ACGIH (2007): TLV-TWA 1 mg/m³ (Inhalable

fraction); A4

Particulates Not Otherwise

Regulated (PNOR): OSHA: PEL-TWA 15 mg/m³ (Total Dust);

5 mg/m³ (Respirable fraction)

Irritancy: Wood dust is a mild irritant

Sensitization: Some wood dusts may cause allergic skin reactions





GHS Safety Data Sheet PROFILE Products, LLC

Terra-Blend™ with UltraGro™

MSDS Number: CON054 Revision Date: 1/1/14

Page 4 of 5

12

ECOLOGICAL INFORMATION

48-hr $LC_{50} = >100\%$ for Daphnia magna when runoff generated using ASTM D7101 (2"/hr rainfall rate) was tested according to EPA-821-R-02-012.

13

DISPOSAL CONSIDERATIONS

Normally can be disposed of as a wood residue. Ensure disposal is in compliance with local, provincial (state), and federal regulations.

11

TRANSPORT INFORMATION

DOT Class: Not regulated #

15

REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List
NRC = Nationally Recognized Carcinogens
OSHAWAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TXAIR = TX Air Contaminants with Health Effects Screening Level

CERCLA = Superfund clean up substance CSWHS = Clean Water Act Hazardous substances EHS302 = Extremely Hazardous Substance EPCRAWPC = EPCRA Water Priority Chemicals HAP = Hazardous Air Pollutants NJEHS = NJ Extraordinarily Hazardous Substances NJHS = NJ Right-to-Know Hazardous Substances OSHAPSM = OSHA Chemicals Requiring process safety management SARA313 = SARA 313 Title III Toxic Chemicals





GHS Safety Data Sheet PROFILE Products, LLC

Terra-Blend™ with UltraGro™

MSDS Number: CON054 Revision Date: 1/1/14

Page 5 of 5

OTHER INFORMATION