

POWER MAX® HD

IDEAL FOR CLEARING:

10+
PARKED CARS

**Concrete,
Asphalt, Gravel**
surfaces

9"-20"
(23 cm - 51 cm)
snow depth

POWER CLEAR®

IDEAL FOR CLEARING:

4-9
PARKED CARS

**Concrete,
Asphalt**
surfaces

2"- 9"
(5 cm - 23 cm)
snow depth

POWER MAX® HD

IDEAL FOR CLEARING:

10+
PARKED CARS

**Concrete,
Asphalt**
surfaces

9"-20"
(23 cm - 51 cm)
snow depth

POWER BROOM

IDEAL FOR CLEARING:

Commercial
application
in all seasons

**Concrete,
Asphalt**
surfaces

TORO®

SNOW BLOWERS

POWER MAX® HD / POWER MAX® / SNOWMASTER® /
POWER CLEAR® / ELECTRIC / BATTERY



AMERICA'S #1
SNOW BLOWER
BRAND†

SHOW DEEP SNOW
WHO'S BOSS

3
YEAR
LIMITED
WARRANTY

ANY **TIME**
ANY **WHERE**
ANY **CONDITIONS**

NEW!

2
YEAR
FULL
COVERED
WARRANTY

OUR BIGGEST
**BLIZZARD
BUSTER**

3
YEAR
LIMITED
WARRANTY

CLEAR SNOW
IN A BIG WAY

COMMERCIAL
1 YEAR
FULL COVERED
WARRANTY



PRECISION CONTROL

Smooth, tight turns are a snap with power steering. *(Select models)*



EASY STREET

Quickly change the chute and deflector direction with a single, smooth motion thanks to the Quick Stick® chute control.



NIGHT VISION

Your visibility will never be clearer with the LED headlight. *(Select models)*



POWER TO BLAST THROUGH HEAVY, DEEP SNOW

Toro's powerful 4-cycle OHV engines give you the power to slice through snow in no time.



EXTENDED LIFE PADDLES

Designed for less downtime with twice the life of Toro standard paddles.



REINFORCED HANDLE

Attached with 4 bolts for maximum rigidity.



ONE PIECE, REINFORCED HANDLE

For added durability and strength.



DRIFT CUTTER

Knocks down large drifts, allowing auger to collect and throw deep snow. *(Select models)*



CAST IRON SKID PLATES

Extra wide .5" skids provide maximum life and reliability. The added weight on the front helps to chew through deep snow piles.



4 TIE-DOWN POINTS

Fasten your product quickly and firmly with our structurally sound integrated tie-down points for safe and easy transportation.



UNIQUE PIN HEIGHT-OF-BRUSH SYSTEM

Precision height adjustment with up to 1/8" adjustments to minimize surface damage and brush wear.



VARIABLE SPEED & POWER STEERING

Commercial variable speed transmission allows you to shift on the fly with 6 forward and 2 reverse speeds, while power steering makes maneuvering easy.

HEAVY-DUTY TWO-STAGE

	928 OAE 38840	1028 OHXE 38841	1232 OHXE 38842
Engine	Toro® Premium 265cc 4-cycle OHV	» Toro Premium 302cc 4-cycle OHV	» Toro Premium 375cc 4-cycle OHV
Throw Distance	Up to 45' (13.5 m)	» Up to 49' (14.9 m)	» Up to 57' (17.4 m)
Clearing Width	28" (71 cm)	28" (71 cm)	» 32" (81 cm)
Starter	Electric Start	Electric Start	Electric Start
Rotor Style	Anti-Clogging System, 11" (28 cm) Dia., Hardened Gears, No Shear Pins Needed	Anti-Clogging System, 11" (28 cm) Dia., Hardened Gears, No Shear Pins Needed	Anti-Clogging System, 11" (28 cm) Dia., Hardened Gears, No Shear Pins Needed
Snow Cut Depth - 1 Pass	21.5" (55 cm)	21.5" (55 cm)	21.5" (55 cm)
Chute/ Deflector Type	Steel Chute / Double Deflector	Steel Chute / Double Deflector	Steel Chute / Double Deflector
Headlight	✓	✓	✓
Handwarmers	-	✓	✓
Warranty[^]	3-Year Limited 45 Days Limited Commercial	3-Year Limited 45 Days Limited Commercial	3-Year Limited 45 Days Limited Commercial

COMMERCIAL SINGLE-STAGE

	721 R-C 38754	821 R-C 38755
Engine	Toro Premium 212cc 4-cycle OHV	» Toro Premium 252cc 4-cycle OHV
Throw Distance	Up to 35' (11 m)	» Up to 40' (12 m)
Clearing Width	21" (53 cm) w/Extended Life Paddles	21" (53 cm) w/Extended Life Paddles
Drive System	Power Propel Self-Propel	Power Propel Self-Propel
Starter	Recoil Start	Recoil Start
Rotor Style	Power Curve Rotor	Power Curve Rotor
Snow Cut Depth - 1 Pass	12.5" (31.75 cm)	12.5" (31.75 cm)
High Capacity Chute w/Locking Deflector	✓	✓
Warranty[^]	2-Year Residential 1-Year Limited Commercial	2-Year Residential 1-Year Limited Commercial
GTS Warranty[^]	2-Year Residential Only	2-Year Residential Only

COMMERCIAL HEAVY-DUTY TWO-STAGE

	1428 OHXE 38843	1432 OHXE 38844
Engine	Toro Premium 420cc 4-cycle OHV	Toro Premium 420cc 4-cycle OHV
Throw Distance	Up to 60' (18.3 m)	Up to 60' (18.3 m)
Clearing Width	28" (71 cm)	32" (81 cm)
Starter	Electric Start	Electric Start
Rotor Style	Anti-Clogging System (ACS), 14" / 36 cm Dia., Commercial-Grade, no shear pins needed	Anti-Clogging System (ACS), 14" / 36 cm Dia., Commercial-Grade, no shear pins needed
Snow Cut Depth - 1 Pass	21.5" / 55 cm w/Drift Breaker (31.75 cm)	21.5" / 55 cm w/Drift Breaker (31.75 cm)
Chute/Deflector Type	Steel / Double Deflector	Steel / Double Deflector
Headlight	✓	✓
Handwarmers	✓	✓
Warranty[^]	3-Year Residential 1-Year Limited Commercial	3-Year Residential 1-Year Limited Commercial

COMMERCIAL POWER BROOM

	38700
Engine	Kohler® Command PRO® Multi-Season
Broom Width	36" (91.4 cm)
Broom Angle	40°
Broom Diameter	25" (63.5 cm)
Broom Speed	200 rpm
Starter	Recoil Start
Steering	Power Steering R/LH Clutch
Tires	15" x 5" (38.1 x 12.7 cm) Drive Tire 5" (12.7 cm) Caster Tire
Speeds	6/2 Variable Speed
Warranty[^]	1-Year Full

[^]See retailer for warranty details. [†]Based on average Traqline unit share for snow blower market from 2013 - 2018. *Compared to Toro® Power Max® models. Capacity will vary with conditions. ^{**}Battery manufacture rating = 60V maximum & 54V typical usage. Actual voltage varies with load.



60V MAX™ BATTERY

IDEAL FOR CLEARING:

4-9
PARKED CARS

Concrete, Asphalt
surfaces

2"- 9"
(5 cm - 23 cm)
snow depth

ELECTRIC

IDEAL FOR CLEARING:

Walkways, Patios, Decks

Concrete, Asphalt
surfaces

2"- 6"
(5 cm - 15 cm)
snow depth

POWER CLEAR®

IDEAL FOR CLEARING:

4-9
PARKED CARS

Concrete, Asphalt
surfaces

2"- 9"
(5 cm - 23 cm)
snow depth

SNOWMASTER®

IDEAL FOR CLEARING:

6-12
PARKED CARS

Concrete, Asphalt
surfaces

6"- 10"
(15 cm - 25 cm)
snow depth

POWER MAX™

IDEAL FOR CLEARING:

8-14
PARKED CARS

Concrete, Asphalt, Gravel
surfaces

9"- 20"
(23 cm - 51 cm)
snow depth

DO THE JOB BETTER, FASTER, EASIER

NEW!

FULL COVERAGE WARRANTY



SNOW-CLEARING CONVENIENCE

2 YEAR FULL WARRANTY



NEW!

GET THE JOB DONE FASTER

2 YEAR FULL WARRANTY

2 YEAR FULL WARRANTY



MAKE SNOW BLOWING LESS WORK

GUARANTEED FOR LIFE WARRANTY

3 YEAR FULL WARRANTY



SNOW-CLEARING MUSCLE

3 YEAR FULL WARRANTY



SNOWDRIFT STRENGTH

All the power to break through heavy, wet snow and throw it up to 40 ft.



CRUSH SNOW TO THE CURB

Rip through tough snow with the durable design of Toro's patent-pending metal Power Edge™ auger.



STARTS THE FIRST TIME, EVERY TIME

Reliable starting and low maintenance with battery power. Flex-Force 60V** batteries have intelligent software to maximize run time and power.



POWERFUL PERFORMANCE

The lightweight Power Shovel snow up to 20 feet while the 1800 Power Curve throws snow up to 30 feet.



TELESCOPING HANDLE

Height adjustment of 6" (15 cm) to fit any user.



QUICK CHUTE LEVER

Aim snow on the go with no cranking needed. *Standard on 1800 Power Curve.*



POWER TO BLAST THROUGH SNOW

Toro's powerful 4-cycle OHV engines give you the power to slice through snow in no time and throw up to 40 feet.



SHREDS SNOW FAST

Efficiently shreds through snow while reducing clogging with the curved paddles and funneled housing of the Power Curve® Technology.



GET A MOVE ON

Keep moving to get the job done faster with the Power Propel®. Our unique scraper keeps the paddle in constant contact with the ground, pulling you through the snow. *(select models)*



YOUR COFFEE IS WAITING. GET BACK TO IT UP TO 30% FASTER THAN A TRADITIONAL TWO-STAGE*

LIGHTNING FAST

Tear through the roughest snow and ice in record time with the engineered powerful auger.



KEEP UP THE PACE

You control how fast or slow you go with the Personal Pace® Self-Propel System. The rear wheel drive system also equips you with the best traction in any snow condition.



EASY STREET

Quickly change the chute and deflector direction in a single, smooth motion thanks to the Quick Stick® chute control. *(select models)*



STAY THE COURSE

Minimize clogging and maximize speed with the guaranteed for life anti-clogging system.



DON'T STOP

No need to replace shear pins in the cold with the commercial-grade auger gearbox.



EASY STREET

Quickly change the chute and deflector direction in a single, smooth motion thanks to the Quick Stick® chute control.

	SINGLE-STAGE		
	39901	39902	39901T (Tool only)
Battery Power	(1) L405 (7.5 ah, 405 wh)	» (2) L324 (6.0 ah, 324 wh)	-
Motor	Brushless DC	Brushless DC	Brushless DC
Throw Distance	Up to 40' (12 m)	Up to 40' (12 m)	Up to 40' (12 m)
Clear Space in Single Charge	Up to 12 parked cars	Up to 18 parked cars	N/A
Charge Time	180 min	150 min (per battery)	N/A
Rotor Style	All Steel Power Edge™	All Steel Power Edge	All Steel Power Edge
Snow Cut Depth - 1 Pass	12" (31 cm)	12" (31 cm)	12" (31 cm)
Chute/Deflector Type	Curved w/Locking Deflector	Curved w/Locking Deflector	Curved w/Locking Deflector
Headlight	✓	✓	✓
Snow Blower Warranty^	2-Year Full	2-Year Full	2-Year Full
Battery Warranty^	3-Year Full	3-Year Full	-

	ELECTRIC	
	POWER SHOVEL™ 38361	POWER CURVE® 38381
Engine	7.5 Amp Series Wound Electric	15 Amp Series Wound Electric
Throw Distance	Up to 20' (6 m)	» Up to 30' (9 m)
Clearing Width	12" (31 cm)	» 18" (46 cm)
Starter	On/Off Switch	On/Off Switch
Rotor Style	Power Curve® Rotor	Power Curve Rotor
Snow Cut Depth - 1 Pass	6" (15 cm)	» 12" (31 cm)
Chute/Deflector Type	-	Locking Deflector
Warranty^	2-Year Full	2-Year Full

	SINGLE-STAGE			
	518 ZR/ZE 38472 / 38473	721 R/E 38752 / 38753	721 QZE 38756	821 QZE 38757
Engine	Toro® Premium 99cc 4-cycle OHV	» Toro Premium 212cc 4-cycle OHV	Toro Premium 212cc 4-cycle OHV	» Toro Premium 252cc 4-cycle OHV
Throw Distance	Up to 25' (8 m)	» Up to 35' (11 m)	Up to 35' (11 m)	» Up to 40' (12 m)
Clearing Width	18" (46 cm)	» 21" (53 cm)	21" (53 cm)	21" (53 cm)
Drive System	Rotor Propelled	» Power Propel® Self-Propel	Power Propel Self-Propel	Power Propel Self-Propel
Starter	Recoil / Electric Start	Recoil / Electric Start	Electric Start	Electric Start
Rotor Style	Power Curve Rotor	Power Curve Rotor	Power Curve Rotor	Power Curve Rotor
Snow Cut Depth - 1 Pass	12" (31 cm)	» 12.5" (32 cm)	12.5" (32 cm)	12.5" (32 cm)
Chute/Deflector Type	Curved w/Locking Deflector	» High Capacity w/Locking Deflector	High Capacity w/Locking Deflector	High Capacity w/Locking Deflector
Warranty^	2-Year Full	2-Year Full	2-Year Full	2-Year Full
GTS Warranty^	2-Year Residential Only	2-Year Residential Only	2-Year Residential Only	2-Year Residential Only

	SNOWMASTER®		
	724 ZXR 36001	724 QXE 36002	824 QXE 36003
Engine	Toro® Premium 212cc 4-cycle OHV	Toro Premium 212cc 4-cycle OHV	» Toro Premium 252cc 4-cycle OHV
Throw Distance	Up to 40' (12 m)	Up to 40' (12 m)	» Up to 45' (14 m)
Clearing Width	24" (61 cm)	24" (61 cm)	24" (61 cm)
Drive System	Personal Pace®	Personal Pace	Personal Pace
Starter	Recoil	» Electric Start	Electric Start
Rotor Style	In-Line 2-Stage, 10" (25 cm) Dia.	In-Line 2-Stage, 10" (25 cm) Dia.	In-Line 2-Stage, 10" (25 cm) Dia.
Snow Cut Depth - 1 Pass	18" (46 cm)	18" (46 cm)	18" (46 cm)
Chute/Deflector Type	Sub Zero Material w/Locking Deflector	» Sub Zero Material	Sub Zero Material
Warranty^	3-Year Limited	3-Year Limited	3-Year Limited
	Guaranteed For Life Lower Chute, Chute & Deflector	Guaranteed For Life Lower Chute, Chute & Deflector	Guaranteed For Life Lower Chute, Chute & Deflector

	COMPACT TWO-STAGE	
	824 OE 37798	826 OAE 37799
Engine	Toro® Premium 252cc 4-cycle OHV	Toro Premium 252cc 4-cycle OHV
Throw Distance	Up to 45' (13.5 m)	Up to 45' (13.5 m)
Clearing Width	24" (61 cm)	» 26" (66 cm)
Auto-Steering	-	✓
Drive System	Friction Disk	Friction Disk
Starter	Electric Start	Electric Start
Rotor Style	Anti-Clogging System, 11" (28 cm) Dia., Hardened Gears, No Shear Pins Needed	Anti-Clogging System, 11" (28 cm) Dia., Hardened Gears, No Shear Pins Needed
Snow Cut Depth - 1 Pass	20" (51 cm)	20" (51 cm)
Chute/Deflector Type	Steel Chute	Steel Chute
Warranty^	3-Year Limited ACS Guaranteed For Life	3-Year Limited ACS Guaranteed For Life

*See retailer for warranty details; †Based on average Traqline unit share for snow blower market from 2013 - 2018. *Compared to Toro® Power Max® models. Capacity will vary with conditions. **Battery manufacture rating = 60V maximum & 54V typical usage. Actual voltage varies with load.