



Ferrous Sulfate Heptahydrate

FORMULA: FeSO4*7H2O F.W. = 278 CAS# 7782-63-0

TYPICAL CHEMICAL ANALYSIS:

FesO4*7H2Ominimum99.5% *Ferrous Ironminimum20.0% *pH (5% Solution)2.5 to 5Adherent water<0.30%</td>*Complies with American Water Works Association Standard B402.

Heavy Metals (mg/kg)

< 0.2 Arsenic Lead < 2Cadmium < 3 Mercury < 0.05Chromium < 40 Nickel < 150< 30 Zinc < 80 Copper Note: Some metals can be lowered upon special request. Calcium Carbonate can be added as anti-caking agent upon request.

PHYSICAL

Physical Form	Blue-Green, Free Flowing Crystal
Bulk Density	55 lb. per cu. Ft.
Main Particle Size Range (90 – 95%)	- 7 + 60 MESH

TYPICAL USES: Water Treatment Flocculation Agent and Coagulant, Fertilizer, Feed Supplement, Paint Pigment.

PACKAGING AND SHIPPING: Bulk - 40,000# Tandem Truck, Pneumatic Truck LTL or Truckload 50# Poly or Paper Bags 2000# Bulk Bags

FREIGHT CLASSIFICATIONS: Ferrous Sulfate has an RQ of 1000 pounds, if less than 1000 pounds is in a single container the material is not regulated by D.O.T. as a hazardous material. Bulk Bag and Bulk DOT Description (> 1000 in container): Environmentally hazardous substances, solid, n.o.s., 9, UN3077, III, RQ, (ferrous sulfate)

The information and statements herein are believed to be reliable but are not to be construed as a warranty or representation for which we assume legal responsibility. Users should undertake sufficient verification and testing to determine the suitability for their own particular purpose. NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE.

7513 E. 96th Street • P.O. Box 50426 • Indianapolis, IN 46250-0426 (317) 845-0045 • Fax: (317) 845-9086