

# Fixture Type: Catalog Number: Project:

# **Surface Mounted**

# Step Light

Model & Voltage	Color Temp & CRI	Lumens	Finish
<b>4501</b> 9-15 VAC	2700K 85 3000K 85	55 55	BBR Bronze on Brass BK Black on Aluminum BZ Bronze on Aluminum WT White on Aluminum

Example: 4501-27BBR

# **FEATURES**

- Slim low profile design-surface mount installation, (no junction box)
- Die-cast aluminum or die-cast brass
- Invisible hardware
- 6' lead wire included
- Compatible with WAC Transformer
- Transformer required
- 10 yrs warranty

### **SPECIFICATIONS**

Construction: Corrosion resistant aluminum alloy, Solid die-

cast brass

Power: 4W

**Input:** 50/60Hz, 9-15 VAC

Dimming: MLV: %

**Light Source:** Integrated LED

3 Step Mac Adam Ellipse

Lens: Tempered Glass Rated Life: 70000 Hours

Finish: Enamel Coated White on Aluminum, Enamel

Coated Bronze on Aluminum, Enamel Coated Bronze on Brass, Enamel Coated Black on

Aluminum

Operating Temp: -40°F to 122°F (-40°C to 50°C)

Standards: UL, cUL, Wet Location Listed, IP66, ADA




### **FINISHES**



Location:

LINE DRAWING







# 12V Magnetic Transformer (Outdoor)

# Accessory

Model & Product		$L \times W \times H$
9075-TRN-SS	75W Magnetic Landscape Lighting Power Supply in Stainless Steel	13.97IN x 5.35IN x 5.63IN
9150-TRN-SS	150W Magnetic Landscape Lighting Power Supply in Stainless Steel	18.9IN x 6.69IN x 6.3IN
9300-TRN-SS	300W Magnetic Landscape Lighting Power Supply in Stainless Steel	18.9IN x 6.69IN x 6.3IN
9600-TRN-SS	600W Magnetic Landscape Lighting Power Supply in Stainless Steel	14.49IN x 10.08IN x 5.94IN

### DESORIE:T9075-TRN-SS

WAC Landscape Lighting Magnetic power supplies are 12V AC to support the entire line of 12V Landscape Lighting products, including Accent, Flood, Well, Indicator, Submersible, 12V Tape Light, Step and Wall, Deck and Patio, Path and Area, and Hardscape lighting products. The Stainless Steel housing enhances protection from corrosive and outdoor elements. Mounting extrusion with variating knockout sizes proved for a simple installation. Heavy gauged grounded and water resistant cord included for simple plug-in power feature. Hinged cover includes a loop to safely lock the power supply with an optional lock to secure access from inner contents. Multiple wire taps ranging from 12V-16V on terminal strip, for long runs where voltage drop may occur. Hinged cover includes a loop to safely lock the power supply with an optional lock to secure access from inner contents.

#### **FEATURES**

- Outdoor rated stainless steel transformer contains an outdoor rated 3-prong plug for power
- Knock outs for power and photosensor connections
- 3-prong outlet for timer
- Taps for 12V, 13V, 14V and 15V
- 6' lead input wire, except for the 600W which comes with a 5' lead wire
- UL 1838 Listed
- MLV Dimming capable, dimming dependent upon fixture type
- 5 year warranty

## **SPECIFICATIONS**

Construction: Stainless steel 120 VAC, 50/60Hz Input:

Finish: Stainless Steel Stainless Steel Operating Temp: -40°F to 122°F (-40°C to 50°C) Standards: UL, cUL, Wet Location Listed, IP65



Fixture Type: Catalog Number:

Project:

Location:

# **FINISHES**



Steel

## **LINE DRAWING**

