



The First Name in Turf Renovation™

LAWNNAIRE® ZTS

A New Approach to Aeration—the Lawnnaire® ZTS Stand-On Aerator

Innovative automatic chain tensoning system reduces the chain maintenance required.

Aeration Depth Gauge provides precise aeration depth control in varying soil conditions

Intuitive control panel with a tine lift switch to raise and lower tines

Flip up operator platform with a quick latch allows for the Lawnnaire® ZTS to be a walk behind aerator and a reduced footprint on trailers.

Integrated jack stands allow for easy maintenance of the Lawnnaire® ZTS

The Lawnnaire® ZTS will change the way you aerate!



SPECIFICATIONS

POWER

Engine Kawasaki FS541V
 Fuel Capacity 5 gal (18.9 L)
 Safety System Interlock, Engine will not start unless parking brake is engaged and OPC is released

TRANSMISSION

Hydrostatic 2 Hydro Gear® ZT3200
 Hydraulic Oil Capacity (qt. / L) 7 qt. (6.6L)

GROUND SPEED

Forward 0 - 7.4 mph (0-11.9 kmh)
 Reverse 0 - 3.1 mph (0-5.6 kmh)

WHEEL & TINE DRIVES

Drive Wheels Driven through roller chains
 Tine Drive Outside aeration tines are driven through roller chains
 Turning Radius - Tines Down 5 ft (1.5 m)
 Turning Radius - Tines Up 0
 Time to Raise/Lower Tines (sec) 1.4 up, 1.8 down

TIRES AND WHEELS

Style
 Drive Pneumatic
 Front Caster Pneumatic
 Drive 18 x 6.50 - 8
 Front Caster 13 x 5.00 - 6
 Pressure
 Drive (psi) 15 lbs. (7 kg)
 Front Caster (psi) 25 lbs. (11 kg)

AERATION

Aeration Width 30 in. (762 mm)
 Number of Tines 48
 Tine Down Pressure 0-700 lbs. (0 - 318 kg)
 Core Depth 2 - 5 in. (50 - 250 mm)
 Holes Per Square Foot ~5.1 (55/m²)

DIMENSIONS

Width 47.25 in. (1200 mm)
 Length 60.5 in. (1537 mm) platform up,
 69.5 in. (1765 mm) platform down
 Height 48 in. (1219 mm)
 Curb Weight 1,235 lbs. (560 kg)
 Productivity up to 97,800 ft²/hr (9,086 m²/hr)
 Warranty 2-year Limited Warranty

OPTIONAL ACCESSORIES

Run flat caster wheels
 Light kit

Specifications subject to change without notice.



Innovative automatic chain tensoning system reduces the chain maintenance required.



Aeration and consistent coring depth control for precision aeration in varying soil conditions; aerates up to 5" deep, in half-inch increments.



Tine lift switch to raise and lower tines conveniently located near control lever.



Optional LED light kit increases productivity by extending the work day.

WWW.RYANTURF.COM