

The Andersons Turf Products

Fertilizer

33-0-5

- Contains Fortify-N
- Contains iron for improved turf color
- Fortify-N features dual nitrogen stabilizer technology minimizing risk from environmental losses such as volatilization, leaching and denitrification.

Guaranteed Analysis

Total Nitrogen (N)	33.00%
33.00% Urea Nitrogen*	
Soluble Potash (K ₂ O)	5.00%
Iron (Fe).....	2.00%
Derived from urea, potassium chloride and ferric oxide.	
Chlorine (Cl) Max.....	4.24%

*33.00% urea nitrogen stabilized with N-[n-butyl] thiophosphoric triamide, and dicyandiamide

F002091

DIRECTIONS FOR USE

Apply only as directed. Apply during the growing season.

Application Rates:

LIGHT:	1.51 lbs/1,000 sq. ft.
LOW:	2.27 lbs/1,000 sq. ft.
MEDIUM:	3.03 lbs/1,000 sq. ft.
HIGH:	3.79 lbs/1,000 sq. ft.

For all applications:

- Apply to dry foliage.
- Water in after application with a minimum of 0.2 inches to help move particles into the turf canopy.
- Do not collect clippings for at least one mowing following application to avoid particle pick-up.

Cool Season Grasses:

- Apply at the LOW or MEDIUM RATE every 6-8 weeks during the period of active growth.
- Apply at the LIGHT RATE when temperatures exceed 85°F.

Warm Season Grasses:

- Apply at the LOW to HIGH RATE every 4-6 weeks during the period of active growth.

Note: This product contains the micronutrient iron for extra greening and to help prevent iron deficiency. Iron may stain concrete and other surfaces. Misapplied product to these surfaces should be removed promptly by sweeping or blowing. DO NOT WASH OFF WITH WATER.

Do not apply near water, storm drains or drainage ditches. Do not apply if heavy rain is expected. Apply this product only to your lawn and sweep any product that lands on the driveway, sidewalk or street, back onto your lawn.

STORAGE AND USE

Store in a clean, dry place.
Reseal opened bag by folding top down and securing.
Use only in clean, dry spreaders.
Do not leave unused product in spreaders.

IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS.

LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/JURISDICTION TO STATE/JURISDICTION.

Product of U.S.A.

Manufactured by:
The Andersons, Inc.
P.O. Box 119
Maumee, OH 43537
www.andersonsplantnutrient.com

Fortify is a registered trademark of The Andersons, Inc.

Suggested Spreader Settings						
These suggested spreader settings are not intended to replace calibration. Please calibrate your spreader before applying product.						
50 lbs. feeds 33,100 sq. ft. (0.76 acre) with 0.50 lbs. N/1,000 sq. ft. at the LIGHT RATE						
50 lbs. feeds 22,000 sq. ft. (0.51 acre) with 0.75 lbs. N/1,000 sq. ft. at the LOW RATE						
50 lbs. feeds 16,500 sq. ft. (0.38 acre) with 1.00 lbs. N/1,000 sq. ft. at the MEDIUM RATE						
50 lbs. feeds 13,100 sq. ft. (0.30 acre) with 1.25 lbs. N/1,000 sq. ft. at the HIGH RATE						
SPREADER	GROUND SPEED	WIDTH OF COVERAGE	SPREADER SETTINGS			
			LIGHT RATE 1.51 lbs/1,000 sq. ft.	LOW RATE 2.27 lbs/1,000 sq. ft.	MEDIUM RATE 3.03 lbs/1,000 sq. ft.	HIGH RATE 3.79 lbs/1,000 sq. ft.
Andersons Model 2000 / AccuPro 2000 (cone 4) Andersons 2000 SR / SR-2000 (cone 4)	3 mph	11 feet	J 1/2	K 1/4	L	L 3/4
Scotts R-8, R-8A (cone 4)	3 mph	11 feet	I	I 3/4	K	K 3/4
Lesco 020093 (pattern 0.25)	3 mph	8 feet	D	D 1/2	E	E 1/2
Lesco 705698 (pattern 0.25)	3 mph	8 feet	10	11	12	13
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) Pattern II-C	4.5 mph	40 feet	4 1/4	4 3/4	5 1/2	6
Vicon (03 Series)	4.5 mph	32 feet	17	22	26	30

SGN 215
Net Wt. 50 Lbs. (22.68 kg)



APT333UFE5.40