

# BRD-2620 BED REDEFINER Operator's Manual

# **WARNING**

**Burn Hazard** 



The muffler or catalytic muffler and surrounding cover may become extremely hot. Always keep clear of exhaust and muffler area, otherwise serious personal injury may occur.

# **WARNING**

The engine exhaust from this product contains chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

# WARNING



Users of this equipment risk injury to themselves and others if the unit is used improperly and/or safety precautions are not followed. Echo provides an operator's manual and a safety manual. Both must be

read and understood for proper and safe operation. Failure to do so could result in serious injury.

Note: This product complies with CAN ICES-2/NMB-2.

Specifications, descriptions and illustrative material in this literature are as accurate as known at the time of publication, but are subject to change without notice. Illustrations may include optional equipment and accessories, and may not include all standard equipment.

X7502343000

#### **TABLE OF CONTENTS**

Table of Contents	2
Introduction	
Servicing Information	3
Parts/Serial Number	3
Service	3
Echo Consumer Product Support	4
Product Registration	4
Additional or Replacement Manuals	4
Safety	4
Manual Safety Symbols and Important Information	4
International Symbols	
Personal Condition and Safety Equipment	7
Equipment	
Emission Control (Exhaust & Evaporative)	12
CARB And EPA Emissions Control Information	12
Description	14
Contents	
Assembly	17
Support Handle	
Edger Blade Installation	
Operation	
Fuel	
Starting Cold Engine	
Starting Warm Engine	
Stopping Engine	
Operation Techniques	
Edging Operation	
Maintenance	
Skill Levels	
Maintenance Intervals	
Air Filter	
Fuel Filter	
Spark Plug	31
Cooling System	
Exhaust System	
Carburetor Adjustment	
Drive Shaft Lubrication	
Blade Replacement/Lubrication	
Troubleshooting	
Storage	
Long Term Storage (Over 30 Days)	
Specifications	
Product Registration	

#### INTRODUCTION

Welcome to the ECHO family. This ECHO product was designed and manufactured to provide long life and on-the-job dependability. Read and understand this manual and the safety manual. Keep the manuals in a safe place for future reference.

The operators manual contains specifications and information for safety, operation, maintenance, storage and assembly specific to this product. Scan the QR codes throughout the operator's manual for more information.

The safety manual explains possible hazards and the measures you should take to insure safe operation.

#### SERVICING INFORMATION

#### Parts/Serial Number

Genuine ECHO Parts and Assemblies for your ECHO products are available only from an Authorized ECHO Dealer. When you do need to buy parts always have the Model Number and Serial Number of the unit with you. For future reference write them in the space provided below.

Model No.	
Serial No.	



#### Service

Service of this product during the warranty period must be performed by an Authorized ECHO Service Dealer. For the name and address of the Authorized ECHO Service Dealer nearest you, ask your retailer or call: 1-800-432-ECHO (3246). Dealer information is also available on our Web Site. <a href="www.echo-usa.com">www.echo-usa.com</a>. When presenting your unit for Warranty service/repairs, proof of purchase is required.

SAFETY BRD-2620

#### **Echo Consumer Product Support**

If you require assistance or have questions concerning the application, operation, or maintenance of this product, call the ECHO Consumer Product Support Department at 1-800-673-1558 from 8:00 am to 5:00 pm (Central Standard Time) Monday through Friday. Before calling, please know the model and serial number of your unit.

#### **Product Registration**

Register your ECHO equipment on-line at <a href="www.echo-usa.com">www.echo-usa.com</a> or by filling out the product registration sheet included in this manual. Registering your product confirms warranty coverage and provides a direct link to ECHO if we find it necessary to contact you.

#### **Additional or Replacement Manuals**

Replacement Operator or Safety Manuals, and Parts Catalogs, are available from your Authorized ECHO Service Dealer, or at www.echo-usa.com, or by contacting ECHO Inc., 400 Oakwood Road, Lake Zurich, IL 60047 (800-673-1558). Always check www.echo-usa.com for updated information.



**Safety Videos** are available from your Authorized ECHO Service Dealer. A \$5.00 shipping charge is required for each video.

#### SAFETY

#### Manual Safety Symbols and Important Information

Throughout this manual and on the product itself, you will find safety alerts and helpful, informational messages preceded by symbols or key words. The following is an explanation of those symbols and key words and what they mean to you.

# **▲** DANGER

The safety alert symbol accompanied by the word "DANGER" calls attention to an act or condition which WILL lead to serious personal injury or death if not avoided.

# WARNING

The safety alert symbol accompanied by the word "WARNING" calls attention to an act or condition which CAN lead to serious personal injury or death if not avoided.

# **A** CAUTION

The safety alert symbol accompanied by the word "CAUTION" calls attention to an act or condition which may lead to minor or moderate personal injury if not avoided.

# NOTICE

The enclosed message provides information necessary for the protection of the unit.

Note: This enclosed message provides tips for use, care and maintenance of the unit.



CIRCLE AND SLASH SYMBOL

This symbol means the specific action shown is prohibited. Ignoring these prohibitions can result in serious or fatal injury.

#### **International Symbols**

Symbol	Description	Symbol	Description
	Warning, See Operator's Manual		Carburetor Adjustment - High Speed Mixture
	Wear Eye, Ear and Head Protection	T	Carburetor Adjustment - Idle Speed
	Wear Hand and Foot Protection		Carburetor Adjustment - Low Speed Mixture
A	Safety/Alert	STOP	Emergency Stop

SAFETY BRD-2620

Symbol	Description	Symbol	Description
	Hot Surface	+0	Fuel and Oil Mixture
		AVOIE Keep Bystanders At	D KICKOUT Least 15 m (50 ft.) Away.
		Beware Thrown Obj	ects Wear Eye Protection
	DO NOT Allow Flames or Sparks Near Fuel	ignition ON OFF	Ignition ON / OFF
3	DO NOT Smoke Near Fuel	₩	Primer Bulb
+	Choke Control "RUN" Position (Choke Open)	1	Choke Control "COLD START" Position (Choke Closed)
	Keep Feet Away From Blade		Rotating Cutting Attachment
S A Lamiconi		Keep Bystan Away	iders and Helpers 15 m (50 ft.)
	Thrown Objects		Direction of Blade



#### **Personal Condition and Safety Equipment**

# **WARNING**

Users of this product risk injury to themselves and others if the unit is used improperly and/or safety precautions are not followed. Proper clothing and safety gear must be worn when operating unit.

#### **Physical Condition**

Your judgment and physical dexterity may not be good:

- · If you are tired or sick
- If you are taking medication
- If you have taken alcohol or drugs

Operate unit only if you are physically and mentally well.

#### **Eye Protection**

# **WARNING**

- Eye protection that meets ANSI Z87.1 or CE requirements must be worn whenever you operate the unit.
- For additional safety, a full-face shield may be worn over safety glasses or goggles to provide protection from sharp branches or flying debris.



SAFETY BRD-2620

#### **Hand Protection**

Wear sturdy, no-slip, rubber work gloves to improve your grip on the handles. Gloves also provide protection against cuts and scratches, cold environments, and reduce the transmission of machine vibration to your hands.

#### **Hearing/Ear Protection**

ECHO recommends wearing hearing protection whenever unit is used.

#### **Breathing Protection**

Operators who are sensitive to dust or other common airborne allergens may need to wear a dust mask to prevent inhaling these materials while operating unit. Dust masks can provide protection against dust, plant debris, and other plant matter such as pollen. Make sure the mask does not impair your vision, and replace the mask as needed to prevent air restrictions.

#### **Proper Clothing**

Wear snug-fitting, durable clothing:

- Pants should have long legs, shirts should have long sleeves.
- · DO NOT WEAR SHORTS.
- DO NOT WEAR TIES, SCARVES, JEWELRY, or clothing with loose or hanging items that could become entangled in moving parts or surrounding growth.
- Keep clothing buttoned or zipped, and keep shirt tails tucked in.

Wear sturdy work shoes with nonskid rubber soles:

- DO NOT WEAR OPEN TOED SHOES.
- DO NOT OPERATE UNIT BAREFOOTED.

Keep long hair away from engine and air intake. Retain hair with cap or net.

Heavy protective clothing can increase operator fatigue, which may lead to heat stroke. Schedule heavy work for early morning or late afternoon hours when temperatures are cooler.

# **WARNING**

The components of this machine generate an electromagnetic field during operation, which may interfere with some pacemakers. To reduce the risk of serious or fatal injury, persons with pacemakers should consult with their physician and the pacemaker manufacturer before operating this machine. In the absence of such information, ECHO does not recommend the use of this machine by anyone who has a pacemaker.


**Extended Operation / Extreme Conditions** 

# **A** CAUTION

Prolonged exposure to cold and/or vibration may result in injury. Read and follow all safety and operation instructions to minimize risk of injury. Failure to follow instructions may result in painful wrist/hand/arm injuries.

It is believed that a condition called Raynaud's Phenomenon, which affects the fingers of certain individuals, may be brought about by exposure to vibration and cold. Exposure to vibration and cold may cause tingling and burning sensations, followed by loss of color and numbness in the fingers. The following precautions are strongly recommended, because the minimum exposure, which might trigger the ailment, is unknown.


- Keep your body warm, especially the head, neck, feet, ankles, hands, and wrists.
- Maintain good blood circulation by performing vigorous arm exercises during frequent work breaks, and also by not smoking.
- Limit the hours of operation. Try to fill each day with jobs where operating the unit or other handheld power equipment is not required.



 If you experience discomfort, redness, and swelling of the fingers followed by whitening and loss of feeling, consult your physician before further exposing yourself to cold and vibration. SAFETY BRD-2620

# Repetitive Stress Injuries (RSI)

It is believed that overusing the muscles and tendons of the fingers, hands, arms, and shoulders may cause soreness, swelling, numbness, weakness, and extreme pain in those areas. Certain repetitive hand activities may put you at a high risk for developing a Repetitive Stress Injury (RSI). An extreme RSI condition is Carpal Tunnel Syndrome (CTS), which could occur when your wrist swells and squeezes a vital nerve that runs through the area. Some believe that



prolonged exposure to vibration may contribute to CTS. CTS can cause severe pain for months or even years.

To reduce the risk of RSI/CTS, do the following:

- Avoid using your wrist in a bent, extended, or twisted position. Instead try
  to maintain a straight wrist position. Also, when grasping, use your whole
  hand, not just the thumb and index finger.
- Take periodic breaks to minimize repetition and rest your hands.
- Reduce the speed and force with which you do the repetitive movement.
- Do exercises to strengthen the hand and arm muscles.
- Immediately stop using all power equipment and consult a doctor if you
  feel tingling, numbness, or pain in the fingers, hands, wrists, or arms. The
  sooner RSI/CTS is diagnosed, the more likely permanent nerve and
  muscle damage can be prevented.

# A DANGER

All over head electrical conductors and communications wires can have electricity flow with high voltages. This unit is not insulated against electrical current. Never touch wires directly or indirectly, otherwise serious injury or death may result.

# **▲** DANGER

Do not operate this product indoors or in inadequately ventilated areas. Engine exhaust contains poisonous emissions and can cause serious injury or death.

**IIIECHO** 

#### Read the Manuals

 Provide all users of this equipment with the Operator's Manual and Safety Manual for instructions on Safe Operation.

#### Clear the Work Area

 Spectators and fellow workers must be warned, and children and animals prevented from coming nearer than 15 m (50 ft.) while the unit is in use.

#### Keep a Firm Grip

 Always hold throttle handle and support handle with thumbs and fingers tightly encircling the handles.

#### Keep a Solid Stance

 Maintain footing and balance at all times. Do not stand on slippery, uneven or unstable surfaces. Do not work in odd positions or on ladders. Do not over reach.

#### **Avoid Hot Surfaces**

 Keep exhaust area clear of flammable debris. Avoid contact during and immediately after operation.





#### Equipment

# **WARNING**

Use only ECHO attachments. Serious injury may result from the use of a non-approved attachment combination. ECHO, INC. will not be responsible for the failure of cutting devices, attachments or accessories which have not been tested and approved by ECHO. Read and comply with all safety instructions listed in this manual and safety manual.

- Check unit for loose/missing nuts, bolts, and screws. Tighten and/or replace as needed.
- Inspect shield for damage and that shield is securely in place. Replace if shield is damaged or missing.
- Check that the cutting attachment is firmly attached and in safe operating condition.
- Check that support handle is adjusted for safe, comfortable operation.
   See Assembly Section for proper adjustment.



# **WARNING**

Moving parts can amputate fingers or cause severe injuries. Keep hands, clothing and loose objects away from all openings.

- ALWAYS stop engine, disconnect spark plug, and make sure all moving parts have come to a complete stop before removing obstructions, clearing debris, or servicing unit.
- ◆ DO NOT start or operate unit unless all guards and protective covers are properly assembled to unit.
- ◆ NEVER reach into any opening while the engine is running. Moving parts may not be visible through openings.

# WARNING

Periodically Check fuel system (fuel lines, vent, grommet, fuel tank, and fuel cap) for leaks especially if the unit is dropped. If damage or leaks are found, do not use unit, otherwise serious personal injury or property damage may occur. Have unit repaired by an authorized servicing dealer before using.

# EMISSION CONTROL (EXHAUST & EVAPORATIVE)

#### **CARB And EPA Emissions Control Information**

The emission control system for the engine is EM (engine modification) and, if the second to last character of the Engine Family on the Emission Control Information label (sample below) is "B", "C", "K", or "T", the emission control system is EM and TWC (3-way catalyst). The fuel tank/fuel line emission control

EMISSION CONTROL INFORMATION ENGINE FAMILY: (E)EINS, 0214EQ DISPLACEMENT: 21.2cc EMISSION COMPLIANCE PERIOD: 50Hours THIS ENGINE MEETS 2013 U.S. EPA EXILVEY & CALIFORNIA EXHAUP ENUSSION REBULATIONS FOR S.O.R.E. REFER TO OWNER'S

MANUAL FOR MAINTENANCE SPECIFICATIONS AND ADJUSTMENTS.

YAMABIKO CORP. MMM/YYYYY



system is EVAP (evaporative emissions). Evaporative emissions for California models are only applicable to fuel tanks.

An Emission Control Label is located on the engine. (This is an EXAMPLE ONLY, information on label varies by engine FAMILY).

#### **Product Emission Durability** (Emission Compliance Period)

EMISSION CONTROL INFORMATION


ENGINE FAMILY: CEHXS.0214KL DISPLACEMENT: 21.2cc EMISSION COMPLIANCE PERIOD: 300Hours THIS ENGINE MEETS 2012 U.S. EPA EXH/EVP & CALIFORNIA EXH/EVP EMISSION REGULATIONS FOR S.O.R.E. REFER TO OWNER'S MANUAL FOR MAINTENANCE SPECIFICATIONS AND ADJUSTMENTS.

YAMABIKO CORP. MMM/YYYY

The 50 or 300 hour emission compliance period is the time span selected by the manufacturer certifying the engine emissions output meets applicable emissions regulations, provided that approved maintenance procedures are followed as listed in the Maintenance Section of this manual.

#### **DESCRIPTION**

Locate the safety decal(s) on your unit. Make sure the decal(s) is legible and that you understand and follow the instructions on it. If a decal cannot be read, a new one can be ordered from your ECHO dealer. The safety label is for example only. Your label may appear slightly different.











- 1. Power Head
- 2. Throttle Handle For Right Hand
- 3. Throttle Trigger Lockout
- 4. Stop Switch
- 5. Support Handle For Left Hand
- 6. Drive Shaft Assembly
- 7. Debris Shield / Flap
- 8. Blade
- 9. Wheel
- 10. Throttle Trigger
- 11. Top Guard
- 12. Spark Arrestor Muffler Or Spark Arrestor Muffler With Catalyst
- 13. Fuel Tank
- 14. Fuel Tank Cap
- 15. Recoil Starter / Handle
- 16. Purge Bulb
- 17. Air Cleaner
- 18. Choke
- 19. Spark Plug



CONTENTS BRD-2620

#### **CONTENTS**

The ECHO product you purchased has been factory pre-assembled for your convenience. Due to packaging restrictions, some assembly may be necessary.

After opening the carton, check for damage. Immediately notify your retailer or ECHO Dealer of damaged or missing parts. Use the contents list to check for missing parts.


- 1 Power Head / Drive Shaft Assembly
- 1 Operator's Manual
- 1 Safety Manual
- 1 Warranty Statement
- 2 Split Pins
- 1 Edger Blade
- 1 Safety Glasses

#### **ASSEMBLY**

#### **Support Handle**


 If necessary, position support handle for comfortable operation and securely tighten screws.


Note: Label shows minimum spacing for support handle location.



#### **Edger Blade Installation**

- Remove bed redefining blade as shown in "Blade Replacement" Section. Discard used split pin.
- Do not remove inner blade adapter (A) or locking tool (B) (not provided).
- Install and center edger blade
   (C) on inner adapter.
- Install outer adapter (D) and nut (E).
- 5. Tighten nut (E) firmly, counterclockwise.
- 6. Remove locking tool (B).
- 7. Install new split pin (F) to secure nut (E).





#### **OPERATION**

# **WARNING**

Moving parts can amputate fingers or cause severe injuries. Keep hands, clothing and loose objects away from all openings. Always stop engine, disconnect spark plug, and make sure all moving parts have come to a complete stop before removing obstructions, clearing debris, or servicing unit.

# WARNING

Engine exhaust IS HOT, and contains Carbon Monoxide (CO), a poison gas. Breathing CO can cause unconsciousness, serious injury, or death. Exhaust can cause serious burns. ALWAYS position unit so that exhaust is directed away from your face and body.

# **▲ WARNING**

Operation of this equipment may create sparks that can start fires around dry vegetation. This unit is equipped with a spark arrestor to prevent discharge of hot particles from the engine. Metal cutters can also create sparks if the cutter strikes rocks, metal, or other hard objects. Contact local fire authorities for laws or regulations regarding fire prevention requirements.

#### **Fuel**

# **WARNING**

Diesel fuels and alternative fuels, such as E-15 (15% ethanol), E-85 (85% ethanol) or any fuels not meeting ECHO requirements are NOT approved for use in ECHO 2-stroke gasoline engines. Use of diesel or alternative fuels may cause performance problems, loss of power, overheating, fuel vapor lock, and unintended machine operation, including, but not limited to, improper clutch engagement. Diesel or alternative fuels may also cause premature deterioration of fuel lines, gaskets, carburetors and other engine components.



#### **Fuel Requirements**

Gasoline - Use 89 Octane [R+M/2] (mid grade or higher) gasoline known to be good quality. Gasoline may contain up to 10% Ethanol (grain alcohol) or 15% MTBE (methyl tertiary-butyl ether). Gasoline containing methanol (wood alcohol) is **NOT** approved. ECHO Red Armor Fuel<sup>™</sup> (Power Fuel<sup>™</sup>) is 93 octane, ethanol-free fuel premixed with ECHO Red Armor<sup>®</sup> engine oil at 50:1 ratio. Use of ECHO Red Armor Fuel <sup>™</sup> (Power Fuel <sup>™</sup>) is recommended to extend engine life in all air-cooled 2-stroke and 2/4-stroke hybrid engines.

**Two Stroke Oil** - A two-stroke engine oil meeting ISO-L-EGD (ISO/CD 13738) and J.A.S.O. <u>FD</u> Standards must be used. Echo brand 2-stroke oils meet these standards. Engine problems due to inadequate lubrication caused by failure to use an ISO-L-EGD (ISO/CD 13738) and J.A.S.O. M345-<u>FD</u> certified oil, such as Echo brand 2-stroke oils, will void the two-stroke engine warranty.

# NOTICE

Echo brand 2-stroke oils may be mixed at 50:1 ratio for application in all Echo engines sold in the past regardless of ratio specified in those manuals.

#### **Handling Fuel**

# **▲** DANGER

Fuel is VERY flammable. Use extreme care when mixing, storing or handling, or serious personal injury may result.

- Use an approved fuel container.
- DO NOT smoke near fuel.
- DO NOT allow flames or sparks near fuel.
- Fuel tanks/cans may be under pressure. Always loosen fuel caps slowly allowing pressure to equalize.
- ◆ NEVER refuel a unit when the engine is HOT or RUNNING!
- DO NOT fill fuel tanks indoors. ALWAYS fill fuel tanks outdoors over bare ground.
- ◆ DO NOT overfill fuel tank. Wipe up spills immediately.
- Securely tighten fuel tank cap and close fuel container after refueling.
- Inspect for fuel leakage. If fuel leakage is found, do not start or operate unit until leakage is repaired.
- ◆ Move at least 3 m (10 ft.) from refueling location before starting the engine.

#### Mixing Instructions

- Fill an approved fuel container with half of the required amount of gasoline.
- 2. Add the proper amount of 2-stroke oil to gasoline.
- 3. Close container and shake to mix oil with gasoline.
- 4. Add remaining gasoline, close fuel container, and remix.

Fue	Fuel to Oil Mix – 50:1 Ratio		
US		Metric	
Gas	Oil	Gas	Oil
Gallons	Oz.	Liter	CC.
1	2.6	5	100
2	5.2	10	200
5	13	25	500

# NOTICE

Spilled fuel is a leading cause of hydrocarbon emissions. Some states may require the use of automatic fuel shut-off containers to reduce fuel spillage.

 Empty the fuel tank prior to storing the unit. Return unused fuel to an approved fuel storage container.

**Storage** - Fuel storage laws vary by locality. Contact your local government for the laws affecting your area. As a precaution, store fuel in an approved, airtight container. Store in a well-ventilated, unoccupied building, away from sparks and flames.



#### NOTICE

Stored fuel ages. Do not mix more fuel than you expect to use in thirty (30) days, ninety (90) days when a fuel stabilizer is added.

#### NOTICE

Stored two-stroke fuel may separate. ALWAYS shake fuel container thoroughly before each use.

# NOTICE

Used oil and gasoline, and soiled towels are hazardous waste materials. Disposal laws vary by locality.


#### **Starting Cold Engine**

# **WARNING**

The attachment will operate immediately when the engine starts, and could result in possible serious injury. Keep movable parts of the attachment away from objects that could become entangled or thrown, and surfaces that could cause loss of control.

#### 1. Stop Switch

Move stop switch button (A) forward, away from the STOP position.



#### 2. Choke


Move choke lever (B) to COLD START ( ) position.

#### 3. Purge Bulb

Pump purge bulb (C) until fuel is visible and flows freely in the clear fuel tank return line. Pump bulb an additional 4 or 5 times.

#### Recoil Starter

Lay the unit on a flat area and keep movable attachment parts clear of all obstacles. Firmly




grasp throttle handle and throttle trigger lockout with left hand and fully depress throttle trigger to wide open position. Rapidly pull recoil starter handle/rope (D) until engine fires (or maximum five [5] pulls).

OPERATION BRD-2620

#### 5. Choke

After engine fires (or 5 pulls). move choke to the RUN ( | | | | | | ) (open) position. Firmly grasp throttle handle and throttle trigger lockout with left hand and fully depress throttle trigger to wide open position. Pull starter handle/rope (D) until engine starts and runs. Release throttle



trigger and allow unit to warm up at idle for several minutes.

Note: If engine does not start with choke in "RUN" position after 5 pulls, repeat instructions 2 - 5.

#### 6. Throttle Trigger

After engine warm-up, grip throttle handle and support handle. Depress the throttle trigger lockout, and gradually depress throttle trigger to increase engine RPM to operating speed.

#### **Starting Warm Engine**

The starting procedure is the same as Cold Start except DO NOT close the choke, and do not hold throttle trigger fully depressed.


# WARNING

The attachment should not move at idle, otherwise serious personal injury may result.

Note: If attachment moves, readjust carburetor according to "Carburetor Adjustment" instructions in this manual or see your ECHO Dealer.


#### 1. Stop Switch

Move stop switch button (A) forward away from the STOP position.



#### 2. Purge Bulb

Pump purge bulb (B) until fuel is visible in the "Clear" fuel return line. Pump bulb an additional 4 or 5 times.



#### Recoil Starter

Lay the unit on a flat area and keep movable attachment parts clear of all obstacles. Firmly grip throttle handle and throttle trigger lockout with left hand. Rapidly pull recoil starter handle/rope (D) until engine fires.

Note: If engine does not start after 5 pulls, use Cold Start Procedure.


#### Stopping Engine

#### 1. Throttle

Release throttle trigger and allow engine to return to idle before shutting off engine.

#### 2. Stop Switch

Move stop switch button (A) backward to STOP position.



# **WARNING**

If engine does not stop when stop switch is moved to STOP position, close choke - COLD START position - to stall engine. Have your ECHO dealer repair stop switch before using unit again.

#### **Operation Techniques**


# **A WARNING**

Before operating unit, be sure to read and understand the entire Operator's Manual to avoid the chance of serious personal injury.

Note: For best results, use BRD redefining blade (provided with unit) ONLY for redefining existing bed edges. For edging next to curbs, sidewalks, or other hard surfaces, remove redefining blade and install ECHO Approved Premium Power Edger blade. Use of redefining blade next to hard surfaces, can lead to premature blade wear.



- Always grip throttle handle with right hand, and support handle with left hand
- Before using Redefiner, check the area and remove objects that could be thrown.
- Carefully plan your direction of travel. Walk outside of bed. Be aware of curbs or other obstacles.
- 4. Work with body turned toward engine as shown. Travel in





# NOTICE

Do not walk towards gear case while operating unit with redefining blade installed, otherwise poor performance or damage to unit could occur.

- When starting to work, run the engine at full throttle, and lower the blade gently into the ground. Travel around perimeter of bed, allowing the Redefiner to improve bed's edge.
- Do not force the blade. Move only as quickly as conditions will allow. If performance suffers or engine RPM drops, reduce walking speed or decrease blade depth and allow engine RPM to return to normal before continuing.




Note: Blade height may need to be adjusted due to differences in height between the bed and the top of the grass.

# **WARNING**

Never adjust blade height while engine is running, otherwise serious personal injury may result.

 Loosen adjustment knob (A) and adjust the blade's depth of cut. Tighten adjustment knob (A) when desired blade height is achieved.

 If shield clogs with mud or debris, do not hit unit against hard surfaces to clean, or damage to unit may occur. Stop engine and unclog shield with a suitable tool.



# NOTICE

Be sure blade has completely stopped spinning before setting unit on concrete or other hard surface. Never allow spinning blade to contact hard surfaces. Carbide teeth on blade can break, or damage to surface can occur.

# WARNING

The complete unit, specifically the drive shaft assembly and muffler exhaust area may become very hot during use. Avoid contact during and immediately after operation, otherwise serious personal injury may result.

#### **Edging Operation**

# **WARNING**

Before edging, be sure to read and understand the entire Operator's Manual and Safety Manual to avoid the chance of serious personal injury.

- Before edging, water the area to soften the ground to make edging easier.
- Before edging, check the area and remove all obstacles and objects that could be thrown.
- 3. Plan to edge regularly to make it easier to keep a neat edge and to avoid having to make more than one pass.

# **WARNING**


Never adjust blade height or clear debris from shield with engine running, otherwise serious personal injury may result.

Note: Blade depth may have to be adjusted due to differences in height between the hard surface and the top of the grass.



4. Loosen blade adjustment knob and adjust the blade's depth of cut to produce a fine cut between sidewalk and grass using a minimum blade depth, usually with about 13 mm (0.5 in.) of the blade into the ground. Tighten adjustment knob.


- Before edging, plan your direction of travel so that the unit will always be on your right side and so that you walk on a hard surface whenever possible.
- 6. Position edger as shown.
- When starting to work, run the engine at full throttle, and lower the blade gently into the ground. Travel around perimeter of bed, allowing the Redefiner to improve bed's edge.



# NOTICE

Use the blade location slot in the top of the debris shield as a guide to align the blade with the cut during edging.

 Do not force the blade. Move only as quickly as the blade will allow.



#### **MAINTENANCE**

# **WARNING**

Moving parts can amputate fingers or cause severe injuries. Keep hands, clothing and loose objects away from all openings. Always stop engine, disconnect spark plug, and make sure all moving parts have come to a complete stop before removing obstructions, clearing debris, or servicing unit. Allow unit to cool before performing service. Wear gloves to protect hands from sharp edges and hot surfaces.

Your ECHO unit is designed to provide many hours of trouble free service. Regular scheduled maintenance will help your unit achieve that goal. If you are unsure or are not equipped with the necessary tools, we recommend that you take your unit to an ECHO Servicing Dealer for maintenance. To help you decide whether you want to DO-IT-YOURSELF or have the ECHO Dealer do it, each maintenance task has been graded. If the task is not listed, see your ECHO Dealer for repairs.

#### Skill Levels

**Level 1** = Easy to do. Common tools may be required.

Level 2 = Moderate difficulty. Some specialized tools may be required.

Level 3 = See your dealer.

Click HERE or go to http://www.echo-usa.com/products/maintenance-kit for information on Maintenance Kits.

#### Maintenance Intervals

COMPONENT/SYSTEM	MAINTENANCE PROCEDURE	REQ'D SKILL LEVEL
Daily or Before Use		
Air Filter	Inspect/Clean *	1
Choke Shutter	Inspect/Clean *	1
Fuel System	Inspect (2)	1
Cooling System	Inspect/Clean	2
Recoil Starter Rope	Inspect/Clean *	1
Screws/Nuts/Bolts	Inspect/Tighten/Replace *	1
Blade	Inspect	1

COMPONENT/SYSTEM	MAINTENANCE PROCEDURE	REQ'D SKILL LEVEL
Every Refuel		•
Fuel System	Inspect (2)	1
Blade	Inspect	1
3 Months	1	•
Air Filter	Replace *	1
Fuel Filter	Inspect *	1
Fuel Cap Gasket	Inspect *	1
Spark Plug	Inspect/Clean/Replace *	1
Muffler Spark Arrestor	Inspect/Clean/Replace *	2
Cylinder Exhaust Port	Inspect/Clean/Decarbon	2
Drive Shaft (Flex Cable Models)	Grease (1)	2
Gear Housing	Grease (1)	2
Blade	Inspect*	
Yearly	ı	1
Fuel Filter	Inspect/Replace *	1
Fuel Cap Gasket	Replace *	1

**IMPORTANT NOTE** - Time intervals shown are maximum. Actual use and your experience will determine the frequency of required maintenance.

#### **MAINTENANCE PROCEDURE NOTES:**

- (1) Apply lithium based grease every 25 hours of use.
- (2) Low evaporative fuel tanks DO NOT require regular maintenance to maintain emission integrity.
- \* Replacement is recommended based on the finding of damage or wear during inspection

#### Air Filter

#### Level 1

Parts Required: Tune Up Kit.


1. Close choke (COLD START [ ] position). This prevents dirt from entering the carburetor throat when the air filter is removed. Brush accumulated dirt from air cleaner area.

2. Remove air filter cover. Brush dirt from inside cover.

# NOTICE

Assure throttle wire retaining clip (A) remains in place as shown when removing or installing air filter cover.

- Remove foam pre-filter (B) and air filter and clean as indicated below:
- 4. Foam Pre-filter.
- Clean foam filter in water/detergent solution and rinse with clean water.
  - Wrap the filter in a clean, dry cloth and squeeze (do not wring) dry. Allow to dry completely before reuse. Do not oil.




#### Air Filter

- Lightly brush debris from filter. Replace filter if it is damaged, fuel soaked, very dirty, or the rubber sealing edges are deformed.
- 6. Assemble components in reverse order.

#### NOTICE

Assure air filter is assembled with pleats oriented vertically.



#### **Fuel Filter**

Level 1.

Parts Required: Tune Up Kit.

# **A** DANGER

Fuel is VERY flammable. Use extreme care when mixing, storing or handling, or serious personal injury may result.

- Use a clean rag to remove loose dirt from around fuel cap and empty fuel tank.
- 2. Pull the fuel filter from the fuel tank.

# NOTICE

Do not damage fuel line while removing fuel filter from tank.

3. Remove the filter from the line and install the new filter.

Note: Federal EPA regulations

require all model year 2012 and later gasoline powered engines produced for sale in the United States to be equipped with a special low permeation fuel supply hose between the carburetor and fuel tank. When servicing model year 2012 and later equipment, only fuel supply hoses certified by EPA can be used to replace the original equipment supply hose. Fines up to \$37,500 may be enforced for using an un-certified replacement part.

#### Spark Plug

Level 2.

Parts Required: Tune Up Kit.


# NOTICE

Use only NGK CMR7H spark plug otherwise severe engine damage may occur.

*IIIEEHD*.



- Remove spark plug and check for fouling, worn and rounded center electrode.
- Clean the plug or replace with a new one. DO NOT sand blast to clean. Remaining sand will damage engine.
- 3. Adjust spark plug gap by bending outer electrode.
- 4. Tighten spark plug to 102-153 kgf•cm (89-133 in•lbf).



#### **Cooling System**


Level 2.

# NOTICE

To maintain proper engine operating temperatures, cooling air must pass freely through the cylinder fin area. This flow of air carries combustion heat away from the engine.

Overheating and engine seizure can occur when:


 Air intakes are blocked, preventing cooling air from reaching the cylinder.



Dust and grass build up on the outside of the cylinder. This build up insulates the engine and prevents the heat from leaving.

Removal of cooling passage blockages or cleaning of cooling fins is considered "Normal Maintenance." Any failure attributed to lack of maintenance is not warranted.


- 1. Remove spark plug lead.
- Remove muffler cover (A).
- 3. Remove engine cover (B).



# **NOTICE**

DO NOT use a metal scraper to remove dirt from the cylinder fins.

- 4. Use brush to remove dirt from the cylinder fins.
- Remove grass and leaves from the grid (C) between the recoil starter and fuel tank.
- Assemble components in reverse order.



#### **Exhaust System**

# Spark Arrestor Screen

Level 2.

Parts Required: Spark Arrestor Screen, Gasket

- 1. Remove spark plug lead.
- 2. Remove muffler cover (A).
- Place piston at Top Dead Center (TDC) to prevent carbon or dirt from entering cylinder.

- Remove spark arrestor screen cover (B), gasket (C), and screen (D), from muffler body.
- Clean carbon deposits from muffler components.

Note: When cleaning carbon deposit, be careful not to damage the catalytic element inside muffler.


- 6. Replace screen if it is cracked, plugged, or has holes burned through.
- 7. Assemble components in reverse order.

#### **Exhaust Port Cleaning**

Level 2.

Parts Required: As needed: Heat Shield

- Remove spark plug lead from spark plug, and remove muffler cover.
- Place piston at top dead center. Remove muffler (A) and heat shield (B).
- Use a wood or plastic scraping tool to clean deposits from cylinder exhaust port (C).



# **NOTICE**

Never use a metal tool to scrape carbon from the exhaust port. Do not scratch the cylinder or piston when cleaning the exhaust port. Do not allow carbon particles to enter the cylinder.

- 4. Inspect heat shield, and replace if damaged.
- Install heat shield and muffler.
- Tighten muffler mounting bolts (or nuts) to 90-110 kgf•cm (80-95 in•lbf).



- 7. Install muffler cover and attach spark plug lead.
- 8. Start engine, and warm to operating temperature.
- 9. Stop engine, and re-tighten mounting bolts (or nuts) to specifications.

#### **Carburetor Adjustment**

Level 2.

# **WARNING**

When carburetor adjustment is completed, the cutting attachment should not move at idle, otherwise serious personal injury may result.

#### **Engine Break-In**

New engines must be operated a minimum duration of two tanks of fuel break-in before carburetor adjustments can be made. During the break-in period your engine performance will increase and exhaust emissions will stabilize. Idle speed can be adjusted as required.

#### **High Altitude Operation**


This engine has been factory adjusted to maintain satisfactory starting, emission, and durability performance up to 330 m (1100 ft.) above sea level (ASL) (96.0 kPa). To maintain proper engine operation and emission compliance above 330 m (1100 ft.) ASL the carburetor <u>may</u> need to be adjusted by an authorized service dealer.

# NOTICE

If the engine is adjusted for operation above 330 m (1100 ft.) ASL, the carburetor must be re-adjusted when operating the engine below 330 m (1100 ft.) ASL, otherwise severe engine damage may result.

Note: Every unit is run at the factory and the carburetor is set in compliance with emission regulations.
Carburetor adjustments, other than idle speed, must be performed by an authorized dealer.

 Check idle speed and reset if necessary. If a tachometer is available, idle speed screw (A) should be set to the specifications found on "Specifications" page of this manual. Turn idle screw (A)




clockwise to increase idle speed; counterclockwise to decrease idle speed.

#### **Drive Shaft Lubrication**

#### Level 1.

Parts Required: Lithium Based Grease.

- Loosen two (2) screws (A) and remove center locating screw (B). Pull gear box and shield from drive shaft housing.
- Pull flexible cable from the drive shaft housing, wipe clean and re-coat with a thin coating (15 ml [½ oz.]) of grease.
- Slide the flexible cable back in the drive housing. DO NOT get dirt on the flex cable.
- 4. Install the gear housing and shield assembly.
- 5. Tighten screws securely.



#### **Blade Replacement/Lubrication**

Level 1.


Parts Required: Blade, new split pin, lithium Based Grease

Note: Grease gear case every 15-25 hours of use. Replace blade when carbide tips have worn away.


- 1. Shut engine off. Disconnect spark plug lead from spark plug.
- 2. Remove split pin (A).
- 3. Rotate blade until holes in inner blade adapter (B) and gear box align. Insert locking tool to lock PTO shaft (C).

Note: Blade nut (D) is left hand thread.

4. Remove blade left hand threaded nut (D) in a clockwise direction using T-wrench. Remove outer fixing plate (E), blade (F) and inner fixing plate (B).



- Clean all loose debris from gear box. 5.
- 6. Remove plug (G) and check level of grease. Grease should fill gear case to bottom of grease plug hole.
- Add grease if necessary using 7. squeeze-type tube. Do not use high pressure grease gun. DO NOT over-fill.




#### TROUBLESHOOTING

- 8. Install inner blade adapter (B) onto PTO shaft (C).
- Install and center new blade (F) onto inner fixing plate (B), with longest side toward shield.
- Install outer fixing plate (E) and nut (D). Tighten left hand threaded nut (D) firmly, counterclockwise.

Note: Never reuse old split pin.

11. Install new split pin (A) to secure nut.



#### **TROUBLESHOOTING**

	ENGINE PROBLEM TROUBLESHOOTING CHART				
Problem	Check	Status	Cause	Remedy	
	Fuel at carburetor	No fuel at carburetor	Fuel strainer or fuel line obstructed	Clean or replace See your Echo dealer	
		No fuel at cylinder	Carburetor	See your Echo dealer	
Engine starts hard or Engine does not	Fuel at cylinder	Muffler wet with fuel	Fuel mixture too rich	OPEN choke Clean or replace air filter Adjust carburetor See your Echo dealer	
start	Spark at end of plug wire	No spark	Stop switch OFF - Electrical problem - Inter- lock switch	Turn switch to ON See your Echo dealer	
	Spark at plug	No spark	Incorrect gap - Covered with carbon - Fouled with fuel - Plug defective	Adjust to 0.65mm (0.026 in.) Clean or replace plug	

	ENGINE PROBLEM TROUBLESHOOTING CHART				
Problem	Check	Status	Cause	Remedy	
	Air filter	Air filter dirty	Normal wear	Clean or replace	
Engine	Fuel filter	Fuel filter dirty	Contaminants or residue in fuel	Replace filter or replace fuel	
runs, but dies	Fuel vent	Fuel vent plugged	Contaminated fuel	Clean or replace	
or	Spark plug	Plug dirty or worn	Normal wear	Clean and adjust or replace	
Engine does not	Carburetor	Improper adjustment	Vibration	Adjust	
acceler- ate properly	Cooling system	Cooling system dirty or plugged	Extended oper- ation in dirty or dusty locations	Clean	
	Spark arrestor screen	Spark arres- tor screen plugged	Normal wear	Replace	
Engine does not crank	N/A	N/A	Internal engine problem	See your Echo dealer	

# DANGER

Fuel vapors are extremely flammable and may cause fire and/or explosion. Never test for ignition spark by grounding spark plug near cylinder plug hole, otherwise serious personal injury may result.

#### **STORAGE**

# WARNING

During operation the muffler or catalytic muffler and surrounding cover become hot. Always keep exhaust area clear of flammable debris during transportation or when storing, otherwise serious property damage or personal injury may result.



STORAGE BRD-2620

#### Long Term Storage (Over 30 Days)

Do not store your unit for a prolonged period of time (30 days or longer) without performing protective storage maintenance which includes the following:

1. Store unit in a dry, dust free place, out of the reach of children.

# A DANGER

# Do not store in enclosure where fuel fumes may accumulate or reach an open flame or spark.

- 2. Place the stop switch in the "OFF" position.
- Remove accumulation of grease, oil, dirt and debris from exterior of unit.
- 4. Perform all periodic lubrication and services that are required.
- 5. Tighten all the screws and nuts.
- 6. Drain fuel tank completely. Press purge bulb 6-7 times to remove remaining fuel from carburetor then drain the tank again. Close choke, start and run the engine until it stops due to lack of fuel.
- 7. Allow engine to cool. Remove the spark plug lead from the spark plug. Remove the spark plug. Pour 7 cc (0.25 oz.) of fresh, clean, two-stroke engine oil into the cylinder through the spark plug hole.
- 8. Pull the recoil starter handle 2-3 times to distribute the oil inside the engine.
- Observe the piston location through the spark plug hole. Pull the recoil handle slowly until the piston reaches the top of its travel and leave it there.
- 10. Install the spark plug. Connect the spark plug lead to the spark plug.



### **SPECIFICATIONS**

MODEL	BRD-2620
Length	1797 mm (70.7 in.)
Width	301 mm (11.9 in.)
Height	328 mm (12.9in.)
Weight (dry) with dry head	8.06 kg (17.7 lb.)
Engine Type	Air cooled, two-stroke, single cylinder gasoline engine
Bore	34.0 mm (1.34 in.)
Stroke	28 mm (1.1 in.)
Displacement	25.4 cc (1.55 cu. in.)
Exhaust	Spark arrestor muffler or spark arrestor muffler with catalyst
Carburetor	Diaphragm w/purge pump
Ignition System	Flywheel magneto, capacitor discharge ignition type
Spark Plug	NGK CMR7H - Gap 0.6 - 0.7 mm (0.024 - 0.026 in.)
Fuel	Mixed (Gasoline and Two-stroke Oil)
Fuel/Oil Ratio	50 : 1 Power Blend X <sup>TM</sup> or ECHO Red Armor <sup>®</sup> ISO-L-EGD (ISO/CD 13738) and J.A.S.O. M345- <u>FD</u> , two-stroke, air-cooled engine oil.
Gasoline	Use 89 Octane unleaded. Do not use fuel containing methyl alcohol, more than 10% ethyl alcohol or 15% MTBE. Do not use alternative fuels such as E-15 or E-85.
Oil	Power Blend X <sup>TM</sup> or ECHO Red Armor <sup>®</sup> Premium Universal 2-Stroke Oil
Fuel Tank Capacity	0.61 lit. (20.6 US fl. oz.)
Starter System	Automatic Rewind Starter
Clutch	Centrifugal Type
Drive Shaft	6.35 mm (1/4 in.) flexible shaft
Gear Case Ratio	2.07:1
Rotating Direction	Counter Clockwise; viewed from right side
Standard Cutter Head	Claw-style cutter (six carbride tips)
Optional Cutter Head	2-tooth edger blade
Handle	Front Cushioned D- loop, Rear - Grip
Vibration Reduction	Rubber cushion

MODEL	BRD-2620
Idle Speed	3,000 RPM
Clutch Engagement Speed	3,800 RPM
Wide Open Throttle Speed (W.O.T.)	11,200 RPMS

#### PRODUCT REGISTRATION

#### Thank you for choosing ECHO Power Equipment

Please go to <a href="http://www.echo-usa.com/Warranty/Register-Your-ECHO">http://www.echo-usa.com/Warranty/Register-Your-ECHO</a> to register your new product on-line. It's **FAST** and **EASY**! NOTE: your information will never be sold or misused by ECHO, Inc. Registering your purchase enables us to contact you in the unlikely event of a service update or product recall, and verifies your ownership for warranty consideration.

If you do not have access to the Internet, you can complete the form below and mail to:

ECHO Inc., Product Registration, PO Box 1139, Lake Zurich IL 60047.

02-2012

X7572270206

WWW ECHO-USA COM

# $/\!\!/\!\!/$ Product registration card : Tarjeta de registro : carte d'enregistrement du produit

Please Print : Por Favor Enscriba Con Letra De Molde : En Lettre Carré S.V.P.

ahorre una estampilla! Le alertaran sobre actualizaciones del producto y/o se le enviara información sobre los nuevos pro-ductos ECHO y las ofertas especiales. Simplemente visite: Registrese en la pagina web www echo DPCIÓN POR INTERNET:

	Confidential: Information provided will not be shared or sold	
usaicolli		i

OPTION EN LIGNE: Enregistrer en ligne et épargner un finnnel Vous serez informé sur les nouveaux produits ECHO et les mises à jour de produit ainsi que les offres spéciales. Simplement visitez le: www.echo-usa.com

Purchaser's Name : Nombre del Comprador : Nom de l'acheteur	ador : Nom de l'aci	heteur	Trimazy use of root: Lightonestonal Lightonestonal Lightonestonal Lightonestonal Countries and Aquiller Usep principal : Lightonestonel Countries
			Do you wish to receive periodic ECHO product information and special offers
Address : Dirección : Adresse			by e-mail? ☐ Yes ☐ No
			¿Desea usted recibir información periódica y ofertas especiales por correo electronico sobre el producto ECHO? $\square$ I Ve $\alpha$ $\square$ No $\square$ No recibir periodico ECHO?
City : Ciudad : Ville	State : Estado :	Zip Code : Código Postal : Code Postal	ECHO et les offres spéciales par courrier électronique ?   Oui   Non
	Province		Did you visit the ECHO website before purchasing your product?  ☐ Yes ☐ No
E-Mail Address : Dirección De Correo Electrónico : Courrier Électronique	Electrónico : Courr	ier Électronique	Visitó usted la pagina web ECHO antes de comprar su producto? □ Sí □ No
			Avez-vous visité le site d'ECHO avant de procurer votre produit?  Oui □ Non
Phone Number : Número De Teléfono : Téléphone		Date of Purchase : Fecha de la Compra : Date de l'achat	What factor(s) most influenced your purchase?
			Prior Experience
Where Purchased : Nombre del Almacén donde fue Comprado : Lieu d'achat	in donde fue Compi	ado : Lieu d'achat	nfluenció más en su compr Precio
			Experiencia Anterior Marca
Model Number: Numero del Modelo: No	lo. de modéle Seri	Model Number : Numero del Modelo: No. de modéle Serial Number : Numero de Serie : No. de série	cteurs) vous a influencé le p
			ance Prix
Registering your purchase enables us to contact y	you in the unlikely even	Registering your purchase enables us to contact you in the unlikely event of a service update or product recall and verifies your	☐ Flabilite ☐ Experience ☐ Qualite ☐ Ami/Famille ☐ Marque ☐ Garantie

Registering vou purchase enables is to contact your in he unlikely enterful of asservice duptide or productive and and verifies your ownership in the event of loss. El legisters is compra nos permite estar en confacto con usted en caso de cualquier evento como el aviso de liempo de servicio o la revocación del producto y verificación de propiedad en caso de cualquier evento como el aviso de liempo de servicio o la revocación del producto y verificación de propiedad en rasso de robo o parcidad. Le mengalement de votre acha non servicio per permitan de voca contacter deficie es can improducte de modificacions de instructions deministen ou der appe del produit et verifier que vous eles se proprietar en case de viol ude perte.

ECHO INC., 400 Oakwood Rd., Lake Zurich, IL 60047 1.800,432,ECHO

U05715001001 - U05715999999



**ECHO, INCORPORATED** 400 Oakwood Road Lake Zurich, IL 60047

www.echo-usa.com