

## Xeri-Bubblers™

Ideal for Shrub Plantings, Trees, Containers, and Flower Beds

### Features







- Adjust flow and radius by turning outer cap
- Clean by completely unscrewing cap from base unit
- Three convenient installation connections available for design flexibility: 10-32 self-tapping thread, 1/4" barb, and 5" spike

### Operating Range

- SXB Series flow: 0 to 13 gph (0 to 49.21 l/h)
- UXB Series flow: 0 to 35 gph (0 to 132.48 l/h)
- Pressure: 15 to 30 psi (1.0 to 2.1 bar)

### Models

- SXB-180-1032: Half-circle, 5 streams, 10-32 thread
- SXB-180-025: Half-circle, 5 streams, 1/4" barb
- SXB-180-SPYK: Half-circle, 5 streams, 5" spike; includes barb x barb coupler
- SXB-360-1032: Full-circle, 8 streams, 10-32 thread
- SXB-360-025: Full-circle, 8 streams, 1/4" barb
- SXB-360-SPYK: Full-circle, 8 streams, 5" spike includes barb x barb coupler
- UXB-360-1032: Full-circle, umbrella, 10-32 thread
- UXB-360-025: Full-circle, umbrella, 1/4" barb
- UXB-360-SPYK: Full-circle, umbrella, 5" spike includes barb x barb coupler



SXB-180-025 SXB-360-025 UXB-360-025  
BARB



SXB-180-1032 SXB-360-1032 UXB-360-1032  
10-32 threads



SXB-180-SPYK SXB-360-SPYK UXB-360-SPYK  
"SPIKE"

### How To Specify

#### SXB - 180 - 1032

Connection  
1032: 10-32 self-tapping thread  
025: 1/4" barb  
SPYK: 5" spike

Pattern  
180 = Half circle  
360 = Full-circle

Model  
SXB: Stream Bubbler  
UXB: Umbrella Bubbler