




## **CS-400 CHAIN SAW**

Increased Power, Professional Features and the Best Value in its Class







- 40.2 cc Power Boost Vortex<sup>™</sup> Engine for Plenty of Cutting Power
- i-30<sup>™</sup> Technology Reduces Starting Effort by 30%
- G-Force Engine Air Pre-Cleaner™ Spins Out Dirt for a Longer-Lasting Engine
- Automotive-style Air Filter Provides Exceptional Filtration
- Computerized Ignition Advance Automatically Adjusts Engine Timing
- Cold Weather By-Pass for Easy Winter Starting
- Vibration Reduction System for Operator Comfort





The G-Force Engine Air Pre-Cleaner™ increases engine life by spinning out dirt prior to filtration.



The rear-mounted, automotive-style air filter features tool-less removal and exceptional filtration.



The i-30<sup>™</sup> starting system reduces starting effort by 30%.

Model	Engine Displacement (cc)	Engine Displacement (cu in)	Carburetor	Pro-Fire® Electronic Ignition	Ignition Advance	Oiling System	Inertia-type Chain Brake	Std. Bar Length (in)	Opt. Bar Length (in)	Fuel Capacity (fl oz)	Oil Capacity (fl oz)	Dry Weight* (lb)
CS-306	30.1	1.84	Diaphragm*	Standard	N.A.	Adjustable Automatic	Standard	14	12	9.3	5.4	7.5
CS-330T	32.6	1.99	Diaphragm	Standard	Standard	Adjustable Automatic	Standard	14	12, 16	10.5	9.8	8.1
CS-341	30.1	1.84	Diaphragm*	Standard	Standard	Adjustable Automatic	Standard	14	12, 16	8.5	5.0	7.8
CS-360T	36.3	2.20	Diaphragm	Standard	Standard	Adjustable Automatic	Standard	16	12, 14	10.5	9.8	8.1
CS-370	36.3	2.20	Diaphragm*	Standard	Digital	Adjustable Automatic	Standard	16	14, 18	13.9	9.5	10.0
CS-400	40.2	2.46	Diaphragm*	Standard	Digital	Adjustable Automatic	Standard	18	16	13.9	9.5	10.1
CS-440	45.0	2.75	Diaphragm	Standard	Standard	Adjustable Automatic	Standard	18	16	15.9	9.5	10.5
CS-520	50.1	3.06	Diaphragm	Standard	Standard	Adjustable Automatic	Standard	20	16, 18	20.3	9.5	10.8
CS-670	66.7	4.07	Diaphragm	Standard	Standard	Adjustable Automatic	Standard	24	16, 20, 27	22.5	13.0	14.3
CS-8000	80.7	4.93	Diaphragm	Standard	Standard	Adjustable Automatic	Standard	24	20, 27, 32, 36	28.9	14.1	16.5

\* With purge pump. \*\* Without bar and chain.