FXLuminaire



Incandescent Path Lights


Milled from extra heavy gauge copper and brass, this petite luminaire is perfect, whether you're specifying for a resort or a backyard. The simple geometry of the DL blends into the environment effortlessly and the beam spread of the DL provides maximum projection with minimum glare. This model is perfect for coastal exposures or areas where irrigation water contains high levels of minerals or caustic salts.

DL: Path Light



The Timeless Beauty of Copper

The appeal of a copper finish lies in its organic quality and natural mottled earthtones that develop over time. Although we ship the copper path lights in a bright condition, they will quickly transform to a penny brown (moss-green brown or a bluegreen patina by the ocean).



INCANDESCENT

ORDERING INFORMATION

DL: Path Light

FACTORY INSTALLED OPTIONS: Order 1 + 2 + 3 + 4						METALS			
Step	Description	Code						CU = Copper	
1	FIXTURE	DL							
2	LAMP	10, 15 (10,000 Hr Xenon), 20	NP = Nickel Plate*						
3	RISER OPTIONS	8R, 12R, 18R, 24R, 36R						POWDER COAT	
4	FINISH	CU, NP, WG, FW, AL, BZ, DG			WG = White Gloss				
EXAMPLE: DL-20-12R-CU = DL - 20W Xenon Lamp - 12" Riser - Copper Finish									
								FW = Flat White	
FIELD	INSTALLED OPT	ONS: Order Individually							
Mount	ts							AL = Almond	
Long S	ilot Spike (25001584	0000) 2.5" x 10" Included ►				ω		BZ = Bronze Metallic	
Super Slot Spike (753900) 2" x 10"			7	V	V			DG = Desert Granite	
SuperJ-Box (<i>SJ-XX**</i>) 2.5" x 12"			- U -						
Post N	lount (PM-XX**) 2.5	" x 13"		V	•			WI = Weathered Iron	
			Long Slot	Super Slot	Super J-Box XX**	Post Mount XX**		VF = Verde Speckle	
EVAM	DI E. CL DC - Super	J-Box - Natural Brass Finish	Spike	Spike	J-DUX XX	~~~~		SB = Sedona Brown	

PHOTOMETRICS:

Spacing for minimum footcandle illumination on level ground.	Circular light pattern	Footcandl	Footcandles:		
CARDINAL CONTRACTOR	14'	DISTANCE	CA-10	CA-20	
A	12'	2'	1.5	3	
		4'	.31	.88	
	10'	6'	.14	.33	
	8'	8'	.08	.14	
	6'	10'	.03	.08	
	4'	12'	.01	.03	
Note: 1fc for commercial projects	2'	14'	0	.01	
.3fc for residential projects					

For conversion to lumens: Multiply footcandles x 10. See FX glossary for a full description of fc and lumens.

The DL includes choice of lamp, riser size, finish, and a Long Slot Spike.

FB = Flat Black

Note: Only the copper portions of the path lights are powder coated. The brass pieces remain natural.

* May require longer lead time ** Denotes finish code

