

# SUPER BLUE FLEX™



**W**ith a strong product heritage and proven years of performance, this tubing is designed to simplify spray head installation making it ideal for challenging landscapes and hard-to-reach areas.

## KEY FEATURES & BENEFITS

### **DURABLE PREMIUM GRADE LINEAR, LOW-DENSITY POLYETHYLENE**

Achieves higher psi strength and performance over time vs. competitive products

### **HIGHLY FLEXIBLE**

For ease of use

### **EASILY UNWINDS FROM CENTER OF COIL**

For added convenience

## ADDED FEATURES

- Coils are shrink-wrapped for ease of handling
- Low-density design protects tubing from landscape
- Five-year warranty

## SPECIFICATIONS

- Maximum working pressure: 120 psi at 100° F
- Inside diameter: .49"
- Outside diameter: .68"
- Wall thickness: .095"
- Nominal size: .50"
- Coil size: 100'



EHF1295-010-D  
Flex pipe ½" 100' coil

# BLUE FLEX ASSEMBLIES



Available in two popular lengths, these sturdy, flexible assemblies protect spray head risers and pipes from breaking when hit or run over by equipment.

## KEY FEATURES & BENEFITS

### STANDARD 8-INCH LENGTH

Provides greater flexibility and strength than competitors' 6-inch models

### PRE-ASSEMBLED

Saves time and money

### TAPE-FREE FITTING INSTALLATION

Makes installation faster and easier

### FEWER THREADED JOINTS

Minimizes leaks

## ADDED FEATURES

- Easily adjusts sprinkler head to required grade
- Compatible for below-grade installation
- Five-year warranty

## SPECIFICATIONS

- Operating pressure range: 25-75 psi
- Maximum operating pressure: 85 psi
- Pressure-tested to 120 psi

## MODELS

Model	Description
B-FLEX8-05	8" x 1/2" male x 1/2" street ell
B-FLEX12-05	12" x 1/2" male x 1/2" street ell
B-FLEX8-0575	8" x 1/2" male x 3/4" street ell
B-FLEX12-0575	12" x 1/2" male x 3/4" street ell

## SPECIFYING INFORMATION

MODEL	LENGTH	FITTING
B-FLEX Blue Flex swing assembly	8 - 8" 12 - 12"	05 - 1/2" male x 1/2" street ell 0575 - 1/2" male x 3/4" street ell
Example: A 12" swing assembly with 3/4" street elbow = <b>B-FLEX12-0575</b>		

## SUPER BLUE FLEX ASSEMBLY FRICTION LOSS DATA

MODELS	GPM FLOW						
	1	2	3	4	5	6	7
B-FLEX8-05	0.04	0.11	0.27	0.47	0.85	1.22	1.78
B-FLEX12-05	0.05	0.15	0.36	0.62	1.13	1.62	2.37
B-FLEX8-0575	0.05	0.14	0.31	0.60	1.07	1.65	2.29
B-FLEX12-0575	0.06	0.18	0.41	0.80	1.42	2.20	3.05

# BLUE FLEX FITTINGS



## ADDED FEATURES

- Five-year warranty

## MODELS

Model	Description
• FFP-T	1/2" barbed tee
• FFP-75EM	3/4" male x 1/2" barb elbow
• FFP-50EM	1/2" male x 1/2" barb elbow
• FFP-C	1/2" barbed coupler