
FOUNTAIN BASINS

access pump chambers and external flo



MODELS:



Model: FB2400 Dimensions: 24"L x 24"W x 10"H Max Pump Flow: 750 gph Plumbing Size: Up to 3/4" Capacity: 20 Gallons Supports Up To: 200 lbs. Warranty: Lifetime



Model: FB3200 Dimensions: 32"W x 13"H Max Pump Flow: 2,000 gph Plumbing Size: (3) 3/4" or (1) 1" hose Capacity: 32 Gallons Supports Up To: 400 lbs. Warranty: Lifetime



Model: FB4600 Dimensions: 46"W x 13"H Max Pump Flow: 4,000 gph Plumbing Size: (3) 34" or (1) 11/2" hose Capacity: 67 Gallons Supports Up To: 1,200 lbs. Warranty: Lifetime

- 1. One-piece construction provides exceptional strength.
- 2. Built-in channels simplify installation, allowing the plumbing to be run on top of the basin.
- 3. Molded cones support the top panel.
- 4. Recessed pocket accepts Triton 3-Way Diverter (FB4600 only). Adjusting the water flow to multiple pieces has never been easier.
- 5. 11/2" conduit recesses allow for clean installation in surrounding masonry without notching.
- 6. Flat panel for optional AF1000 Auto Fill installation.



FOUNTAIN ACCESSORIES



pipe the same height as your fountain and water!





Model: TR3WAY Dimensions: 53/8"L x 41/2"W x 21/8"H Inlet: 11/2" FIPT Outlet: (3) 3/4" Insert Includes: (2) removable "T" handles Warranty: 1 year

The Triton 3-Way Diverter is the only manifold designed exclusively for Pond-free fountain installations. The 11/2" inlet allows unrestricted flow into the manifold, delivering the maximum possible volume to all three of the $\mbox{\em 3}\!\!\!4''$ outlets. True 'ball' style valves with removable handles enable independent flow adjustment of each outlet. The compact design makes it a perfect fit for installation in all Pump Vaults and Fountain Basins.





Part No. FBKIT1

For Use With: FP200 - 500 & MD250 - 750

- Single ball valve
- 6' of ¾" diameter kink-free hose
- (1) standpipe sealant strip
 ¾" insert x ¾" socket fitting
- 1½" cord stopper for conduit sleeve

Warranty: 1 year



Part No. FBKIT3

For Use With: MD1000 - 2000, TW1200 - 2400 & TT1500 - 3000

- Triton 3-Way Diverter
- 20' of ¾" diameter kink-free hose
- (3) standpipe sealant strips
- (3) 3/4" insert x 3/4" socket fittings • (2) 11/2" cord stoppers for conduit sleeves

Warranty: 1 year

Model FB4600 shown 39