



Ask Any Pro!™

225 SERIES TRIMMERS

Powerful Performance in a New Look



5 year consumer, 1 year commercial and 90 day rental warranty.

TRIMMERS



- 21.2cc Power Boost Vortex™ Engine Provides Plenty of Trimming Power
- i-30™ Technology Reduces Starting Effort by 30%
- Built-in Arm Rest and Spark Plug Protector for Added Comfort and Durability
- Commercial-Duty Air Filtration System Provides Long Engine Life
- Available in a Variety of Configurations

www.echo-usa.com

225 SERIES TRIMMERS



Ask Any Pro!™

The 225 Series of Trimmers features a whole new look to the 21.2cc engine and is available in a variety of configurations: Standard with an i-30™ starter (SRM-225 and GT-225), with an i-75™ starter (SRM-225i and GT-225i), split boom (SRM-225SB), or "U"-handle (SRM-225U). Common features to all include: a 21.2cc Power Boost Vortex™ engine for plenty of trimming power, i-30™ technology to reduce starting effort by 30%, a built-in arm rest and spark plug protector for added comfort and durability, and a commercial-duty air filtration system to provide long engine life.



5 year consumer, 1 year commercial and 90 day rental warranty.



A powerful, smooth-running 21.2cc Power Boost Vortex™ engine provides plenty of trimming power.



Rubber over molded grip provides comfortable all day operation.



The U Turn™ trimmer head, equipped with .095" diameter Cross-Fire® line, reloads in seconds (available on SRM series only).



TRIMMER SPECIFICATIONS

* Includes cutting head, excludes harness ** Without cutting head, includes shield

| Model | Engine Displacement (cc) | Carburetor (w/Purge Pump) | Fuel Capacity (fl. oz.) | Shaft Length (in) | Shaft Type | Starting System | Cutting Head | Cutting Swath (in) | Shield | Drive Shaft | Nylon Line (in dia) | Dry Weight (lb)* | Dry Weight (lb)** |
|-----------|--------------------------|---------------------------|-------------------------|-------------------|-------------|-----------------|----------------|--------------------|----------|---------------|---------------------|------------------|-------------------|
| GT-200R | 21.2 | Rotary | 15.2 | 48 | Curved | i-30™ | Rapid-Loader™ | 16 | Std. GT | 4-Layer Cable | .080 Cross-Fire® | 9.3 | 8.8 |
| GT-200i | 21.2 | Rotary | 15.2 | 48 | Curved | i-75™ | Rapid-Loader™ | 16 | Std. GT | 4-Layer Cable | .080 Cross-Fire® | 9.6 | 8.8 |
| GT-225 | 21.2 | Rotary | 14.9 | 48 | Curved | i-30™ | Rapid-Loader™ | 16 | Std. GT | 4-Layer Cable | .080 Cross-Fire® | 10.2 | 9.7 |
| GT-225i | 21.2 | Rotary | 14.9 | 48 | Curved | i-75™ | Rapid-Loader™ | 16 | Std. GT | 4-Layer Cable | .080 Cross-Fire® | 10.5 | 9.7 |
| GT-251 | 25.4 | Diaphragm | 14.2 | 52 | Curved | i-30™ | Rapid-Loader™ | 16 | Std. GT | Flexible | .080 Cross-Fire® | 10.4 | 9.9 |
| SRM-210 | 21.2 | Rotary | 15.2 | 59 | Straight | i-30™ | ECHOMATIC Pro™ | 17 | Std. SRM | 4-Layer Cable | .095 Cross-Fire® | 11.4 | 10.6 |
| SRM-210i | 21.2 | Rotary | 15.2 | 59 | Straight | i-75™ | Rapid-Loader™ | 17 | Std. SRM | 4-Layer Cable | .095 Cross-Fire® | 11.6 | 10.9 |
| SRM-210SB | 21.2 | Rotary | 15.2 | 59 | Split Shaft | i-30™ | ECHOMATIC Pro™ | 17 | Std. SRM | 4-Layer Cable | .095 Cross-Fire® | 11.9 | 11.1 |
| SRM-210U | 21.2 | Rotary | 15.2 | 59 | Straight | Standard | ECHOMATIC Pro™ | 17 | Std. SRM | 4-Layer Cable | .095 Cross-Fire® | 12.9 | 12.1 |
| SRM-225 | 21.2 | Rotary | 14.9 | 59 | Straight | i-30™ | U Turn™ | 17 | Std. SRM | 4-Layer Cable | .095 Cross-Fire® | 12.1 | 11.3 |
| SRM-225i | 21.2 | Rotary | 14.9 | 59 | Straight | i-75™ | U Turn™ | 17 | Std. SRM | 4-Layer Cable | .095 Cross-Fire® | 12.4 | 11.6 |
| SRM-225SB | 21.2 | Rotary | 14.9 | 59 | Split Shaft | i-30™ | U Turn™ | 17 | Std. SRM | 4-Layer Cable | .095 Cross-Fire® | 12.9 | 12.1 |
| SRM-225U | 21.2 | Rotary | 14.9 | 59 | Straight | i-30™ | U Turn™ | 17 | Std. SRM | 4-Layer Cable | .095 Cross-Fire® | 13.6 | 12.8 |
| SRM-230 | 22.8 | Rotary | 19.6 | 59 | Straight | Standard | ECHOMATIC Pro™ | 17 | Std. SRM | 4-Layer Cable | .095 Cross-Fire® | 12.2 | 11.4 |
| SRM-230S | 22.8 | Rotary | 19.6 | 59 | Straight | Standard | ECHOMATIC Pro™ | 17 | Std. SRM | Steel | .095 Cross-Fire® | 12.0 | 11.2 |
| SRM-230U | 22.8 | Rotary | 19.6 | 59 | Straight | Standard | ECHOMATIC Pro™ | 17 | Std. SRM | Steel | .095 Cross-Fire® | 13.2 | 12.4 |
| SRM-251 | 25.4 | Diaphragm | 14.2 | 59 | Straight | i-30™ | ECHOMATIC Pro™ | 17 | Std. SRM | Flexible | .095 Cross-Fire® | 11.3 | 10.5 |
| SRM-260 | 25.4 | Rotary | 19.6 | 59 | Straight | Standard | ECHOMATIC Pro™ | 17 | Std. SRM | 4-Layer Cable | .095 Cross-Fire® | 12.5 | 11.1 |
| SRM-260S | 25.4 | Rotary | 19.6 | 59 | Straight | Standard | ECHOMATIC Pro™ | 17 | Std. SRM | Steel | .095 Cross-Fire® | 12 | 10.7 |
| SRM-261T | 25.4 | Rotary | 19.6 | 59 | Straight | Standard | ECHOMATIC | 17 | Std. SRM | 4-Layer Cable | .095 Cross-Fire® | 12.8 | 10.9 |
| SRM-265 | 25.4 | Diaphragm | 16.9 | 59 | Straight | i-30™ | ECHOMATIC Pro™ | 17 | Std. SRM | 4-Layer Cable | .095 Cross-Fire® | 13.4 | 12.3 |
| SRM-265S | 25.4 | Diaphragm | 16.9 | 59 | Straight | i-30™ | ECHOMATIC Pro™ | 17 | Std. SRM | Steel | .095 Cross-Fire® | 12.9 | 12.1 |
| SRM-265T | 25.4 | Diaphragm | 16.9 | 59 | Straight | i-30™ | ECHOMATIC Pro™ | 17 | Std. SRM | 4-Layer Cable | .095 Cross-Fire® | 13.7 | 12.7 |
| SRM-265U | 25.4 | Diaphragm | 16.9 | 59 | Straight | i-30™ | ECHOMATIC Pro™ | 17 | Std. SRM | 4-Layer Cable | .095 Cross-Fire® | 14.4 | 13.5 |
| SRM-280 | 28.1 | Diaphragm | 21.6 | 59 | Straight | Standard | ECHOMATIC Pro™ | 17 | Std. SRM | 4-Layer Cable | .095 Cross-Fire® | 13.5 | 12.6 |
| SRM-280S | 28.1 | Diaphragm | 21.6 | 59 | Straight | Standard | ECHOMATIC Pro™ | 17 | Std. SRM | Steel | .095 Cross-Fire® | 13.4 | 12.5 |
| SRM-280T | 28.1 | Diaphragm | 21.6 | 59 | Straight | Standard | ECHOMATIC Pro™ | 17 | Std. SRM | 4-Layer Cable | .095 Cross-Fire® | 13.6 | 12.7 |
| SRM-280U | 28.1 | Diaphragm | 21.6 | 59 | Straight | Standard | ECHOMATIC Pro™ | 17 | Std. SRM | 4-Layer Cable | .095 Cross-Fire® | 14.5 | 13.6 |