

# HUNTER DRIPLINE

BUILT FOR RELIABILITY AND EFFICIENCY



Hunter Dripline (HDL) is Hunter's solution for dense plantings and gardens all around the world. With built-in check valve emitters, HDL delivers water slowly and evenly for consistent distribution. It is primarily used at grade, but can also be used subsurface when required.

- Three pressure-compensating options: HDL-PC (standard), HDL-CV (includes check valve), HDL-R (reclaimed applications)
- Pressure-compensating emitters
- Color-coded stripes to identify flow
- Emitter spacing at 12", 18", 24"
- Tubing diameter: 0.660" (OD) x 0.560" (ID). Wall thickness 0.050"
- Strong UV resistance
- Stretch-wrapped 100', 250', and 500' coils make handling easy and efficient



**HDL**  
100', 250', 500', and 1,000' lengths

## PRODUCT SPECIFICATIONS

<b>Flow</b>	0.4, 0.6, or 0.9 GPH
<b>Working Pressure</b>	10 to 60 PSI
<b>Minimum Filtration</b>	120 mesh
<b>Warranty</b>	5 years (plus 2 additional years for environmental stress cracking)

- Available without emitters (blank)
- Emitter inlet filtration and extra-wide flow labyrinth to prevent clogging
- Full-size outlet pool and raised wall inhibit debris and roots from entering the emitter
- Check valves keep the line charged up to 6' and prevent low-point drainage (HDL-CV only)
- Warranty period: 5 years (2 additional years for environmental stress cracking)

