

FILTER REGULATOR

System: **Regulation and Filtration, All in One Component**

FEATURES

- Factory-assembled and water-tested
- Highest quality components (stainless steel filter screen, standard flush cap, top-of-the-line regulator)
- Wide flow range to cover most micro irrigation applications
- Warranty period: 2 years

HFR-100-075, HFR-075

- Pressure regulation: 25 or 40 PSI
- Flow: 0.5 to 15 GPM (30 to 900 GPH)
- Operating pressure: 20 to 120 PSI
- Operating temperature: up to 120° F
- 150 mesh; 100 microns stainless steel screen



HFR-100-075-25

HFR-100-075-40

Height: 7"
Width: 2¾"
Length: 6¼"
1" inlet x ¾" outlet



HFR-075-25

HFR-075-40

Height: 7"
Width: 2¾"
Length: 6¼"
¾" inlet x ¾" outlet



HY-100, HY-100-75,

HY-075

Height: 6"
Width: 3"
Length: 5"

HY-151

Height: 11"
Width: 4.5"
Length: 8"

HUNTER FILTER REGULATOR

Model	Description
HFR-075-25	¾" inlet x ¾" outlet, regulated at 25 PSI
HFR-075-40	¾" inlet x ¾" outlet, regulated at 40 PSI
HFR-100-075-25	1" inlet x ¾" outlet, regulated at 25 PSI
HFR-100-075-40	1" inlet x ¾" outlet, regulated at 40 PSI

HUNTER Y-FILTER

- Filter HY-100 1" Male NPT
- Filter HY-100-075 1" Male NPT inlet x ¾" Male outlet
- Filter HY-075 ¾" Male
 - Filter only (no regulation)
 - Extra large 150 mesh; 100 microns stainless steel screen
- Filter HY-151 1½" Male NPT
 - Filter only (no regulation)
 - Extra large 120 mesh; 125 microns stainless steel screen
- Flow: Up to 60 GPM
- Maximum pressure: 120 PSI

MICRO