

I-20

Radius: **17' to 46'**
 Flow: **0.36 to 14.8 GPM**
 Inlet: **¾"**

FEATURES

- Models plastic riser: Shrub, 4", 6", 12"
 - Models stainless steel riser: 4", 6"
 - Arc setting: 50° to 360°
 - Factory installed rubber cover
 - Through-the-top arc adjustment
 - QuickCheck™ arc mechanism
 - Water lubricated gear-drive
 - Nozzle choices: 34
 - Nozzle racks: 1.5 to 8.0 Blue, 2.0 to 4.5 Low Angle Gray, 0.50 to 3.0 Short Radius Black, 6.0 to 13.0 Green, MPR-25, MPR-30, MPR-35
 - Warranty period: 5 years
- ▶ Automatic arc return
 - ▶ Non-strippable drive
 - ▶ Part- and full-circle in one model
 - ▶ Headed and slotted set screw
 - ▶ FloStop® control
 - ▶ Reclaimed water ID
 - ▶ Stainless steel riser
 - ▶ Drain check valve (up to 10' of elevation)

OPERATING SPECIFICATIONS

- Radius: 17' to 46'
- Flow: 0.36 to 14.8 GPM
- Recommended pressure range: 25 to 70 PSI
- Operating pressure range: 20 to 100 PSI
- Precipitation rates: 0.4 in/hr approximately
- Nozzle trajectory: Std = 25°, Low Angle = 13°

▶ = *Advanced Feature descriptions on page 30*



I-20 Reclaimed
 Available as a factory installed option on all models

I-20 (PLASTIC) – SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

| 1 Model | 2 Standard Features | 3 Feature Options | 4 Nozzle Options |
|---|---|--|---|
| I-20-00 = Shrub I-20-04 = 4" Pop-up I-20-06 = 6" Pop-up I-20-12 = 12" Pop-up | Adjustable arc, plastic riser, check valve, 8 standard nozzles, and 4 low-angle nozzles | (blank) = No option NCV = Without check valve (only available on 4" model) R = Drain check valve and reclaimed water ID | Blue 1.5 - 8.0 Gray Low Angle Black Short Radius Green High Flow MPR-25-Q, T, H, F MPR-30-Q, T, H, F MPR-35-Q, T, H, F 1.5 to 4.0 = only nozzles 1.5 - 4.0 can be factory-installed |

I-20 (STAINLESS STEEL) – SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

| 1 Model | 2 Standard Features | 3 Feature Options | 4 Nozzle Options |
|--|---|--|---|
| I-20-04-SS = 4" Pop-up I-20-06-SS = 6" Pop-up | Adjustable arc, stainless steel riser, check valve, 8 standard nozzles, and 4 low-angle nozzles | (blank) = No option NCV = Without check valve (only available on 4" model) R = Drain check valve and reclaimed water ID | Blue 1.5 - 8.0 Gray Low Angle Black Short Radius Green High Flow MPR-25-Q, T, H, F MPR-30-Q, T, H, F MPR-35-Q, T, H, F 1.5 to 4.0 = only nozzles 1.5 - 4.0 can be factory-installed |

Examples:
 I-20-12 - R - 4.0 = 12" Pop-up, adjustable arc, with reclaimed water ID, and 4.0 nozzle



I-20-00
 Overall height: 7¾"
 Exposed diameter: 1¾"
 Inlet size: ¾"



I-20-04
 Overall height: 7½"
 Pop-up height: 4"
 Exposed diameter: 1¾"
 Inlet size: ¾"



I-20-06
 Overall height: 9¾"
 Pop-up height: 6"
 Exposed diameter: 1¾"
 Inlet size: ¾"



I-20-12
 Overall height: 17"
 Pop-up height: 12"
 Exposed diameter: 1¾"
 Inlet size: ¾"

ROTORS