

## **Specification Sheet**

Type:			
Model:			
Project:			

## MODEL: LMR16-LED-4W-F-2700K | 4 WATT MR16 LED LAMP

Compact, low-voltage lamps favored for most outdoor lighting fixtures. Standard 4 watt lamp with 45° degree beam angle. Favored for directional illumination and weather-resistant design, ideal for highlighting landscaping and architectural features with precision. Optimal power efficiency and durability, making them a reliable choice for enhancing outdoor spaces. Produces a gentle, warm light to accent your landscape.

**CONSTRUCTION:** Vented alluminum body and durable black plastic.

**PASSIVE COOLING:** Aluminum heatsink fins. Passive heat exchanger to transfer heat from device LED components to improve device performance and extend its life.

**LED SOURCE:** CREE XPE LED diodes delivers exceptional brightness and energy efficiency, making it an ideal for residential to commercial.

PINS: G4 bi-pin, dual contacts.

WARRANTY: Ten year warranty.

## **DIMENSIONS:**

Height from top of pins to top of lamp	1.56 inches
Width —	2 inches
Bi-Pins Length	0.4375 inches
Ship Weight —	0.12 pounds

## SPECIFICATIONS:

WATTS: 4 watts		
BEAM ANGLE: 45° degrees		
BEAM SPREAD: Flood		
LIGHT OUTPUT: 250 lumens		
COLOR: Warm White		
COLOR TEMPERATURE: 2700K		
OPERATING VOLTAGE: 12 - 14 volts		
<b>CRI</b> : Ra>80		
LED SOURCE: CREE XPE		
HALOGEN EQUIVALENT: 20 watts		
RATED HOURS: 50,000 hours		
AMBIENT OPERATING TEMPERATURE: <72°C		







