

**Best Control
Electronic Pump Controllers**

Features

BEST CONTROL start and stop the water pump according to the users needs. It monitors the water pressure and flow that runs through it and protects the pumps against dangerous working conditions like dry running.

APPLICATIONS

- Flood Suction
- Irrigation
- Water Treatment
- Filtration



FEATURES

- Fixed Starting Pressure
- Dual Voltage
- UL Listed
- Outdoors use (IP65)
- Automatic Restart*
- Anti-Jamming Function*

OTHER BENEFITS

- Easy Installation
- Reduced dimensions
- Constant flow
- No Maintenance
- No need to install pressure tanks
- Can be installed on surface or submersible pumps

TECHNICAL INFORMATION

MODEL	STARTING PRESSURE	VOLTAGE	PH	MAX. AMP.	SUCT.	DISCH.
PCBC 16F16S-22	22 PSI	115/230	1	16	1"	1"
PCBC 16F16S-32	32 PSI	115/230	1	16	1"	1"
PCBC 16F16Q-32	32 PSI	115/230	1	16	1¼"	1¼"
PCBC 16F16S-42	42 PSI	115/230	1	16	1"	1"

* AUTOMATIC RESTART. In case of stopping due to a water shortage, the device will automatically make 10 double attempts to restart over the 24 hours following the failure, each lasting approximately 5 seconds to allow the pump and the system to reload if

possible. The user can try to restart the device at any time by pressing the Restart button. If for any reason the pump remains idle for 24 consecutive hours, the device will start the pump for about 5 seconds.

* ANTI-JAMMING FUNCTION. Pump protection against dry running with automatic reset. Equipped with automatic restart* in case of failure and anti-jamming* function.