



- 01 **Compact:** Get all the benefits of a rotor in a spray-sized package
- 02 **Short Radius:** Get close-in rotor coverage with a 15' minimum radius
- 03 **Reliable:** The PGJ is engineered to take on harsh conditions for years on end

## PGJ ROTOR

### *The PGJ Delivers All the Benefits of a Rotor in a Compact, Spray-Sized Package*

The PGJ was built to bring all the efficient benefits of rotary sprinklers to applications that typically call for a spray. Its many features include a rack of easy-to-install-and-change, water-efficient nozzles, easy arc adjustment, and all the safety and durability that comes with a rubber cover. The PGJ is capable of working in tandem with larger rotors to combine big and small areas in a single zone, offering a convenience and efficiency that sprays do not. When used in the right application, the PGJ allows fewer heads to perform more efficiently at a more economical price.

# PGJ FEATURES & SPECIFICATIONS

## Features

- Models: Shrub, 4", 6", 12"
- Nozzle choices: 8
- Standard factory installed nozzle: 2.0 only
- Through-the-top arc adjustment
- Water lubricated gear-drive
- Arc setting: 40 to 360 degrees
- Nozzle range: 0.75 to 5.0 GPM
- Factory installed rubber cover
- Quick check arc mechanism
- Warranty period: 2 years

## Specifications

- Radius: 15' to 37'
- Flow rate: 0.64 to 5.3 GPM
- Recommended pressure range: 30 to 50 PSI
- Operating pressure range: 20 to 100 PSI
- Precipitation rates: 0.6 in/hr approx.
- Nozzle trajectory: 14 degrees approx.

### PGJ – SPECIFICATION BUILDER: ORDER 1 + 2 + 3

| 1 | Model                      | 2 | Standard Features                  | 3 | Feature Options                                                          |
|---|----------------------------|---|------------------------------------|---|--------------------------------------------------------------------------|
|   | <b>PGJ-00</b> = Shrub      |   | Adjustable arc, 8 standard nozzles |   | <b>(blank)</b> = No option                                               |
|   | <b>PGJ-04</b> = 4" Pop-up  |   |                                    |   | <b>V</b> = Drain check valve                                             |
|   | <b>PGJ-06</b> = 6" Pop-up  |   |                                    |   | <b>R</b> = Drain check valve and reclaimed water ID (pop-up models only) |
|   | <b>PGJ-12</b> = 12" Pop-up |   |                                    |   |                                                                          |

#### Examples:

PGJ-04 = 4" pop-up, adjustable arc

PGJ-06 - V = 6" pop-up, adjustable arc, with drain check valve

PGJ-12 - R = 12" pop-up, adjustable arc, with drain check valve and reclaimed water ID

## Model



### PGJ-00

Overall Height 7"  
Pop-up Height: N/A  
Exposed Diameter: 1½"  
Inlet Size: ½"



### PGJ-04

Overall Height: 7½"  
Pop-up Height: 4"  
Exposed Diameter: 1½"  
Inlet Size: ½"



### PGJ-06

Overall Height: 9½"  
Pop-up Height: 6"  
Exposed Diameter: 1½"  
Inlet Size: ½"



### PGJ-12

Overall Height: 16¾"  
Pop-up Height: 12"  
Exposed Diameter: 1½"  
Inlet Size: ½"

## Advanced Features

### NOZZLES SELF-ALIGN

For easy installation and removal; marked for easy identification.



### PGJ RECLAIMED

Available as a factory-installed option on all models.



### EASILY FINE-TUNE

Nozzle adjustments through the top of the sprinkler with screwdriver or Hunter wrench.



**Website** hunterindustries.com | **Customer Support** 1-800-383-4747 | **Technical Service** 1-800-733-2823

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.

  
Gregory R. Hunter, President of Hunter Industries

