FITTINGS

Fittings: 16-18 mm Dripline

Uses: Barbed and Premium Fittings

BARBED FITTINGS

- Acetal material
- Dual barb provides stronger hold than single barb
- Ideal for use with Eco-Mat®, Eco-Wrap™, PLD
- · Fits 17 mm dripline and tubing
- Brown color to match PLD dripline
- No clamps necessary
- Warranty period: 1 year

OPERATING SPECIFICATIONS

• Maximum pressure: 60 PSI

FITTINGS



PLD-075 34" MPT x 17 mm Barb



PLD-050 ½" MPT x 17 mm Barb



PLD-ELB 17 mm Barb Elbow



PLD-CPL 17 mm Barb Coupling



PLD-CAP 17 mm Barb x ½" MPT with Cap



PLD-TEE 17 mm Barb Tee



PLD-075-TBTEE 17 mm Barb Tee x ¾" Thread



PLD-BV 17 mm Barb Shut-off Valve



PLD-AVR ½" Air/Vacuum Relief Valve

PLD-LOC

- · High quality glass-filled polypropylene
- Easy push-on installation, threads lock it into place
- Easier and faster than other fittings
- Fits multiple sizes of dripline and tubing (Inside diameter range from 0.520" to 0.620")
- Brown color blends in with dripline and landscape
- · Reusable and ideal for drip irrigation maintenance
- Warranty period: 2 years

OPERATING SPECIFICATIONS

Maximum pressure: 60 PSI

FITTINGS



PLD-LOC 075 34" Male Pipe Thread x Loc



PLD-LOC 050 ½" Male Pipe Thread x Loc



PLD-LOC ELB Locking Elbow



PLD-LOC CPLLocking Coupler



PLD-LOC CAP End Cap x Loc



PLD-LOC TEELocking Tee



PLD-LOC FHS 34" Female Hose Swivel x Loc