

PRS40

PRESSURE REGULATED

Models: **Shrub, 4", 6", 12"**
Pressure Regulation: **40 PSI**

FEATURES

- Models: Shrub, 4", 6", 12"
- Gray identification cap for easy field ID
- Innovative directional flush plug design
- 6" and 12" models come standard as no side inlet, ensuring proper installation with check valve
- Drain check valve installed (14' of elevation) comes standard
- Warranty period: 5 years
- ▶ Co-molded wiper seal
- ▶ Heavy-duty spring
- ▶ Industry's strongest spray body
- ▶ Innovative seal design
- ▶ Pro-Spray check valve
- ▶ Pressure regulated to 40 PSI

OPERATING SPECIFICATIONS

- Operational pressure range: 15 to 100 PSI

FACTORY INSTALLED OPTIONS

- Reclaimed water ID cap

USER INSTALLED OPTIONS

- Reclaimed water ID cap (P/N 458562)
- Snap-on reclaimed cover (P/N PROSRCCAP)
- ▶ = *Advanced Feature descriptions on page 50*



PRS40 Reclaimed

PRS40 models include optional factory-installed purple reclaimed caps



Related Solutions: MP Rotator

PRS40 is designed specifically for the MP Rotator®



PROS-00-PRS40
Retracted height: 4½"
Inlet size: ½"



PROS-04-PRS40-CV
Retracted height: 5⅞"
Pop-up height: 4"
Exposed diameter: 2¼"
Inlet size: ½"



PROS-06-PRS40-CV
Retracted height: 8¾"
Pop-up height: 6"
Exposed diameter: 2¼"
Inlet size: ½"



PROS-12-PRS40-CV
Retracted height: 16⅞"
Pop-up height: 12"
Exposed diameter: 2¼"
Inlet size: ½"

PRS40 - SPECIFICATION BUILDER: ORDER 1 + 2

1 Model	2 Options
PROS-00-PRS40 = 40 PSI regulated shrub adapter	(blank) = No option
PROS-04-PRS40 = 40 PSI regulated 4" Pop-up	CV = Factory-installed drain check valve
PROS-06-PRS40 = 40 PSI regulated 6" Pop-up	<i>(Pop-up models only)</i>
PROS-12-PRS40 = 40 PSI regulated 12" Pop-up	R = Factory-installed reclaimed body cap
	<i>(Shrub molded in purple)</i>

Examples:

- PROS-04-PRS40 - CV = 4" Pop-up regulated at 40 PSI, drain check valve
- PROS-06-PRS40 - CV = 6" Pop-up regulated at 40 PSI, drain check valve
- PROS-12-PRS40 - CV - R = 12" Pop-up regulated at 40 PSI, drain check valve, reclaimed body cap