

- FINISH GRADE/TOP OF MULCH
- QUICK COUPLER VALVE: BUCKNER MODEL QB
- VALVE BOX WITH COVER
- PVC SCH 80 NIPPLE (AS REQD LENGTH)
- 3-INCH MINIMUM DEPTH OF 3/4-INCH WASHED GRAVEL
- BRICK (1 OF 2)
- PVC SCH 40 ELL
- PVC SCH 40 TEE OR ELL
- PVC MAINLINE PIPE
- PVC SCH 40 ELL
- (1) 2" X 2" REDWOOD STAKE WITH STAINLESS STEEL GEAR CLAMPS OR EQUIVALENT SUPPORT SYSTEM

NOTE: FURNISH FITTINGS AND PIPING TO BE SIZED PER THE NOMINAL QUICK COUPLING VALVE INLET SIZE

<u></u>	Ą	우	부	D,	
SCALE:	APPVD BY: SC	CHKD BY: DS	DRWN BY: AES	DATE: 05-06-2013	
	BY:	÷Υ	BY:	05-0	
N.T.S	SC	DS	AES)6–2ເ	
)13	ck
	<u> </u>	:		PART NO.	ne
		1		⊢ N	, kost
	INSTALLATION	{ t	Z Z		(3)
	ALL				Ç
න	ATI		NTRTF/		MA
QB B	Ż		<u>П</u>		
	<u> </u>				🛪
	PIECE	L			
	ĆE,	-	\triangleright	REV	