# ROAM

#### Range: **Up to 1,000 ft.** *Type:* **Remote**

## **FEATURES**

- Works with Hunter X-Core<sup>®</sup>, Pro-C<sup>®</sup>, PCC, ICC2, I-Core<sup>®</sup> and ACC controllers through a SmartPort<sup>®</sup> connection
- 128 programmable addresses for use of multiple Roam remotes in the same neighborhood
- Manually run watering cycles without modifying regular program
- Programmable run times: 1 to 90 minutes
- Range: 1000' (line of sight)
- Warranty: 2 years

### **REMOTE SPECIFICATION**

- Transmitter power source: 4 AAA batteries included
- Receiver power source: 24 VAC, from controller through
  a SmartPort connector
- System operating frequency: 433 MHz band
- SmartPort connector can be mounted up to 50' (max.) from controller
- FCC approved: No FCC license required



**Transmitter and Receiver** Height: 7" Width: 2¼" Depth: 114"



Hunter remotes require

SmartPort wiring harness. The SmartPort is a connector that is wired to the terminals on the controller, and allows quick connection to any Hunter receiver.

the installation of a

SmartPort



Wall Mount Bracket for SmartPort P/N 258200

ROAM	
Model	Description
ROAM-KIT	Transmitter, receiver, SmartPort wiring harness, and 4 AAA batteries included
ROAM-TR	Transmitter unit and 4 AAA batteries included
ROAM-R	Receiver unit

#### **OPTIONS (SPECIFY SEPARATELY)**

Model	Description
ROAM-WH	SmartPort wiring harness (length: 6' pack of 50)
ROAM-SCWH	Shielded SmartPort wiring harness (length: 25')
258200	Wall Mount Bracket for SmartPort