

Specifications

	Walk-Behind	Pre-Wet Systems					AccuSpray™		
	SL-80 SL-80SS	PWS-100	PWS-175	PWS-225	PWX-200	PWX-250	VSS-1000	VSS-2000	VSS-3000
Empty Weight	60 lb (27.2 kg)	45 lb (20.4 kg)	150 lb (68.0 kg)	350 lb (158.8 kg)	170 lb (77.1 kg)	200 lb (90.7 kg)	172 lb (78.0 kg)	450 lb (204.1 kg)	520 lb (235.9 kg)
Overall Length	48" (121.9 cm)	34" (86.4 cm)	22" (55.9 cm)	55" (139.7 cm)	93.75" (238.1 cm)	105.25" (267.3 cm)	60" (154.4 cm)	88" (223.5 cm)	94" (238.8 cm)
Overall Height	33" (83.8 cm)	17" (43.2 cm)	35" (88.9 cm)	26" (66.0 cm)	25.3" (64.3 cm)	32" (81.3 cm)	50" (127.0 cm)	64" (162.6 cm)	68" (172.7 cm)
Overall Width	28" (71.1 cm)	11" (27.9 cm)	32" (81.3 cm)	30" (76.2 cm)	15.75" (40.0 cm)	14.6" (37.2 cm)	48" boom (121.9 cm)	82" boom (208.3 cm)	82" boom (208.3 cm)
Floor Length		N/A			144" (365.8 cm)	155" (393.6 cm)	45" (114.3 cm)	74" (188.0 cm)	80" (203.2 cm)
Floor Width		N/A			88" (223.5 cm)	94" (238.8 cm)	32" (81.3 cm)	36" (91.4 cm)	39" (99.1 cm)
Tank Length	—	N/A			89" (226.1 cm)	100" (254.0 cm)	37" (94.0 cm)	47" (119.4 cm)	60" (152.4 cm)
Tank Width	—	N/A			16" (40.6 cm)	13.5" (34.3 cm)	30" (76.2 cm)	37" (94.0 cm)	42" (106.7 cm)
Capacity	12 gal (45.4 L)	30 gal (113.6 L)	75 gal (283.9 L)	225 gal (851.7 L)	200 gal (757.1 L)	250 gal (946.3 L)	100 gal (378.5 L)	200 gal (757.1 L)	300 gal (1,135.6 L)
Spraying Width	Up to 48" (121.9 cm)	Pre-wet only	Pre-wet/anti-icing		Pre-wet only		6' (1.8 m)	Up to 25' (7.6 m)	
Spraying Volume	1 gal/min (3.8 L/min)	2 gal/min (7.6 L/min)	5 gal/min (18.9 L/min)		2 gal/min (7.6 L/min)	2 gal/min (7.6 L/min)	4' (1.2 m) boom	8' (2.4 m) boom	
							20 gal (75.7 L) per acre at 10 mph (16.1 km/h)	20 gal (75.7 L) per lane mile/acre at 10 mph (16.1 km/h)	

	Rotary Broom
	SS-4000
Empty Weight	238 lb (108.0 kg)
Overall Length	72" (182.9 cm) 80" (203.2 cm) including snow blade
Overall Height	42.5" (108.0 cm)
Overall Width	40" (101.6 cm)
Brush Width	40" (101.6 cm)
Snow Blade Width	40" (101.6 cm) 37" (94 cm) angled
Speed	2.7 mph (4.35 km/h)
Engine	HONDA®

	Liqui Maxx™			
	TSA-300	TSA-500	TSA-750	TSA-1250
Empty Weight	320 lb (145.2 kg)	475 lb (215.5 kg)	740 lb (335.7 kg)	860 lb (390.1 kg)
Overall Length (w/pump)	101" (256.5 cm)	112" (284.5 cm)	118" (299.7 cm)	119" (302.3 cm)
Overall Height	24" (60.9 cm)	48" (121.9 cm)	55" (139.7 cm)	73" (185.4 cm)
Overall Width	48" (121.9 cm)	59" (149.9 cm)	75" (190.5 cm)	85" (215.9 cm)
Capacity	300 gal (1,135.6 L)	500 gal (1,892.7 L)	750 gal (2,839.1 L)	1,250 gal (4,731.7 L)
Suggested Gross Vehicle Weight Rating (GVWR) (lb)*	8,500-10,000 lb	14,000-16,000 lb	16,000-19,500 lb	19,500-26,000 lb
Vehicle Class	Class 2B	Class 4	Class 5	Class 6

	Standard (HFS-100)	Deluxe (HFD-200)
	Pump Frame	Powder coated steel with fork pockets
Pump	Wet-Seal 210 gal/min (794.9 L/min) centrifugal circulation pump	
Motor	Sealed 5.5 hp HONDA®	
Control	On/Off 1-zone	Automatic 3-zone controlled flow (GPS optional)

	PBA-300
Overall Width	98" (248.9 cm)
Spray Width (boom only)	8' (0.305 m)
Spray Width (w/wing sprayer)	Adjustable, up to 24' (7.32 m)
Mounting	2" receiver mount
Spraying Capacity	10 to 60 gal/acre depending on vehicle speed

	Brine Maker
	Brine Pro™ 2000
Empty Weight	1,520 lb (680.4 kg)
Overall Length	100" (254.0 cm)
Overall Height	89" (226.0 cm)
Overall Width	86" (218.4 cm)
Mixing Tank	265 gal (1,003.0 L)
Brine Tank	285 gal (1,078.8 L)
Hopper Volume	1 cu yd of salt (0.765 cu m)
Brine Production	Up to 1,050 gal/h (Up to 3,974.7 L/h)
Inlet Flow Rate	Up to 15 gal/min (56.8 L/min)
Electrical Connection	220 VAC, 50 A service, single phase

	Brine Storage Tanks	
	VTA-300	VTA-500
Empty Weight	550 lb (249.5 kg)	1,300 lb (589.7 kg)
Overall Height	120" (304.8 cm)	156" (396.2 cm)
Overall Width	90" (228.6 cm)	102" (259.1 cm)
Total Capacity	3,000 gal (11,356.2 L)	5,000 gal (18,927.1 L)

All SnowEx products are covered by a 2-year warranty. Visit snowexproducts.com for details. Specifications subject to change without prior notice. *Verify your vehicle meets the size and weight requirements.