


Mailing Address: P.O. Box 1674 Warsaw, IN 46581-1674 Phone: 844.SEYMOUR Fax: 574-267-8508 www.SeymourMidwest.com Shipping Address: 2666 S. Country Club Rd. Warsaw, IN 46580

# Roller Squeegee Double-Ribbed Style Assembly Instructions



1/2" wrench

### Parts Shipped with Unit:

- Head assembly
- Aluminum handle (not pictured)
- Wrap-around brace (set of 2)
- Bolt bag
- Hook hardware bag

If Roller Squeegee comes <u>without</u> a protective cardboard tube, proceed to Handle Instructions.

If Roller Squeegee comes <u>with</u> a protective cardboard tube, follow these instructions:

- 1. <u>DO NOT</u> attempt to remove the tube by cutting.
- 2. On one end of roller, using a 1/2" wrench, remove the hex head bolt, loc washer and axle.
- 3. Slide off cardboard tube.
- 4. Replace axle, loc washer, and bolt as shown. Tighten.

### Handle Instructions:

- 1. Insert flat-tipped end of handle into channel-shaped crossbar. NOTE: This may be a tight fit requiring working the handle back and forth.
- 2. Align holes and insert middle sized bolt. Do not tighten until all hardware is in place.
- 3. Place hanging hook on label side of handle. Hook should be positioned so squeegee can be hung, with roller head up, for drying or storing.

### Wrap-Around Brace Instructions:


- 1. Align holes of flat end of braces with holes on head assembly and insert the two shortest bolts.
- 2. Align holes of wrap-around end of braces with the handle, as shown, and insert the longest bolt.
- 3. Start all loc nuts on bolts. Use wrenches to tighten, being careful not to over-tighten. Over-tightening may result in crushing the handle, thereby compromising its strength.

#### FULL WARRANTY

All Midwest Rake products carry a full warranty against manufacturer defects in quality and workmanship. Products which have been abused or worn out from normal use are excluded from this warranty. We reserve the right to replace or issue credit on an individual basis









## **ROLLER SQUEEGEE REPLACEMENT PARTS LIST**

(Double-Ribbed)

- SA30017 Frame Assembly 24"
- SA30024 Frame Assembly 36"
- SA30027 Frame Assembly 48"
- SA10047 Roller 24" w/end caps (non-absorbent)
- SA10048 Roller 36" w/end caps (non-absorbent)
- SA10049 Roller 48" w/end caps (non-absorbent)
- SA10050 Roller 36" w/end caps (poly foam)
- SA10051 Roller 36" w/end caps (PVA)
- SA30001 Braces wrap around (set)
- SA20209 Handle 60" bent aluminum blue powder coated with 5" green vinyl grip
- SP50003 Grip 5" green vinyl
- RM50027 Axle- 1/2" stainless steel
- RM60025 Bolt 5/8" stainless steel
- RM60026 Loc washer stainless steel
- SA60000 Bolt bag: 4 bolts, 4 loc nuts
- SA60075 Hardware Bag: 1 hook, 1 bolt, 1 loc nut