

Specifications

	Utility			Tailgate Pro		Bulk Pro™		Tow Pro™		Drop Pro™	Precision Pro	V-Maxx™ - Dump Box		V-Pro™	
	SP-100 SP-125	SR-210 SP-225	SP-325	SP-575X	SP-1075X	SP-1575	SP-1875	SP-7000	SP-1225G	SD-600 SD-1400	SP-1675	SP-2200	SP-2400	SP-2000	SP-3000 SP-6000
Empty Weight	75 lb (34.0 kg) 65 lb (29.5 kg)	68 lb (30.8 kg)	79 lb (35.8 kg)	106 lb (48.1 kg)	141 lb (63.9 kg)	160 lb (72.6 kg)	180 lb (81.7 kg)	985 lb (446.8 kg)	190 lb (86.2 kg)	175 lb (79.4 kg) 375 lb (170.1 kg)	290 lb (131.5 kg)	353 lb (160.1 kg)	326 lb (147.9 kg)	280 lbs (127.0 kg)	386 lb (175.1 kg) 416 lb (188.7 kg)
Overall Length	22" (55.9 cm)		18" (45.7 cm)	20.5" (52.1 cm)	21" (53.3 cm)	20.5" (52.1 cm)	24" (60.9 cm)	128" (325.1 cm)	30" (76.2 cm) excl. trailer tongue	24" (61.0 cm) 30" (76.2 cm)	30" (76.2 cm)	18" (45.7 cm)	14" (35.6 cm)	64" (162.6 cm)	77" (195.6 cm)
Overall Height	30" (76.2 cm)	32" (81.3 cm)	33" (83.8 cm)	35" (88.9 cm)	40" (101.6 cm)	34" (86.4 cm)	36" (91.4 cm)	60" (152.4 cm)	30" (76.2 cm)	28" (71.1 cm) 38" (96.5 cm)	30" (76.2 cm)	20" (50.8 cm)	24" (60.9 cm)	27" (68.6 cm)	27" (68.6 cm) 36" (91.4 cm)
Overall Width	30" (76.2 cm)		33" (83.8 cm)	38" (96.5 cm)	52" (132.1 cm)	38" (96.5 cm)	52" (132.1 cm)	64" (162.6 cm)	44" (111.8 cm)	49.5" (125.7 cm) 60" (152.4 cm)	49.5" (125.7 cm)	96" (243.8 cm)	84" (213.4 cm)	48.5" (123.2 cm)	
Floor Length	N/A										N/A		45" (114.3 cm)	58" (147.3 cm)	
Floor Width	N/A										N/A		34" (86.4 cm)	58" (147.3 cm)	
Hopper Length	22" (55.9 cm)		16.5" (41.9 cm)	20.5" (52.1 cm)	21" (53.3 cm)	20.5" (52.1 cm)	21" (53.3 cm)	78" (198.1 cm)	N/A	20.25" (51.4 cm) 24.25" (61.6 cm)	20" (50.8 cm)	17" (43.2 cm)		53" (134.6 cm)	66" (167.6 cm)
Hopper Width	30" (76.2 cm)		33" (83.8 cm)	38" (96.5 cm)	47.5" (120.7 cm)	38" (96.5 cm)	47" (119.4 cm)	48" (124.5 cm)	N/A	48" (121.9 cm) 59.4" (150.8 cm)	48" (121.9 cm)	95.5" (242.6 cm)	84" (213.4 cm)	48.5" (123.2 cm)	48.5" (123.2 cm)
Capacity ¹	3.0 cu ft (0.085 cu m)/240 lb (108.9 kg)		3.25 cu ft (0.092 cu m) 260 lb (117.9 kg)	5.75 cu ft (0.163 cu m) 460 lb (208.7 kg)	10.75 cu ft (0.304 cu m) 880 lb (399.1 kg)	5.25 cu ft (0.149 cu m) 420 lb (190.5 kg)	9.0 cu ft (0.254 cu m) 720 lb (326.6 kg)	1.5 cu yd (1.07 cu m) 3,240 lb (1,469.6 kg)	12.0 cu ft (0.3 cu m) 960 lb (435.5 kg)	6.0 cu ft (0.169 cu m) 480 lb (217.7 kg) 14.0 cu ft (0.395 cu m) 1,120 lb (508.0 kg)	6.0 cu ft (0.169 cu m) 480 lb (217.7 kg)	N/A		0.4 cu yd (0.3 cu m) 880 lb (399.2 kg)	0.5 cu yd (0.4 cu m) 1,080 lb (489.9 kg) 1.0 cu yd (0.8 cu m) 2,160 lb (979.8 kg)
Spreading Width	Up to 20" (6.0 m)	Up to 25" (7.6 m)		Up to 40" (12.2 m)		Up to 30" (9.2 m)	Up to 40" (12.2 m)	Up to 30" (9.2 m)	Up to 40" @ 5 mph (12.2 m @ 8 km/h)	36" (91.4 cm) 48" (121.9 cm)	4" to 12" (1.2 to 3.7 m)	Up to 40" (12.2 m)		Up to 30" (9.1 m)	Up to 40" (12.2 m)
Mounting	2" (5.1 cm) receiver hitch is standard			Pivot, receiver or 3-point mount optional		2" (5.1 cm) receiver hitch is standard	Pivot, receiver or 3-point mount optional	Integral trailer	Integral trailer	Category 1, 3-point mount standard (SD-1400 only)	Integrated 3-point mount standard with optional receiver and utility mounts	Universal mounting kit to fit most dump bodies (some fabrication required)*		Positive locking mount with bolt-down kit and ratchet-strap assist	

	V-Maxx™				Super Maxx™ II			Walk-Behind		
	SP-7550	SP-8500 SP-8500H SP-8550	SP-9300	SP-9500	SP-9300X SP-9300XH	SP-9500X SP-9500XH	SP-9800X SP-9800XH	SP-65	SP-85 SP-85SS	SD-95 SD-95SS
Empty Weight	550 lb (249.5 kg)	780 lb (353.8 kg)	939 lb (425.9 kg)	994 lb (450.8 kg)	989 lb (448.6 kg)	1,044 lb (473.6 kg)	1,100 lb (499.0 kg)	25 lb (11.3 kg)	42 lb (19.1 kg)	55 lb (24.9 kg)
Overall Length	89.5" (227.3 cm)	105.5" (268.0 cm)	108" (274.3 cm)	130" (330.2 cm)	144" (365.6 cm)	155" (393.6 cm)		50" (127.0 cm)	52" (132.1 cm)	48" (121.9 cm)
Overall Height	34" (86.4 cm)	39" (99.1 cm)	43" (109.2 cm)	45.5" (115.6 cm)	43" (109.2 cm)	45" (114.3 cm)	55" (139.6 cm)	28" (71.1 cm)	33" (83.8 cm)	36" (91.4 cm)
Overall Width	49" (124.5 cm)	48" (121.9 cm)	54" (137.2 cm)	52" (132.1 cm)	54" (137.1 cm)		66" (167.6 cm)	26" (66.0 cm)	29" (73.7 cm)	38.25" (97.2 cm)
Floor Length	66" (167.6 cm)	84" (213.4 cm)	100" (254.0 cm)	106" (269.2 cm)	113" (287 cm)	122" (309.9 cm)		N/A		
Floor Width	44" (111.8 cm)	44" (111.8 cm)	49.5" (125.7 cm)	49" (124.5 cm)	54" (137.1 cm)		66" (167.6 cm)	N/A		
Hopper Length	78" (198.1 cm)	96" (243.8 cm)	107.5" (273.1 cm)	118.5" (301.0 cm)	108" (274.3 cm)	120" (304.8 cm)	120" (304.8 cm)	18" (45.7 cm)	20" (50.8 cm)	13" (33.0 cm)
Hopper Width	49" (124.5 cm)	48" (121.9 cm)	54" (137.2 cm)	52" (132.1 cm)	54" (137.2 cm)	54" (137.2 cm)	66" (167.6 cm)	23" (58.4 cm)		30" (76.2 cm)
Capacity ¹	Struck 1.5 cu yd (1.2 cu m) Rounded 1.8 cu yd (1.4 cu m)	Struck 2.2 cu yd (1.8 cu m) Rounded 2.5 cu yd (2.0 cu m)	3.2 cu yd (2.6 cu m)	4.2 cu yd (3.4 cu m)	Struck 3.2 cu yd (2.6 cu m) Rounded 3.5 cu yd (2.8 cu m)	Struck 4.2 cu yd (3.4 cu m) Rounded 4.5 cu yd (3.6 cu m)	Struck 6.0 cu yd (4.8 cu m) Rounded 6.5 cu yd (5.2 cu m)	100 lb (45.4 kg)	160 lb (72.6 kg)	
Spreading Width	Up to 40" (12.2 m)									
Mounting	Positive locking mount with bolt-down kit and ratchet-strap assist				Truck bed mounted with tie-down straps and controls			N/A		

	Rotary Broom
	SS-4000
Empty Weight	238 lb (108.0 kg)
Overall Length	72" (182.9 cm) 80" (203.2 cm) including snowblade
Overall Height	42.5" (108.0 cm)
Overall Width	40" (101.6 cm)
Brush Width	40" (101.6 cm)
Snow Blade Width	40" (101.6 cm) 37" (94 cm) angled
Speed	2.7 mph (4.35 km/h)
Engine	HONDA®

¹ Material weight equates to approximately 2,000 lb/cu yd or 80 lb/cu ft (1 bag of rock salt). All SnowEx products are covered by a 2-year warranty. Visit snowproducts.com for details. Specifications subject to change without prior notice.
*No low profile. Distance of overhang from hinge pins cannot exceed 18 inches.