

# ECHO<sup>®</sup>

Ask Any Pro!<sup>™</sup>

## 225 SERIES TRIMMERS

Powerful Performance in a New Look

**5** year  
Consumer  
Warranty

5 year consumer, 1 year commercial  
and 90 day rental warranty.

TRIMMERS



- 21.2cc Power Boost Vortex<sup>™</sup> Engine Provides Plenty of Trimming Power
- i-30<sup>™</sup> Technology Reduces Starting Effort by 30%
- Built-in Arm Rest and Spark Plug Protector for Added Comfort and Durability
- Commercial-Duty Air Filtration System Provides Long Engine Life
- Available in a Variety of Configurations

[www.echo-usa.com](http://www.echo-usa.com)

# 225 SERIES TRIMMERS



Ask Any Pro!™

The 225 Series of Trimmers features a whole new look to the 21.2cc engine and is available in a variety of configurations: Standard with an i-30™ starter (SRM-225 and GT-225), with an i-75™ starter (SRM-225i and GT-225i), split boom (SRM-225SB), or "U"-handle (SRM-225U). Common features to all include: a 21.2cc Power Boost Vortex™ engine for plenty of trimming power, i-30™ technology to reduce starting effort by 30%, a built-in arm rest and spark plug protector for added comfort and durability, and a commercial-duty air filtration system to provide long engine life.



5 year consumer, 1 year commercial and 90 day rental warranty.



A powerful, smooth-running 21.2cc Power Boost Vortex™ engine provides plenty of trimming power.



Rubber over molded grip provides comfortable all day operation.



The U Turn™ trimmer head, equipped with .095" diameter Cross-Fire® line, reloads in seconds (available on SRM series only).



## TRIMMER SPECIFICATIONS

\* Includes cutting head, excludes harness \*\* Without cutting head, includes shield

Model	Engine Displacement (cc)	Carburetor (w/Purge Pump)	Fuel Capacity (fl. oz.)	Shaft Length (in)	Shaft Type	Starting System	Cutting Head	Cutting Swath (in)	Shield	Drive Shaft	Nylon Line (in dia)	Dry Weight (lb)*	Dry Weight (lb)**
GT-200R	21.2	Rotary	15.2	48	Curved	i-30™	Rapid-Loader™	16	Std. GT	4-Layer Cable	.080 Cross-Fire®	9.3	8.8
GT-200i	21.2	Rotary	15.2	48	Curved	i-75™	Rapid-Loader™	16	Std. GT	4-Layer Cable	.080 Cross-Fire®	9.6	8.8
GT-225	21.2	Rotary	14.9	48	Curved	i-30™	Rapid-Loader™	16	Std. GT	4-Layer Cable	.080 Cross-Fire®	10.2	9.7
GT-225i	21.2	Rotary	14.9	48	Curved	i-75™	Rapid-Loader™	16	Std. GT	4-Layer Cable	.080 Cross-Fire®	10.5	9.7
GT-251	25.4	Diaphragm	14.2	52	Curved	i-30™	Rapid-Loader™	16	Std. GT	Flexible	.080 Cross-Fire®	10.4	9.9
SRM-210	21.2	Rotary	15.2	59	Straight	i-30™	ECHOMATIC Pro™	17	Std. SRM	4-Layer Cable	.095 Cross-Fire®	11.4	10.6
SRM-210i	21.2	Rotary	15.2	59	Straight	i-75™	Rapid-Loader™	17	Std. SRM	4-Layer Cable	.095 Cross-Fire®	11.6	10.9
SRM-210SB	21.2	Rotary	15.2	59	Split Shaft	i-30™	ECHOMATIC Pro™	17	Std. SRM	4-Layer Cable	.095 Cross-Fire®	11.9	11.1
SRM-210U	21.2	Rotary	15.2	59	Straight	Standard	ECHOMATIC Pro™	17	Std. SRM	4-Layer Cable	.095 Cross-Fire®	12.9	12.1
SRM-225	21.2	Rotary	14.9	59	Straight	i-30™	U Turn™	17	Std. SRM	4-Layer Cable	.095 Cross-Fire®	12.1	11.3
SRM-225i	21.2	Rotary	14.9	59	Straight	i-75™	U Turn™	17	Std. SRM	4-Layer Cable	.095 Cross-Fire®	12.4	11.6
SRM-225SB	21.2	Rotary	14.9	59	Split Shaft	i-30™	U Turn™	17	Std. SRM	4-Layer Cable	.095 Cross-Fire®	12.9	12.1
SRM-225U	21.2	Rotary	14.9	59	Straight	i-30™	U Turn™	17	Std. SRM	4-Layer Cable	.095 Cross-Fire®	13.6	12.8
SRM-230	22.8	Rotary	19.6	59	Straight	Standard	ECHOMATIC Pro™	17	Std. SRM	4-Layer Cable	.095 Cross-Fire®	12.2	11.4
SRM-230S	22.8	Rotary	19.6	59	Straight	Standard	ECHOMATIC Pro™	17	Std. SRM	Steel	.095 Cross-Fire®	12.0	11.2
SRM-230U	22.8	Rotary	19.6	59	Straight	Standard	ECHOMATIC Pro™	17	Std. SRM	Steel	.095 Cross-Fire®	13.2	12.4
SRM-251	25.4	Diaphragm	14.2	59	Straight	i-30™	ECHOMATIC Pro™	17	Std. SRM	Flexible	.095 Cross-Fire®	11.3	10.5
SRM-260	25.4	Rotary	19.6	59	Straight	Standard	ECHOMATIC Pro™	17	Std. SRM	4-Layer Cable	.095 Cross-Fire®	12.5	11.1
SRM-260S	25.4	Rotary	19.6	59	Straight	Standard	ECHOMATIC Pro™	17	Std. SRM	Steel	.095 Cross-Fire®	12	10.7
SRM-261T	25.4	Rotary	19.6	59	Straight	Standard	ECHOMATIC	17	Std. SRM	4-Layer Cable	.095 Cross-Fire®	12.8	10.9
SRM-265	25.4	Diaphragm	16.9	59	Straight	i-30™	ECHOMATIC Pro™	17	Std. SRM	4-Layer Cable	.095 Cross-Fire®	13.4	12.3
SRM-265S	25.4	Diaphragm	16.9	59	Straight	i-30™	ECHOMATIC Pro™	17	Std. SRM	Steel	.095 Cross-Fire®	12.9	12.1
SRM-265T	25.4	Diaphragm	16.9	59	Straight	i-30™	ECHOMATIC Pro™	17	Std. SRM	4-Layer Cable	.095 Cross-Fire®	13.7	12.7
SRM-265U	25.4	Diaphragm	16.9	59	Straight	i-30™	ECHOMATIC Pro™	17	Std. SRM	4-Layer Cable	.095 Cross-Fire®	14.4	13.5
SRM-280	28.1	Diaphragm	21.6	59	Straight	Standard	ECHOMATIC Pro™	17	Std. SRM	4-Layer Cable	.095 Cross-Fire®	13.5	12.6
SRM-280S	28.1	Diaphragm	21.6	59	Straight	Standard	ECHOMATIC Pro™	17	Std. SRM	Steel	.095 Cross-Fire®	13.4	12.5
SRM-280T	28.1	Diaphragm	21.6	59	Straight	Standard	ECHOMATIC Pro™	17	Std. SRM	4-Layer Cable	.095 Cross-Fire®	13.6	12.7
SRM-280U	28.1	Diaphragm	21.6	59	Straight	Standard	ECHOMATIC Pro™	17	Std. SRM	4-Layer Cable	.095 Cross-Fire®	14.5	13.6