

# TRIMMERS



# **Performance!**

What more can be said about the world's finest professional-grade trimmers? ECHO's easy-to-use custom ergonomic controls, lightweight design, and powerful 2-stroke engines provide the tools to enhance productivity. Spend less time creating a lasting impression and more time enjoying it! All ECHO Trimmers are backed by a 5-year consumer and a 2-year commercial warranty.



## ECHO TRIMMER FEATURES AND BENEFITS

- A Tool-less air filter cover for easy access
- Commercial-grade felt air filtration for long engine life
- **C 2-stage commercial-grade air filtration** for long engine life
- I-30<sup>™</sup> starting system for reduced effort starting
- E i-75™ starting system for reduced effort starting
- Digital ignition system for easy starting
- **G** Purge bulb for easy starting
- H New cylinder/piston plating for increased engine life

- **I** Lined clutch for smooth engagement and less slippage
- **I** Ergonomic throttle handle with rubber grip for comfort
- K Ergonomic, adjustable front handle for a custom fit
- **Debris shield with integrated cut-off knife** for optimal line length
- **M** Engine vibration-reduction system for operator comfort
- **N** Extra heavy-duty vibration-reduction system for operator comfort
- Speed-Feed<sup>®</sup> 400 cutting head for easy reloading
- **P** High-capacity Speed-Feed® cutting head for larger line diameters



### STRAIGHT SHAFT TRIMMERS

# SRM-225

#### ECHO's best-selling trimmer is also the most fuel efficient.

- 21.2 cc professional-grade, 2-stroke engine
- 59" straight shaft
- Speed-Feed<sup>®</sup> 400 head

#### ABDFGIJK

# **SRM-225**i

#### A Speed-Feed<sup>®</sup> head and i-75<sup>™</sup> starting technology.

- 21.2 cc professional-grade, 2-stroke engine
- 59" straight shaft
- Speed-Feed® 400 head

#### ABEFGIJ



#### Outstanding power, durability, and performance.

- · 22.8 cc professional-grade, 2-stroke engine
- 59" straight shaft
- Speed-Feed® 400 head

#### A B F G I J K L NO

# RM-266

#### **Powerful performance and** superior design.

- 25.4 cc professional-grade, 2-stroke engine
- 59" straight shaft
- · High-capacity Speed-Feed® head

#### ACDFGIJ KLNP

# 2992

#### A solid steel drive shaft improves acceleration and reduces weight.

- 25.4 cc professional-grade, 2-stroke engine
- 59" straight shaft
- High-capacity Speed-Feed<sup>®</sup> head

#### ACDEGIJ KONP



## RM-266T

#### **Incredible power with 50%** more torque.

- 25.4 cc professional-grade, 2-stroke engine
- 59" straight shaft
- High-capacity Speed-Feed® head

#### ACDFGIJ KLNP

# SRM-280

#### A new class of performance.

- 28.1 cc professional-grade, 2-stroke engine
- 59" straight shaft
- High-capacity Speed-Feed<sup>®</sup> head

#### ACFGIJ KLNP

# 805

#### A solid steel drive shaft improves acceleration and reduces weight.

- 28.1 cc professional-grade, 2-stroke engine
- 59" straight shaft

• High-capacity Speed-Feed® head

#### AFGIKLP



# RM-280T

ECHO's top choice with 50% more torque.

- 28.1 cc professional-grade, 2-stroke engine
- 59" straight shaft
- High-capacity Speed-Feed® head

#### AFGIKLP











#### **Trimmer Specifications**

| Model    | Engine Disp.<br>(cc) | Carburetor<br>(w/Purge<br>Pump) | Fuel<br>Capacity<br>(fl. oz.) | Shaft<br>Length<br>(in) | Shaft Type | Starting<br>System | Cutting Head          | Cutting<br>Swath<br>(in) | Shield   | Drive Shaft   | Arbor<br>(mm) | Nylon Line<br>(in dia) | Dry<br>Weight<br>(lb)* | Dry<br>Weight<br>(lb)** |
|----------|----------------------|---------------------------------|-------------------------------|-------------------------|------------|--------------------|-----------------------|--------------------------|----------|---------------|---------------|------------------------|------------------------|-------------------------|
| GT-225   | 21.2                 | Rotary                          | 14.9                          | 48                      | Curved     | i-30™              | Rapid-Loader™         | 16                       | Std. GT  | 4-Layer Cable | -             | .080 Cross-Fire®       | 10.1                   | 9.6                     |
| GT-225i  | 21.2                 | Rotary                          | 14.9                          | 48                      | Curved     | i-75™              | Rapid-Loader™         | 16                       | Std. GT  | 4-Layer Cable | -             | .080 Cross-Fire®       | 10.6                   | 10.1                    |
| GT-225SF | 21.2                 | Rotary                          | 14.9                          | 48                      | Curved     | i-30™              | Speed-Feed® 400       | 16                       | Std. GT  | 4-Layer Cable | -             | .080 Cross-Fire®       | 10.6                   | 10.1                    |
| GT-225L  | 21.2                 | Rotary                          | 14.9                          | 55                      | Curved     | i-30™              | Speed-Feed® 400       | 16                       | Std. GT  | 4-Layer Cable | -             | .080 Cross-Fire®       | 11.2                   | 9.96                    |
| SRM-225  | 21.2                 | Rotary                          | 14.9                          | 59                      | Straight   | i-30™              | Speed-Feed® 400       | 17                       | Std. SRM | 4-Layer Cable | 20            | .095 Cross-Fire®       | 12                     | 11.1                    |
| SRM-225i | 21.2                 | Rotary                          | 14.9                          | 59                      | Straight   | i-75™              | Speed-Feed® 400       | 17                       | Std. SRM | 4-Layer Cable | 20            | .095 Cross-Fire®       | 12.5                   | 11.6                    |
| SRM-230  | 22.8                 | Rotary                          | 19.1                          | 59                      | Straight   | Standard           | Speed-Feed® 400       | 17                       | Std. SRM | 4-Layer Cable | 20            | .095 Cross-Fire®       | 12.2                   | 11.3                    |
| SRM-266  | 25.4                 | Rotary                          | 16.9                          | 59                      | Straight   | i-30™              | High-Cap. Speed-Feed® | 17                       | Std. SRM | 4-Layer Cable | 20            | .095 Cross-Fire®       | 13.4                   | 12.5                    |
| SRM-266S | 25.4                 | Rotary                          | 16.9                          | 59                      | Straight   | i-30™              | High-Cap. Speed-Feed® | 17                       | Std. SRM | Solid Steel   | 20            | .095 Cross-Fire®       | 13.1                   | 12.2                    |
| SRM-266T | 25.4                 | Rotary                          | 16.9                          | 59                      | Straight   | i-30™              | High-Cap. Speed-Feed® | 17                       | Std. SRM | 4-Layer Cable | 20            | .095 Cross-Fire®       | 13.6                   | 12.8                    |
| SRM-280  | 28.1                 | Rotary                          | 21.1                          | 59                      | Straight   | Standard           | High-Cap. Speed-Feed® | 17                       | Std. SRM | 4-Layer Cable | 20            | .095 Cross-Fire®       | 13.4                   | 12.5                    |
| SRM-280S | 28.1                 | Rotary                          | 21.1                          | 59                      | Straight   | Standard           | High-Cap. Speed-Feed® | 17                       | Std. SRM | Solid Steel   | 20            | .095 Cross-Fire®       | 13.1                   | 12.2                    |
| SRM-280T | 28.1                 | Rotary                          | 21.1                          | 59                      | Straight   | Standard           | High-Cap. Speed-Feed® | 17                       | Std. SRM | 4-Layer Cable | 20            | .095 Cross-Fire®       | 13.5                   | 12.8                    |

\*with cutting head and shield \*\*without cutting head or shield

# Convenience of Cordless... the Power of ECHO!

The DSRM-200 Grass Trimmer has all the conveniences of a cordless unit, but built with the power of ECHO know-how. With gas-like performance, the DSRM-200 will make quick (and environmentally-clean) work of any trimming job and has all the power needed to cut through thick grass and weeds.

# **DSRM-200**

#### 36V grass trimmer.

- · 36V DC motor provides more cutting power than lower voltage alternatives
- 94 watt hour Lithium Ion battery provides extended run time
- Hi-low speed switch provides optimized cutting time
- Dual .080" diameter line with 12" cutting swath provides greater cutting efficiency
- Speed-Feed® 400 cutting head provides easy line reloading without disassembly, tap to advance line feeding, and holds up to 20' of trimmer line
- Narrow debris shield for increased visibility while cutting
- Foam cushioned front handle and rubber grip throttle handle for more comfort and control

#### **Cordless Trimmer Specifications**

| Model    | Voltage<br>(v) | Cutting Head       | Cutting<br>Swath (in) | Shield               | Drive<br>Shaft | Nylon Line<br>(in dia) | Dry Weight<br>(lb)* |
|----------|----------------|--------------------|-----------------------|----------------------|----------------|------------------------|---------------------|
| DSRM-200 | 36             | Speed-Feed®<br>400 | 12                    | Standard<br>Cordless | Solid Steel    | .080 SilenTwist        | 11                  |

\*with cutting head, excludes harness

# ITHIUM/ION



Battery LBC-360



Battery Charger 99944200802



