



## SRM-266 SERIES TRIMMERS

- 25.4 cc Power Boost Vortex™ Engine for Plenty of Power
- i-30™ Technology Reduces Starting Effort by 30%
- Larger 2-stage Commercial Air Filter for Improved Filtration and Even Longer Engine Life
- Upgraded Chrome Cylinder Plating Process for Improved Longevity in Harsh Conditions
- Rubber Handles Provide a Comfortable Grip
- 59" Straight Shaft with Flex Cable Drive (SRM-266S Features a Solid Steel Shaft)
- Pro-Torque™ Version Available with 50% More Torque at the Cutting Head (SRM-266T)
- High Capacity Speed-Feed® Head Reloads in Seconds Without Disassembly



5 year consumer, 2 year commercial,  
and 90 day rental warranty.

Visit [www.echo-usa.com/5year](http://www.echo-usa.com/5year) to learn more.



## SRM-266 SERIES TRIMMERS

The SRM-266 Trimmer series features a powerful 25.4 cc Power Boost Vortex™ engine for environmentally clean performance, rubber left and right handle grips for comfortable all day operation, i-30™ technology to reduce starting effort by 30%, a larger 2-stage commercial air filter for improved filtration and even longer engine life and upgraded chrome cylinder plating process for improved longevity in harsh conditions.

SRM-266  
Shown

16.9 fl oz  
capacity see-  
through fuel tank

i-30™ starting  
technology

25.4 cc Power Boost  
Vortex™ engine

Rubber throttle  
control

Larger 2-stage  
commercial air  
filtration

5 year consumer, 2 year  
commercial, and 90 day  
rental warranty

Heavy-duty gear  
case with sealed  
bearings

Speed-Feed® Head Reloads  
in Seconds Without Disassembly



A powerful, smooth-running  
25.4 cc Power Boost Vortex™  
engine provides plenty of  
power.



A rubber throttle handle  
provides comfortable all day  
operation. The left hand grip  
is also rubber-coated.



Model	Engine Displacement (cc)	Carburetor (w/Purge Pump)	Fuel Capacity (fl oz)	Shaft Length (in)	Shaft Type	Starting System	Cutting Head	Cutting Swath (in)	Shield	Drive Shaft	Cross-Fire® Nylon Line (in dia.)	Dry Weight* (lb)	Dry Weight** (lb)
GT-225	21.2	Rotary	14.9	48	Curved	i-30™	Rapid-Loader™	16	Std. GT	4-Layer Cable	.095	10.1	9.6
GT-225i	21.2	Rotary	14.9	48	Curved	i-75™	Rapid-Loader™	16	Std. GT	4-Layer Cable	.095	10.6	10.1
GT-230	22.8	Rotary	19.1	52	Curved	Standard	Speed-Feed®	16	Std. GT	4-Layer Cable	.095	11.5	10.5
SRM-225	21.2	Rotary	14.9	59	Straight	i-30™	Speed-Feed®	17	Std. SRM	4-Layer Cable	.095	12	11.2
SRM-225i	21.2	Rotary	14.9	59	Straight	i-75™	Speed-Feed®	17	Std. SRM	4-Layer Cable	.095	12.5	11.7
SRM-230	22.8	Rotary	19.1	59	Straight	Standard	Speed-Feed®	17	Std. SRM	4-Layer Cable	.095	12.2	11.2
SRM-266	25.4	Rotary	16.9	59	Straight	i-30™	High Capacity Speed-Feed®	17	Std. SRM	4-Layer Cable	.095	13.4	12.5
SRM-266S	25.4	Rotary	16.9	59	Straight	i-30™	High Capacity Speed-Feed®	17	Std. SRM	Solid Steel	.095	13.1	12.2
SRM-266T	25.4	Rotary	16.9	59	Straight	i-30™	High Capacity Speed-Feed®	17	Std. SRM	4-Layer Cable	.095	13.6	12.8
SRM-280	28.1	Rotary	21.1	59	Straight	Standard	ECHOMATIC™	17	Std. SRM	4-Layer Cable	.095	13.4	12.5
SRM-280S	28.1	Rotary	21.1	59	Straight	Standard	ECHOMATIC™	17	Std. SRM	Solid Steel	.095	13.1	12.2
SRM-280T	28.1	Rotary	21.1	59	Straight	Standard	ECHOMATIC™	17	Std. SRM	4-Layer Cable	.095	13.5	12.8

\*Includes cutting head, exclude harness  
\*\* Without cutting head, includes shield