



Count on it.

# Super Funny Pipe

## Pipe Fittings and Flex-Assemblies

### CONTROLLERS

This unique piping acts like an extension cord, allowing you to put sprinklers exactly where you want them. Even deep-seated high-pops are easy to install in difficult, hard-to-trench locations.



Super Funny Pipe

#### Features

- Provides easy installation for problem areas
- Cushions sprinklers from external impact
- Connects to sprinklers and Toro fittings
- Flexible, thick-walled polyethylene pipe
- 30.5m (100') coils available in stretch wrap

#### Specifications

- Wall thickness: 2.5mm (.10") ± .01
- Inside diameter: 12.4mm (.49") ± .01
- Outside diameter: approximately 18mm (.70")

#### Super Funny Pipe

- 850-23 6m (20') length working pressure: 8.2 Bar (120 PSI)
- 850-24 15.2m (50') coil working pressure: 8.2 Bar (120 PSI) (36Kg)
- 850-25 30.5m (100') coil working pressure: 8.2 Bar (120 PSI) (68Kg) (more flexible)


#### Fittings

To be used only with Toro Super Funny Pipe

- 850-20 Coupling
- 850-31 13mm (1/2") Male Elbow
- 850-32 20mm (3/4") Male Elbow
- 850-33 20-13mm (3/4"-1/2") Female Adapter
- 850-34 13mm (1/2") Female Elbow
- 850-35 13mm (1/2") Male Adapter
- 850-36 20mm (3/4") Male Insert 3/4" x 3/8"
- 850-37 Tee Barbed inserts require no clamps.



Super Funny Pipe Fittings



One of the most useful and time-saving sprinkler installation aids is Toro Super Funny Pipe. Whether you are installing a new system or replacing an old sprinkler, Super Funny Pipe can make your job faster and easier.

Super Funny Pipe is a high-strength poly tubing that solves tough sprinkler installation and replacement problems. Simply put, it acts as a flexible extension cord between the water line and the sprinkler, allowing you to position sprinklers easily where you need them—even in hard-to-reach areas.

Super Funny Pipe Friction Loss – Metric				
LPM Flow				
5	10	15	20	25
0,30	1,02	2,00	3,77	5,58

Note: This chart indicates the amount of pressure loss (in kPa) per meter of Super Funny Pipe installed at stated flow rates (LPM).

Super Funny Pipe Friction Loss – English						
GPM Flow						
1	2	3	4	5	6	7
0.01	0.02	0.06	0.09	0.15	0.21	0.27

Note: This chart indicates the amount of pressure loss (PSI) per foot of Super Funny Pipe installed at stated flow rates (GPM).

Super Funny Pipe Fittings Friction Loss Chart – Metric						
LPM Flow						
Model No.	Description	5	10	15	20	25
850-31	13mm Male Elbow	1,87	6,43	13,8	28,7	46,9
850-32	20mm Male Elbow	2,23	7,42	17,8	37,1	61,4
850-34	13mm Female Elbow	1,87	6,43	13,8	28,7	46,9
850-35	13mm Male Adapter	0,89	3,08	6,89	16,1	28,2
850-36	20mm Male Adapter	1,35	4,13	9,55	21,8	37,7

Note: This chart indicates the amount of pressure loss (in kPa) per meter of Super Funny Pipe at stated flow rates (LPM).

Super Funny Pipe Fittings Friction Loss Chart – English								
GPM Flow								
Model No.	Description	1	2	3	4	5	6	7
850-31	1/2" Male Elbow	0.05	0.15	0.36	0.62	1.13	1.62	2.37
850-32	3/4" Male Elbow	0.06	0.18	0.41	0.80	1.42	2.20	3.05
850-34	1/2" Female Elbow	0.05	0.15	0.36	0.62	1.13	1.62	2.37
850-35	1/2" Male Adapter	0.03	0.06	0.18	0.31	0.60	1.00	1.41
850-36	3/4" Male Adapter	0.04	0.10	0.23	0.43	0.80	1.37	1.86

Note: This chart indicates the amount of pressure loss (PSI) per foot of Super Funny Pipe at stated flow rates (GPM).

# Super Funny Pipe Flex Assemblies

Make installation easier with Toro's new flex assemblies. 13mm (1/2") and 20mm (3/4") fittings conveniently pre-assembled onto 200mm (8") and 300mm (12") lengths of Toro Super Funny Pipe.

## Features

- Flexible yet durable segments of Toro Super Funny Pipe with factory pre-installed fittings
- Allows sprinkler heads to be moved or adjusted to grade easily
- Perfect for hard to trench areas
- Prevents damage to sprays, rotors or pipes, especially when run over by vehicles or equipment
- Available in 20 cm or 30 cm (8" or 12") lengths with 13mm or 20mm (1/2" or 3/4") fittings
- Packaged in a re-sealable bag for convenience on the job site

## Specifications

- Wall thickness: 2.5mm (.10") ± .01
- Inside diameter: 12.4mm (.49") ± .01
- Outside diameter: approximately 18mm (.70")
- Recommended operating pressure: 1.7 – 5.2 Bar (25 – 75 PSI)
- Maximum operating pressure: 5.9 Bar (85 PSI)
- Models:
  - SPFA-585: 20 cm (8") length with 13mm x 13mm (1/2" x 1/2") fittings
  - SPFA-5875: 20 cm (8") length with 13mm x 20mm (1/2" x 3/4") fittings
  - SPFA-5125: 30 cm (12") length with 13mm x 13mm (1/2" x 1/2") fittings
  - SPFA-51275: 30 cm (12") length with 13mm x 20mm (1/2" x 3/4") fittings



Flex Assemblies

## Specifying Information

Specifying Information			
SPFA 5X X X X			
Description	Inlet Fitting	Length	Outlet Fitting
SPFA—Super Funny Pipe Flex Assembly	5—13mm (1/2")	8—20cm (8") 12—30cm (12")	5—13mm (1/2") fitting 75—20mm (3/4") fitting
For Example: When specifying a Super Funny Pipe Flex Assembly that is 30 cm (12") in length and has a 13mm (1/2") inlet fitting and a 20 mm (3/4") outlet fitting, you would specify: <div style="text-align: center; background-color: #cccccc; padding: 2px;">SPFA-51275</div>			



**Count on it.**

Worldwide Headquarters  
 The Toro Company  
 8111 Lyndale Avenue South  
 Bloomington, MN 55420  
 Phone: 952-888-8801  
 Fax: 952-887-7265  
[www.toro.com](http://www.toro.com)

GB Form Number: 200-xxxx  
 ©2005 The Toro Company – All Rights Reserved.