WAC LIGHTING

WL-LED120

Step And Wall Light

Fixture Type:

Catalog Number:

Project:

Location:

Model & Voltage	Color Temp & CRI	Lumens	Finish
O WL-LED120 120 VAC	O Amber 90 O 3000K 90	36	O BK Black on Aluminum O BZ Bronze on Aluminum O WT White on Aluminum

Example: WL-LED120-C-WT

For custom requests please contact customs@waclighting.com

DESCRIPTION

WAC Lighting Step and Wall Lights are designed to seamlessly blend into any architecture featuring a sleek interchangeable magnetic faceplate with no visible hardware. These luminaires offer enhanced energy-efficient functionality and optimized light output to adequately illuminate stairs, walls and walkways with little or no glare. Light engine is IP66 sealed for both indoor and outdoor applications.

FEATURES

- · Louvered design offers shielded illumination
- · Magnetized design for easy installation and maintenance
- Low profile, flush to wall aesthetics with no visible hardware
- 5 year warranty

SPECIFICATIONS

Color Temp: Amber,3000K
Input: 120 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10% Rated Life: 50000 Hours

Mounting: Fits into 2" x 4" J-Box with minimum inside

dimensions of 3"L x 2"W x 2.5"D

Standards: ETL, cETL,IP66,Title 24 JA8 Compliant

Wet Location Listed

Construction: Die-cast corrosion resistant aluminum alloy

REPLACEMENT PARTS


W-4051-120-BK - LED120 Cover Plate BK W-4051-120-BZ - LED120 Cover Plate BZ W-4051-120-WT - LED120 Cover Plate WT



FINISHES:

Bronze on White on Black on Aluminum Aluminum Aluminum

LINE DRAWING:



WAC LIGHTING

WL-LED120

Step And Wall Light

Fixture Type:	
Catalog Number:	
Project:	_
Location:	

Model & Voltage	Color Temp & CRI	Lumens	Finish
O WL-LED120F 277 VAC	O Amber 90 O 3000K 90	36	O BK Black on Aluminum O BZ Bronze on Aluminum O WT White on Aluminum

Example: WL-LED120F-C-WT

For custom requests please contact customs@waclighting.com

DESCRIPTION

WAC Lighting Step and Wall Lights are designed to seamlessly blend into any architecture featuring a sleek interchangeable magnetic faceplate with no visible hardware. These luminaires offer enhanced energy-efficient functionality and optimized light output to adequately illuminate stairs, walls and walkways with little or no glare. Light engine is IP66 sealed for both indoor and outdoor applications.

FEATURES

- Louvered design offers shielded illumination
- Magnetized design for easy installation and maintenance
- Low profile, flush to wall aesthetics with no visible hardware
- 5 year warranty

SPECIFICATIONS

 Color Temp:
 3000K,Amber

 Input:
 277 VAC,50/60Hz

CRI: 90

Rated Life: 50000 Hours

Mounting: Fits into 2" x 4" J-Box with minimum inside

dimensions of 3"L x 2"W x 2.5"D

Standards: ETL, cETL,IP66

Wet Location Listed

Construction: Die-cast corrosion resistant aluminum alloy



FINISHES:

Bronze on White on Black on Aluminum Aluminum Aluminum

LINE DRAWING:

REPLACEMENT PARTS

W-4051-120-BK - LED120 Cover Plate BK W-4051-120-BZ - LED120 Cover Plate BZ W-4051-120-WT - LED120 Cover Plate WT