

LED HARDSCAPE WITH ALL THE FEATURES YOU NEED







2700 + 3 + 3000

7122-27/30 12 inches

7182-27/30 18 inches

12V

- Quick Release connection at fixture to easily detach after installation
- Integral Brightness control
- Select Color Temperature in the field
- Capstone bracket after installation
- · Corrosion-resistant aluminum alloy
- Factory-sealed water tight fixture
- Transformer required (sold separately)

6", 12", 18"

5¼", 11¼", 17¼"

- Tightly spaced and diffused LEDs for even illumination
- 6' lead wire and direct burial gel-filled wire nuts included

0


0 . 0

· Patents pending

9-15VAC Input: Lumens:

0 . 0 .

Up to 350 lm Rated Life: 50,000 hours





7062-27/30 6 inches



7032* 3 inches * Due to its compact size, the 7032 is dedicated in either 2700K or 3000K.

See photometric data on page 112





3"





Length	Model	Color Temp	Wattage	Max Lumens	Finishes
3"*	7032-27 7032-30	2700K Warm White* 3000K Pure White*	1.5W, 2.5VA	50	BZ Bronze on Aluminum GH Graphite SD Sand
6"	7062-27/30	2700K Warm White 3000K Pure White	4.5W, 5.6VA	110	BZ Bronze on Aluminum BBR Bronze on Brass GH Graphite SD Sand
12"	7122-27/30	2700K Warm White 3000K Pure White	7.0W, 7.3VA	230	BZ Bronze on Aluminum BBR Bronze on Brass GH Graphite SD Sand
18"	7182-27/30	2700K Warm White 3000K Pure White	8.5W, 8.5VA	350	BZ Bronze on Aluminum GH Graphite SD Sand

Example: 7182-27/30SD