

WL-LED120

Step And Wall Light

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Voltage	Color Temp & CRI	Lumens	Finish
O WL-LED120 120 VAC	O Amber 90O 3000K 90	36 36	O BK Black on Aluminum O BZ Bronze on Aluminum
○ WL-LED120F 277 VAC	O Amber 90 O 3000K 90	36 36	O WT White on Aluminum

Example: WL-LED120-AM-BK

DESCRIPTION

WAC Lighting Step and Wall Lights are designed to seamlessly blend into any architecture featuring a sleek interchangeable magnetic faceplate with no visible hardware. These luminaires offer enhanced energy-efficient functionality and optimized light output to adequately illuminate stairs, walls and walkways with little or no glare. Light engine is IP66 sealed for both indoor and outdoor applications.

FEATURES

- Louvered design offers shielded illumination
- Magnetized design for easy installation and maintenance
- Low profile, flush to wall aesthetics with no visible hardware
- 5 year warranty

SPECIFICATIONS

Construction: Die-cast corrosion resistant aluminum alloy

Power: 3.5W, 3W

Input: 277 VAC, 50/60Hz, 120 VAC

Dimming: , ELV: 100-10%
Light Source: Integrated LED
Rated Life: 50000 Hours

Mounting: Fits into 2" x 4" J-Box with minimum inside dimensions of

3"L x 2"W x 2.5"D

Finish: Enamel Coated: White on Aluminum, Bronze on

Aluminum, Black on Aluminum, Enamel Coated: Black on

Aluminum, White on Aluminum

Operating Temp: $-40^{\circ}\text{F to }104^{\circ}\text{F }(-40^{\circ}\text{C to }40^{\circ}\text{C})$

Standards: ETL, cETL, Wet Location Listed, IP66, ADA, Title 24 JA8

Compliant

REPLACEMENT PARTS

W-4051-120-BK - LED120 Cover Plate BK W-4051-120-BZ - LED120 Cover Plate BZ W-4051-120-WT - LED120 Cover Plate WT



FINISHES:



LINE DRAWING:

