

WL-LED140

Step And Wall Light

	Fixture Type:
-	Catalog Number:
	Project:
•	Location:
	•

Model & Voltage	Color Temp & CRI	Lumens	Finish
O WL-LED140 120 VAC	O Amber 90O 3000K 90	3 3	O BK Black on Aluminum O BZ Bronze on Aluminum
O WL-LED140F 277 VAC	→ Amber 90→ 3000K 90	3	O WT White on Aluminum

Example: WL-LED140-AM-BK

DESCRIPTION

WAC Lighting Step and Wall Lights are designed to seamlessly blend into any architecture featuring a sleek interchangeable magnetic faceplate with no visible hardware. These luminaires offer enhanced energy-efficient functionality and optimized light output to adequately illuminate stairs, walls and walkways with little or no glare. Light engine is IP66 sealed for both indoor and outdoor applications.

FEATURES

- Geometric design with downward illumination
- Magnetized design for easy installation and maintenance
- Low profile, flush to wall aesthetics with no visible hardware
- 5 year warranty

SPECIFICATIONS

Construction: Die-cast corrosion resistant aluminum alloy Power: 3.5W, 3W

Input: 120 VAC, 50/60Hz, 277 VAC

Dimming: ELV: 100-10%,
Light Source: Integrated LED
Rated Life: 50000 Hours

Mounting: Fits into 2" x 4" J-Box with minimum inside dimensions of

3"L x 2"W x 2.5"D

Finish: Enamel Coated: Black on Aluminum, White on Aluminum,

Bronze on Aluminum, Enamel Coated: White on

Aluminum, Black on Aluminum


Operating Temp: $-40^{\circ}\text{F to }104^{\circ}\text{F }(-40^{\circ}\text{C to }40^{\circ}\text{C})$

Standards: ETL, cETL, Wet Location Listed, IP66, Title 24 JA8


Compliant, ADA

REPLACEMENT PARTS

W-4091-140-BK - LED140 Cover Plate BK W-4091-140-BZ - LED140 Cover Plate BZ W-4091-140-WT - LED140 Cover Plate WT



FINISHES:



LINE DRAWING:

