

WAC LIGHTING

Rubix

Wall Mount 3000K

Fixture Type:

Catalog Number:

Project:

Location:

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
○ WS-W2509 10" - 1 Light ○ WS-W2510 10" - 2 Lights	○ 3000K 90 ○ 3000K 90	16W 30W	805 1385	○ AL Brushed Aluminum ○ BK Black ○ BZ Bronze ○ GH Graphite ○ WT White

Example: **WS-W2509-AL**

DESCRIPTION

Available in single and twin light configurations, this die-cast aluminum LED wall luminaire is Wet Location listed for a broad range of exterior lighting applications. Designed with asquare profile, this version of Rubix mounts upwards or downwards.

FEATURES

- 2509 Single, 2510 Double
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction:	Die-cast Aluminum
Power:	16W, 30W
Input:	120-277V, 50/60Hz
Dimming:	ELV: 100-10% , 0-10V: 100-5%
Light Source:	Integrated LED
Rated Life:	70000 Hours
Mounting:	Mounts directly to junction box, Can be mounted on wall in all orientations
Finish:	Powder Coat Bronze:Bronze, Powder Coat Bronze::Brushed Aluminum, Powder Coat Bronze::Black, Powder Coat Bronze:::White, Powder Coat Bronze:::Graphite, Powder Coat White:White, Powder Coat White::Black, Powder Coat White:::Brushed Aluminum, Powder Coat White:::Graphite, Powder Coat White:::Bronze
Operating Temp:	-40°F to 122°F (-40°C to 50°C)
Standards:	UL, cUL, Wet Location Listed, IP65, Title 24 JA8 Compliant, ADA



FINISHES:



LINE DRAWING:

